

WELL NO : 7119/12-1

COORDINATES: 71 DEG. 06'08.00" N
19 DEG. 47'40.29" E

SEISM. LOC.: 738424 SP 484

LICENSEE : STATOIL/ESSO/HYDRO

LICENSE NO : 060

PERMIT NO : 251

RIG : ROSS RIG

CONTRACTOR : ROSS DRILLING CO. A/S

BOTTOM HOLE TEMPERATURE: 96 °C

OPERATOR: STATOIL

SPUD CLASSIFICATION : WILDCAT

COMPL. CLASSIFICATION: P&A GAS/CONDENSATE DISCOVERY

FORMATION AT TD : TRIASSIC

PRODUCING FORMATION :


TOTAL DEPTH (MSL) : 3063 M

WATER DEPTH : 200 M

ELEVATION KB : 25 M

SPUD DATE : 14.06.80

COMPL. DATE: 10.10.80



REMARKS:

CASINGS AND LEAK-OFF TESTS					
TYPE	CASING DIAM. inches	DEPTH BELOW KB m	HOLE DIAM. inches	DEPTH BELOW KB m	L.O.T MUD EQV. g/cm3
CONDUCTOR	30	262	36	263	
SURF. COND.	20	575	26	590	1.10
INTERM.	13 3/8	1526	17 1/2	1540	1.68
INTERM.	9 5/8	2479	12 1/4	2491	1.80
LINER	7		8 1/2		

CONVENTIONAL CORES			
CORE NO	INTERVALS CORED m	RECOVERY	
		m	%
1	2667.0 - 2674.0	5.7	82
2	2674.0 - 2675.0	0.2	22
3	2675.5 - 2678.0	2.3	92
4	2680.0 - 2685.0	5.2	94
5	2700.0 - 2714.0	12.7	90
6	2714.0 - 2715.0	0.8	75
7	2718.0 - 2736.3	18.3	100
8	2736.3 - 2754.0	17.4	96
9	2754.0 - 2772.0	18.0	100
10	2772.0 - 2790.0	18.0	100
11	2810.0 - 2828.9	18.9	100
12	2828.5 - 2846.0	17.2	99
13	2924.0 - 2975.0	12.3	96
14	2984.0 - 3002.0	17.6	98

MUD PROPERTIES				
DEPTH BELOW KB m	WEIGHT g/cm3	FUNNEL VISC. sec	FILTRATE LOSS cm3	REMARKS
275	1.04	55		
575	1.08			
615	1.10	49		
1020	1.11	43		
1335	1.20	49		
1685	1.21	50		
20075	1.20	45		
2550	1.25	51		
2580	1.32	49		
2870	1.28	57		

AVAILABLE LOGS			
LOG TYPE	INTERVALS	1/200	1/500
ISF/SONIC/GR	225 - 613	X	
ISF/SONIC/MSFL/GR	600 - 1566	X	
ISF/SONIC/MSFL/GR	1551 - 2513	X	
ISF/SONIC/MSFL/GR	2504 - 2791	X	
ISF/SONIC/MSFL/GR	2700 - 3004	X	
ISF/SONIC/MSFL/GR	2900 - 3092	X	
ISF/SONIC/MSFL/GR	225 - 3092		X ¹
FDC/GR	600 - 1567	X	
FDC/CNL/GR	1551 - 2514	X	
FDC/CNL/GR	2504 - 2792	X	
FDC/CNL/GR	2739 - 3006	X	
FDC/CNL/GR	2950 - 3092	X	
FDC/CNL/GR	600 - 3092		X ²
LSS/GR	287 - 612	X	X
LSS/GR	600 - 1567	X	X
LSS/GR	1551 - 2513	X	X
LSS/GR	2504 - 3092	X	X
DLL/MSFL/GR	2504 - 3006	X	X
DLL/MSFL/GR	2950 - 3088	X	X
CDM	600 - 3092	X	
CDM-AP	2504 - 3092	X	X
RFT	Tests 1-14	1:100	
Temp Log	235 - 2200	1:1000	
CBL/GR	225 - 1551	X	X
CBL/VDL/GR	1000 - 3054	X	X
Mud	250 - 3092		X
Velocity	225 - 3092	1:1000	X

¹ MSFL not run above 600 m.
² CNL not run above 1551 m.

DRILL STEM TESTS											
TEST NO	FLOW NO	DEPTH BELOW KB	CHOKE SIZE mm	RECOVERY						PRESS. (psi)	
				OIL Sm ³ /day	GAS M Sm ³ /day	OIL GRAV. g/cm ³	GAS GRAV. rel. air	GOR m ³ /m ³	OTHER FLUIDS/REMARKS	FSIP	FFP
		NONE									

DRILL BIT CUTTINGS AND WET SAMPLES		
SAMPLE TYPE	INTERVAL BELOW KB	NUMBER OF SAMPLES
CUTTINGS	290 - 3091	396
WET SAMPLES	295 - 3088	560

SHALLOW GAS	
DEPTH INTERVAL m KB	REMARKS
	NONE

GEOLOGICAL TOPS

WELL : 7119/12-1

	Depth m (RKB)
Quaternary	
T-7	0 - 465
Tertiary	
T-6	465 - 810
T6-3	465 - 539
T6-2	539 - 629
T6-1	629 - 810
Cretaceous	
T-5	810 - 1055
T-4	1055 - 2497
T4-4	1055 - 2136
T4-3/T4-2	2136 - 2440
T4-1 ?	2440 - 2497
Jurassic	
T4-1 ?	2497 - 2526
T-2	2526 - 2610
T3-2	2526 - 2610
T-2	2610 - 3088
T2-5	2610 - 2814
T2-4	2814 - 3007
T2-3	3007 - 3088

TD = 3088