



AVAILABLE LOGS			
LOG TYPE	INTERVALS	1/200	1/500
GR	125 - 215	X	
ISF LSS GR	215 - 1010	X	
ISF SONIC	961 - 2646	X	
ISF SONIC	2633 - 3571	X	
ISF LSS	3210 - 3736	X	
ISF SONIC	3721 - 4185	X	
ISF SONIC	215 - 4185		X
FDC CNL	961 - 2643	X	
FDC CNL	2633 - 3737	X	
FDC CNL	3721 - 4173	X	
FDC CNL	961 - 4173		X
CDM	2633 - 3738	X	
CDM	3720 - 4049	X	
CDM AP	2633 - 3739	X	X
CDM AP	3721 - 4050	X	X
RFT (TEST:1-2)		X	
TEMPERATURE	50 - 3725	1:1000	
DEVIATION SURVEY	3721 - 4189		X
TELECO M.W.D.	3550 - 2740	X	X
MUD	215 - 4285		X
VELOCITY (L.T.S.)	215 - 4185	1:1000	X

(Air Gun Well Velocity Survey & C.L.D. 1stk)  
(Synthetic Seismogram Marine, 10cm/s, 1stk)  
(Synthetic Seismogram, b/p-w/t, 10sm/s, 2stk)  
(Two Way Travel Time log, 10cm/s 1stk)  
(VSP, 10cm/s, b/p-w/t, proc:july-81, 10stk)  
M.W.D. = Measurement while drilling.

MUD PROPERTIES				
DEPTH BELOW KB	WEIGHT	FUNNEL	FILTRATE	REMARKS
m	g/cm3	VISC. sec	LOSS cm3	
220	1.04	53		PER HOUR
400	1.04	53	60	
800	1.03	27		
970	1.04	27		
1250	1.10	47		
1690	1.30	46		
1840	1.26	47		
2650	1.56	48		
3010	1.63	50		
3390	1.69	45		
3750	1.96	85		
4000	1.99	55		
4200	2.03	51		

DRILL BIT CUTTINGS AND WET SAMPLES		
SAMPLE TYPE	INTERVAL BELOW KB	NUMBER OF SAMPLES
CUTTINGS	860 - 4513	936
WET SAMPLES	220 - 4813	990

SHALLOW GAS	
DEPTH INTERVAL m KB	REMARKS
337 - 340	A COUPLE OF THIN GASCHARGED LAYERS NOT THICKER THAN 1 M.

