

WELL NO 1/9-3

CASINGS				
TYPE	DIAM inches	DEPTH BELOW KB m	HOLE DIAM inches	DEPTH BELOW KB m
COND	36	163	44	170
SFC	20	434	26	445
INT	16	1345	19 1/2	1360
INT	13 3/8	2761	17 1/2	2771
INT	9 5/8	3830	12 1/4	3835
LINER			8 1/2	4570

AVAILABLE LOGS			
TYPE	INTERVAL m	1/200	1/500
IEL /	164 - 2770	x	x
BHC			
Sonic	2703 - 4208	x	x
IEL	410 - 1350	x	x
"	3823 - 4561	x	x
DL	3062 - 3350	x	x
FDC	433 - 4563	x	x
FDC /			
CNL	2730 - 4209	x	x
CNL /			
GR	425 - 1350		x
CNL /			
GR	3823 - 4562	x	x
CDM	164 - 2772	x	
"	1300 - 2769	x	
"	3821 - 4565	x	
CDM ap	3821 - 4565		x
T	62 - 1455	x	x
"	375 - 3791		x
"	1040 - 2555	x	x
CNL /			
CCL	2900 - 3500	x	
GR /			
CCL	2800 - 3850	x	
CBL	300 - 1346	x	
"	280 - 1454	x	
CBL /			
VDL	1200 - 2700	x	
CBL /			
VDL	2200 - 3822	x	

CONVENTIONAL CORES				
NO	INTERVAL m	RECOVERY		
		m	QUALITY	%
1	3053.0-3066.7	12.3		90
2	3066.7-3082.5	15.8		100
3	3105.3-3123.5	17.3		98
4	3164.6-3173.1	5.8		68
5	3173.1-3191.8	5.6		30
6	3191.8-3208.3	15.8		96
7	3208.3-3214.9	5.8		87
8	3214.9-3233.5	18.5		99

TESTS					
TYPE	NO	INTERVAL m	RECOVERY	FSIP psi	FFP psi
DST	1	3205 - 3214	19 mm ch, 29.5 SM ³ water, no HC		
"	2	3157 - 3180	9.5 mm ch, 7.9 SM ³ oil, 4.8 M SM ³ gas, 34 ^o API		
"	3	3126 - 3125	2.5 - 3.0 SM ³ WPD traces of oil and gas		
"	4	3094 - 3112	19 mm ch, 397.5 SM ³ oil, 648.4 m SM ³ gas, 50 ^o API		
			0.71 rel air after 2 acid frac.		

REMARKS

WELL NO 1/9-3

CASINGS				
TYPE	DIAM inches	DEPTH BELOW KB m	HOLE DIAM inches	DEPTH BELOW KB m
COND				
SFC				
INT				
INT				
INT				
LINER				

CONVENTIONAL CORES				
NO	INTERVAL m	RECOVERY		
		m	QUALITY	%

AVAILABLE LOGS			
TYPE	INTERVAL m	1/200	1/500
CBL /			
VDL	2700 - 3500	x	
CBL /			
VDL	2740 - 3212	x	
SRS	433 - 4560	1/1000	x
Mud	170 - 4570		x

TESTS					
TYPE	NO	INTERVAL m	RECOVERY	FSIP psi	FFP psi

REMARKS