

WELL NO 2/1-2

CASINGS				
TYPE	DIAM inches	DEPTH BELOW KB m	HOLE DIAM inches	DEPTH BELOW KB m
COND	30	169.4	36	174
SFC	20	557.3	26	562
INT	13 3/8	2225.7	17 1/2	2231
INT	9 5/8	3138.0	12 1/4	3140
INT			8 1/2	3551
LINER				

AVAILABLE LOGS			
TYPE	INTERVAL m	1/200	1/500
ISF-			
Sonic	90 - 502	x	x
ISF-			
Sonic	450 - 2235	x	x
ISF/			
Sonic	2228 - 3145	x	x
ISF/			
Sonic	3138 - 3555	x	x
B	556 - 1542	x	
FDC/			
CNL	2445 - 3144	x	x
FDC/			
CNL	3125 - 3555	x	x
CDM	3132 - 3285	x	
" ap	3151 - 3274		x
" pp	3146 - 3274		
T	1413 2350	x	x
CBL	170 - 700	x	x
SRS	90 - 3555		x
Mud	90 - 3555		x

CONVENTIONAL CORES				
NO	INTERVAL m	RECOVERY		
		m	QUALITY	%
1	3318.0-3336.2	18.2		100

TESTS					
TYPE	NO	INTERVAL m	RECOVERY	FSIP psi	FFP psi

REMARKS