

## WELL NO 15/5-1

CASINGS				
TYPE	DIAM inches	DEPTH BELOW KB m	HOLE DIAM inches	DEPTH BELOW KB m
COND	30	194	36	194.5
SFC	20	705	26	712
INT	13 3/8	2722	17 1/2	2738
INT	8 5/8	3497	12 1/4	3511
INT				
LINER	7	3766	8 3/8	3775

AVAILABLE LOGS			
TYPE	INTERVAL m	1/200	1/500
GR	100 - 192	x	x
BHC-			
GR	192 - 712	x	x
ISF-			
Sonic	705 - 2739	x	x
ISF-			
Sonic	2718 - 3403	x	x
ISF-			
Sonic	3345 - 3508	x	x
ISF-			
Sonic	3498 - 3601	x	x
ISF-			
Sonic	3497 - 3773	x	x
FDC-			
GR	705 - 2739	x	x
FDC/			
CNL	2718 - 3510	x	x
FDC/			
CNL	3497 - 3602	x	x
FDC/			
CNL	3570 - 3774	x	x
DLL/			
MSFL	3545 - 3598	x	x
DLL/			
MSFL	3570 - 3774	x	x
CDM	1700 - 2739	x	
"	2718 - 3510	x	
"	3498 - 3773	x	
CDM <sub>ap</sub>	1701 - 2730	x	x
"	2725 - 3499	x	x
"	3502 - 3772	x	x

CONVENTIONAL CORES				
NO	INTERVAL m	RECOVERY		
		m	QUALITY	%
1	3561.0-3578.5	16.9		97
2	3578.5-3593.1	11.7		80
3	3593.1-3600.7	7.4		97
4	3609.9-3623.0	11.0		79
5	3623.0-3625.5	1.5		60

TESTS					
TYPE	NO	INTERVAL m	RECOVERY	FSIP psi	FFP psi
DST	1	3610 - 3614	4.8 mm ch, 18.1 SM <sup>3</sup> cond, 33.7 M SM <sup>3</sup> gas, 43° API, GOR 1861 M <sup>3</sup> /M <sup>3</sup> .	6802	5967
"	2	3561 - 3584	19 mm ch, 474 SM <sup>3</sup> cond, 622.9 M SM <sup>3</sup> gas, 43.4° API, GOR 1320 M <sup>3</sup> /M <sup>3</sup>	6858	6457

REMARKS

