

WELL NO 15/9-2

CASINGS				
TYPE	DIAM inches	DEPTH BELOW KB m	HOLE DIAM inches	DEPTH BELOW KB m
COND	30	171	36	171
SFC	20	399	26	415
INT	13 3/8	1181	17 1/2	1195
INT	9 5/8	2788	12 1/4	2819
INT				
LINER	7	3763	8 1/2	3764

CONVENTIONAL CORES				
NO	INTERVAL m	RECOVERY		
		m	QUALITY	%
1	3498.0-3515.0	16.5		97
2	3515.0-3533.3	18.3		100
3	3533.3-3551.6	18.3		100
4	3551.6-3569.9	18.3		100
5	3569.9-3588.2	18.3		100
6	3588.2-3606.5	18.0		98.5
7	3606.5-3624.5	17.7		98.3
8	3624.5-3642.8	17.8		97.4
9	3642.8-3661.1	18.3		100
10	3661.1-3669.9	8.8		100
11	3674.0-3692.0	17.5		97

AVAILABLE LOGS			
TYPE	INTERVAL m	1/200	1/500
GR	127 - 171	x	x
ISF			
Sonic	171 - 3761	x	x
FDC /			
CNL	399 - 3761	x	x
DLL /			
MSFL	3450 - 3675	x	x
MLL /			
ML	3475 - 3760	x	x
LSS /			
Sonic	2784 - 3750	x	x
NGS	3450 - 3760	x	
TDT	3475 - 3760	x	x
CDM	2884 - 3760	x	
" ap	2791 - 3759	x	x
" ap	2791 - 3760	x	x
CBL	399 - 1176		x
"	1908 - 2785	x	
CBL /			
VDL	2686 - 3721	x	
SRS	171 - 3760	1/1000	x
Mud	171 - 3764		x

TESTS					
TYPE	NO	INTERVAL m	RECOVERY	FSIP psi	FFP psi

REMARKS