

WELL NO 24/12-1

CASINGS				
TYPE	DIAM inches	DEPTH BELOW KB m	HOLE DIAM inches	DEPTH BELOW KB m
COND	30	186	36	187
SFC	20	755	26	771
INT	13 3/8	2855	17 1/2	2876
INT	9 1/2	3966	12 1/4	3980
INT				
LINER			8 1/2	4825

AVAILABLE LOGS			
TYPE	INTERVAL m	1/200	1/500
GR	135 - 186	x	x
ISF-			
Sonic	186 - 4822	x	x
BHC-			
GR	3870 - 4823	x	x
FDC	747 - 3968	x	x
FDC/			
CNL	4140 - 4823	x	x
CDM <sup>ap</sup>	2848 - 3970	x	
"	4121 - 4677	x	x
CBL/			
VDL	136 - 753	x	
CBL/			
VDL	272 - 2848	x	x
CBL	3704 - 3963	x	
SRS	186 - 4823		x
Mud	190 - 4825		x

CONVENTIONAL CORES				
NO	INTERVAL m	RECOVERY		
		m	QUALITY	%
1	4170.5-4173.3	2.3		82
2	4173.3-4178.9	5.6		100
3	4178.9-4182.0	3.1		100

TESTS					
TYPE	NO	INTERVAL m	RECOVERY	FSIP psi	FFP psi

REMARKS