

# WELL NO 25/1-6

CASINGS				
TYPE	DIAM inches	DEPTH BELOW KB m	HOLE DIAM inches	DEPTH BELOW KB m
COND	30	192.7	36	193
SFC	20	460	26	463
INT	13 3/8	1314	17 1/2	1320
INT	9 5/8	2520	12 1/4	2545
INT			8 1/2	2895
LINER				

AVAILABLE LOGS			
TYPE	INTERVAL m	1/200	1/500
GR	114 - 193	x	x
ISF-			
Sonic	193 - 468	x	x
ISF-			
Sonic	457 - 1322	x	x
ISF-			
Sonic	1314 - 2098	x	x
ISF-			
Sonic	1998 - 2399	x	x
ISF-			
Sonic	2399 - 2549	x	x
ISF-			
Sonic	2523 - 2893	x	x
B	1314 - 2550	x	x
FDC/			
CNL	193 - 467	x	x
FDC/			
CNL	1314 - 2399	x	x
FDC/			
CNL	2399 - 2550	x	x
FDC/			
CNL	2523 - 2894	x	x
FDC	457 - 1322	x	x
CDM	2000 - 2550	x	
"	2523 - 2894	x	
" ap	1968 - 2541	x	x
"	2536 - 2896	x	x
pp	1964 - 2547		
CBL	111 - 457	x	
"	100 - 1312	x	
"	1000 - 2523	x	x

CONVENTIONAL CORES				
NO	INTERVAL m	RECOVERY		
		m	QUALITY	%
1	2127 - 2136	9		100

TESTS					
TYPE	NO	INTERVAL m	RECOVERY	FSIP psi	FFP psi

REMARKS

# WELL NO 25/1-6

## CASINGS

TYPE	DIAM inches	DEPTH BELOW KB m	HOLE DIAM inches	DEPTH BELOW KB m
COND				
SFC				
INT				
INT				
INT				
LINER				

## AVAILABLE LOGS

TYPE	INTERVAL m	1/200	1/500
SRS	192 - 2893	1/1000	x
Mud	192 - 2900		x

## CONVENTIONAL CORES

NO	INTERVAL m	RECOVERY	
		m	QUALITY %

## TESTS

TYPE	NO	INTERVAL m	RECOVERY	FSIP psi	FFP psi

REMARKS