

## WELL NO 2/11-4

CASINGS				
TYPE	DIAM inches	DEPTH BELOW KB m	HOLE DIAM inches	DEPTH BELOW KB m
COND	30	165	36	165
SFC	20	389	26	396
INT	13 3/8	1279	17 1/2	1281
INT	9 5/8	2556	12 1/4	2559
INT				
LINER	7	2750	8 1/2	2854

AVAILABLE LOGS			
TYPE	INTERVAL m	1/200	1/500
GR	100 - 165	x	
ISF-			
Sonic	165 - 396	x	
ISF-			
Sonic	388 - 1280	x	
ISF-			
Sonic	1278 - 2558	x	x
FDC/			
CNL	2556 - 2857	x	
CDM <sub>ap</sub>	1280 - 2558	x	x
CBL	60 - 1006	x	
CBL	2410 - 2728	x	
CBL/			
VDL/			
TT	40 - 2554	x	
CBL/			
VDL/			
TT	47 - 2556	x	
GR/			
CLL	60 - 1006	x	
T	2250 - 2590	x	
SRS	164 - 2855	1/1000	x
Mud	164 - 2858		x

CONVENTIONAL CORES				
NO	INTERVAL m	RECOVERY		
		m	QUALITY	%
1	2582.5-2594.1	6.1		53
2	2594.1-2601.7	0.75		9.8
3	-		<i>misrun</i>	
4	2605.7-2608.5	2.8		100
5	2608.5-2619.0	10.5		100

TESTS					
TYPE	NO	INTERVAL m	RECOVERY	FSIP psi	FFP psi
DST	1	2698 - 2707	9.5 mm ch, 20.7 SM <sup>3</sup> water		
"	2	2588 - 2595	12.7 mm ch, 223 SM <sup>3</sup> oil, 5 M <sup>3</sup> wann, GOR 790 after frac.	6106	2390

REMARKS