SIMON PETROLEUM TECHNOLOGY
WELL: 34/7-12
Print: 7567k Units: (M) F Top 320 Bottom 2787 Scale 1:500 TD 2784
Length: FT Initials: AW
DIGITAL WIRELINE LOGS PACKAGE
1995
This image may not be used or reproduced without written permission from
SIMON PETROLEUM TECHNOLOGY SPT

COMPLETION LOG

51

Enclosure I b.

ESSO / STATOIL / NORSK HYDRO / ELF
DEMINEX / DNO

saga

# Saga Petroleum a.s.

## Composite Well Log

## Well 34/7-12

| | | | |
|---|---|---|---|
| SCALE | : 1:500 | RIG | : TREASURE SAGA |
| COUNTRY | : NORWAY | LOCATION COORDINATES | |
| AREA | : B-STRUCTURE | LATITUDE | : 61° 16' 17.86" |
| OPERATOR | : SAGA PETROLEUM A.S. | LONGITUDE | : 02° 06' 47.26" |
| LICENCE | : 089 | UTM COORDINATES | 6 793 527.6m N |
| RIG TAKEN OVER BY THE LICENCE | : 30.09.87 | | 452 441.5m E |
| DATE SPUDDED | : 11.10.87 | ELEVATIONS | |
| T.D. DATE | : 15.11.87 | RKB-MEAN SEA LEVEL | : 26m |
| RIG RELEASED | : 16.12.87 | RKB-SEA FLOOR | : 216m |
| COMPLETION STATUS | : OIL DISCOVERY | WATER DEPTH | : 190m |
| | | TOTAL DEPTH driller's depth | : 2784m |
| | | logger's depth | : 2785m |

| DRILLING CONTRACTOR | MUDLOGGING SERVICE |
|---|---|
| WILH. WILHELMSEN | EXPLORATION LOGGING |

| CASING | SHOE (mRKB) | HOLE SIZE | INTERVALL (mRKB) |
|---|---|---|---|
| 30" | 327 | 36" | 216-332 |
| 20" | 838 | 26" | 332-852 |
| 13 3/8" | 1851 | 17 1/2" | 852-1865 |
| 9 5/8" | 2366 | 12 1/4" | 1865-2784 |

LOCATION MAP




OPEN HOLE LOGS

TELECO (MWD) / ATLAS WIRELINE SERVICES

| Casing Record | Hole Size | Logged Interval (m RKB) | Type of Log | Run No. | Date |
|---|---|---|---|---|---|
| 30" 327 m | 36" to 332 m | 216.0 - 327.0 | GR to surface | 1A | 25.10.87 |
| 20" 838 m | 17 1/2" (26") to 852 m | 327.0 - 852.0 | MWD (GR, Res, Dir) GR to surface | 1A | 25.10.87 |
| 13 3/8" 1851 m | 17 1/2" to 1865 m | | MWD | | |
| | | 837.7 - 1852.6 | DIFL-LSBHC-GR | 1A | 25.10.87 |
| | | 837.7 - 1836.1 | CDL-GR | 1A | 25.10.87 |
| | | 858.0 - 1848.7 | COREGUN | 1A | 25.10.87 |
| 9 5/8" 2366 m | 12 1/4" to T.D. | | MWD | | |
| | | 2100.0 - 2476.0 | DLL-MLL-GR | 2A | 06.11.87 |
| | | 2100.0 - 2479.5 | CDL-CNL-GR | 2A-B | 06.11.87 |
| | | 2171.0 - 2312.0 | FMT | 2A-E | 06.11.87 |
| | | | MWD | | |
| | | 1852.0 - 2784.3 | DIFL-LSBHC-GR | 3B | 15.11.87 |
| | | 600.0 - 1852.0 | ACBL | 3A | 15.11.87 |
| | | 1852.0 - 2784.4 | CNL-CDL-GR | 3C | 15.11.87 |
| | | 2210.0 - 2474.0 | FMT | 3G | 15.11.87 |
| | | 2210.0 - 2692.0 | FMT | 3H | 17.11.87 |
| | | MISRUN | DIPMETER | 3A | 17.11.87 |
| | | 1850.0 - 2784.0 | DIPMETER | 3B | 18.11.87 |
| | | 2140.0 - 2784.0 | CNL-CDL-GR | 3D | 18.11.87 |
| | | 2125.0 - 2784.0 | DLL-MLL-GR | 3B | 18.11.87 |
| | | | VSP | 3A | 18.11.87 |
| | | 1875.0 - 2775.0 | COREGUN | 3B-C | 19.11.87 |
| T.D. 2785 m (logger's depth) | | | | | |

AUTHOR: T. L. LARSEN APPR: B. GUSTAVSEN DRAFTED BY: R. KJØLSTAD DATE: MAY 1988

GEOLOGICAL SYMBOLS

CLAY/CLAYSTONE, BRECCIA, SALT, SHALE, LIMESTONE, ANHYDRITE/GYPSUM, SILTSTONE, CHALK, VOLCANICS, SAND/SANDSTONE, DOLOMITE, COAL, CONGLOMERATE, MARL, GNEISSEOUS/BASEMENT

LITH.PREFIXES

CALCAREOUS, DOLOMITIC, ARGILLACEOUS, CHERTY, GLAUCONITIC, MICACEOUS, PYRITIC, TUFFACEOUS, METAMORPHICS, SIDERITE

FOSSILS

FORAMINIFERA, SHELL DEBRIS, MACROFOSSILS

WELL LOG SYMBOLS

SIDEWALL CORE, SIDEWALL CORE, NO RECOVERY, CORE, RFT, SHOWS, FLUORESCENCE AND CUT, SHOWS STAIN FLUORESCENCE, AND CUT, GAS, ON LOGS, CASING SHOE, DRILL STEM TEST

WELL 34/7-12 - CORE SUMMARY

| Core No. | Cut Interval m RKB | Cut m | Recovered Interval m RKB | Recovered m | Recovered % | Correction Factor m | Recovered Interval Log m RKB |
|---|---|---|---|---|---|---|---|
| 1 | 2169.0 - 2196.5 | 27.5 | 2169.0 - 2196.3 | 27.3 | 99.3 | +2.50 | 2171.50 - 2198.80 |
| 2 | 2196.5 - 2214.0 | 17.5 | 2196.5 - 2212.9 | 16.4 | 93.4 | +2.50 | 2199.00 - 2215.40 |
| 3 | 2214.0 - 2216.0 | 2.0 | 2214.0 - 2215.5 | 1.5 | 75 | +1.75 | 2215.75 - 2217.25 |
| 4 | 2216.0 - 2228.0 | 12.0 | 2216.0 - 2224.9 | 8.9 | 74.2 | +1.75 | 2217.75 - 2226.65 |
| 5 | 2228.0 - 2242.0 | 14.0 | 2228.0 - 2242.0 | 14.0 | 100 | +1.75 | 2229.75 - 2243.75 |
| 6 | 2242.0 - 2262.0 | 20 | 2242.0 - 2261.5 | 19.5 | 97.5 | +2.25 | 2244.25 - 2263.75 |
| 7 | 2262.0 - 2290.0 | 28 | 2262.0 - 2289.9 | 27.9 | 99.6 | +1.75 | 2263.75 - 2291.65 |
| 8 | 2290.0 - 2305.5 | 15.5 | 2290.0 - 2305.0 | 15.0 | 96.8 | +1.75 | 2291.75 - 2306.75 |
| 9 | 2305.5 - 2333.0 | 27.5 | 2305.5 - 2332.5 | 27.0 | 98.2 | +1.25 | 2306.75 - 2333.75 |
| 10 | 2333.0 - 2360.5 | 27.5 | 2333.0 - 2356.3 | 23.3 | 84.7 | +1.00 | 2334.00 - 2357.30 |

WELL 34/7-12 - FORMATION MULTI TESTER

| Depth m RKB | Hydrostatic Mud Pressure Before psia | Hydrostatic Mud Pressure After psia | Temperature Corrected Formation Pressure psia | Temperature Corrected Formation Pressure bar | Remarks |
|---|---|---|---|---|---|
| Run 2A | | | | | |
| 2171.0 | 5372.7 | 5372.3 | 4924.9 | 339.56 | |
| 2182.0 | 5399.4 | 5399.4 | 4936.3 | 340.35 | |
| 2189.5 | 5418.2 | 5417.9 | 4943.8 | 340.86 | |
| 2194.5 | 5430.4 | 5430.0 | 4948.9 | 341.21 | |
| 2203.5 | 5452.5 | 5452.5 | 4958.1 | 341.84 | |
| 2210.0 | 5468.7 | 5468.5 | 4964.9 | 342.32 | |
| 2218.5 | 5489.5 | 5489.4 | 4976.6 | 343.12 | |
| 2230.0 | 5517.3 | 5517.4 | 4986.7 | 343.82 | |
| 2242.0 | 5546.5 | 5546.6 | 5005.1 | 345.09 | |
| 2244.0 | 5551.3 | 5551.3 | 5006.9 | 345.21 | |
| 2249.5 | 5564.6 | 5564.7 | 5007.3 | 345.24 | |
| 2253.0 | 5573.0 | 5573.0 | 5010.2 | 345.44 | |
| 2261.0 | 5592.4 | 5592.5 | 5021.5 | 346.22 | |
| 2271.0 | 5516.8 | 5617.0 | 5037.7 | 347.33 | |
| 2280.0 | 5639.0 | 5639.2 | 5048.5 | 348.08 | |
| 2289.5 | 5662.5 | 5662.5 | 5062.0 | 349.01 | |
| 2302.5 | 5694.2 | 5694.5 | 5080.5 | 350.29 | |
| 2312.0 | 5717.5 | 5717.5 | 5094.2 | 351.23 | |
| 2171.0 | 5372.8 | 5371.5 | 4925.3 | 339.59 | Segregated sample, 1 gallon chamber empty |
| Run 2B | | | | | |
| 2171.5 | 5371.7 | 5371.6 | 4925.8 | 339.62 | Segregated sample, 1 gallon chamber empty. |
| Run 2C | | | | | |
| 2189.5 | 5419.5 | 5418.6 | 4943.4 | 340.84 | Segregated sample. |
| Run 2D | | | | | |
| 2189.5 | 5420.0 | - | 4943.9 | 340.87 | Segregated sample. |
| Run 2E | | | | | |
| 2249.5 | 5565.0 | 5564.4 | 5006.9 | 345.21 | Segregated sample, 1 gallon chamber empty. |
| Run 3G | | | | | |
| 2210.0 | 5477.2 | 5477.4 | 4964.9 | 342.32 | |
| 2312.0 | 5729.8 | 5729.9 | 5094.8 | 351.27 | |
| 2471.0 | 6122.3 | 6122.2 | 5363.2 | 369.78 | Pressure draw down 3000 psi. |
| 2474.0 | 6121.8 | 6122.1 | 5362.3 | 369.72 | Pressure draw down 3500 psi. Tool differential stuck at 2465 m RKB. |
| Run 3H | | | | | |
| 2210.0 | 5294.9 | 5294.9 | 4970.8 | 342.72 | |
| 2210.0 | 5261.4 | 5281.6 | 4964.9 | 342.32 | |
| 2312.0 | 5531.6 | 5533.2 | 5093.6 | 351.19 | |
| 2609.0 | 6259.5 | 6258.9 | 5556.9 | 383.13 | |
| 2626.0 | 6278.2 | 6297.6 | 5581.4 | 383.44 | |
| 2647.0 | 6348.1 | 6347.6 | 5611.7 | 386.91 | |
| 2677.0 | 6420.2 | 6420.2 | 5654.9 | 389.89 | Pressure draw down 1500 psi. |
| 2692.0 | 6459.1 | - | 5676.4 | 391.37 | |
| 2252.5 | 5384.9 | - | 5009.9 | 345.42 | Segregated sample. |

WELL 34/7-12 - DST SUMMARY

| Test No. | Interval m RKB (logged) | BHP bar | BHT °C | Reference depth m RKB | WHP bar | WHT °C | Choke size mm | Flow rate $Sm^3/day$ |
|---|---|---|---|---|---|---|---|---|
| 1 | 2276.2 - 2282.2 | 336.5 | 84.2 | 2230.7 | 104.6 | 65.5 | 12.7 | 1297 |
| 2 | 2229.0 - 2235.0 | 294.8 | 83.4 | 2202.6 | 127.0 | 63.2 | 12.7 | 888 |
| 3 | 2205.5 - 2209.5 | 333.2 | 82.1 | 2161.3 | 156.3 | 50.3 | 14.3 | 1460 |

All values are from the end of the main flow in each test.
Reference depth = measuring depth for BHP and BHT.