SIMON PETROLEUM TECHNOLOGY — WELL: 16/4-2

Print: 11373 P — Units: (M) F — Top: 118 — Bottom: 3120 — Scale: 1/500 — TD: 3115

Length: 24 FT — Initials: JAT

DIGITAL WIRELINE LOGS PACKAGE
1995
This image may not be used or reproduced without written permission from
SIMON PETROLEUM TECHNOLOGY SPT

COMPLETION LOG

U-639 — COMPLETION — 3 P

ENCLOSURE 1

HYDRO

Completion log

Scale 1:500

Well: 16/4-2

7 DES. 1990
REGISTRERT
OLJEDIREKTORATET

Location map

Scale 0 20 40km

Coordinates:	58°35'47.17" N, 02°01'48.03" E — UTM: 6 495 672.7 m N, 443 619.5 m E, ED 50 ZONE 31 CM 3°E
Elevation K B	25 m
Water Depth:	93.5 m MSL
Total Depth (Driller):	3117.0 m RKB
Total Depth (Logger):	3114.5 m RKB
Formation at Total Depth	Upper Jurassic Draupne Formation

Country:	Norway
Licence:	087
Owners:	Norsk Hydro, Statoil, Shell, Conoco
Field:	—
Date Spudded:	June 29, 1990
Reached Total Depth:	July 22, 1990
Completed:	July 29, 1990
Well Status:	Abandoned
Rig:	Vildkat
Contractor:	SDS
Mudlogging Company:	Exlog Norge a.s
Geologists:	Fearn, Hayes, Skjold, Bomstad
Prepared by:	Ree, Hayes
Controlled by:	Holehouse
Date:	December 1990

Casing Records:

30" at 204.5 m

18 5/8" at 479 m Leak off 1.86 rd

13 3/8" at 1683 m Leak off 1.90 rd

Comments

Diesel/EZ pills used to free stuck 13 3/8" casing, resulting in diesel contamination of mud system below 1710m.

Logs Run

DIL/LSS//GR	LDL/AMS	SHDT/GR	RFT/GR	CST/GR	MWD
1A. 1708.0– 478 m 2B. 3112.5–1685 m	1A. 1708.0– 478 m	2A. 3114–1685 m	2A. 3111.5–1920 m	2A. 3113–1715 m	ANADRILL LWD 200–1703 m MWD 118.5–3113 m
	LDL/CNL/NGL/AMS		VSP	CBL/VDL/GR	
	2B. 3112.5–1685 m		2A. 3110–1000 m	2A. 1680– 963 m	

Legend

Conglomerate; Sand Sandstone; Silt Siltstone; Clay; Claystone; Shale; Limestone; Dolomite; Dolomitic Limestone; Calcareous Dolomite; Chalk; Marl Marlstone; Coal Lignite; Anhydrite; Salt; Gypsum; Tuff; Igneous Extr Intr; Sandy very, Sandy, Sandy slightly; Silty very, Silty, Silty slightly; Argillaceous

C Carbonaceous mat; Chert; Glauconite; M Mica; Pyrite; Macrofossils; Macrofossils frag; Microfossils

Hydrocarbon Shows: Oil stain; Fluorescence; Visible cut; Fluorescence cut; Gas shows

Casing Shoe; Deviation 2°; Dipmeter results 3°; Two way time from velocity survey, depth m K B, e.g. Relative MSL 3603 m 1.450 s

Core Interval; (No recovery); Side Wall Core; (No recovery)

Perforated Interval; Cement Plug Interval

DST: Through casing; Open hole; Re - Run; RFT/FIT

MWD: Anadrill Schlumberger (118.5–479 m)

DEPTH SCALE 1:500 (1 cm = 5.0 m) AVERAGING INTERVAL 0.3 m

GAMMA RAY: 0 COR-GAMA AAPI 200 — DEPTH (m) MD — RESISTIVITY: 0.2 COR RES OHM MTRS 20; 0.2 RESIST OHM MTRS 20 — AVERAGE PENETRATION RATE: 100 ROP*5 M/HR 1

Wireline: Schlumberger (479–3114.5 m)

0.00 GR (GAPI) 100.00 — 0.20 ILD (OHMM) 2000.00

0.00 SGR (GAPI) 100.00 — 0.20 SFLU (OHMM) 2000.00

TD 3117 m
TD 3114.5 m (LOGGER)

SYSTEM — SERIES — STAGE — GROUP — FORMATION — MEMBER

0.00 GR (GAPI) 100.00; 0.00 SGR (GAPI) 100.00; 320.00 SP (mV) 420.00; 0.20 ILD (OHMM) 2000.00; 0.20 SFLU (OHMM) 2000.00; 240.00 DTLN (uS/FT) 40.00; 240.00 DTLF (uS/FT) 40.00; 10000.00 TENSION (LB) 0.00

CORE REPORT AND FORMATION PRESSURE WORKSHEET

HYDRO — CORE REPORT (1 of 2)

Well No: 16/4-2 — Core No's: 1 — Interval: 1920 - 1925 — Area: Norwegian North Sea — Cut: 1920.0 - 1927.0m — Date: 15.07.90 — Scale: 1:25 — Well RKB: 25m — Recovery: 1920.0 - 1926.2m 88.6% — Geolog.st: Bomstad/Hayes

Depth m	Description	Shows
1920.0	Sd: 100% clr - occ mlky, Qtz,pred f, occ vf-crs, pred subrnd mod srtd, lse-fr non calc, rr mic, metallic, rr grn-blk hvy min, no sed str.	No shows
1922.0	Sd: 100%, pred f, occ vf-m, rr crs, else a.a.	No shows

HYDRO — CORE REPORT (2 of 2)

Well No: 16/4-2 — Core No's: 1 — Interval: 1925 - 1927 — Area: Norwegian North Sea — Cut: 1920.0 - 1927.0m — Date: 15.07.90 — Scale: 1:25 — Well RKB: 25m — Recovery: 1920.0 - 1926.2m 88.6% — Geolog.st: Bomstad/Hayes

Depth m	Description	Shows
1925.80	Sd: 100% clr - occ mlky, Qtz, pred f, occ vf - m, rr crs, pred subrnd, mod- w srtd lse- fri, non calc, rr mic, metallic, rr grn-blk hvy min, no sed str	No shows
1926.20		No shows
1927.0	NOT RECOVERED. Interval 1920.3m to 1922.0m consisted of a sand and mud slurry which flowed out of the barrel and was not recoverable. Aluminium sleeve was not cut into 1m sections except for core shoe interval 1925.8m to 1926.2m	

HYDRO — FORMATION PRESSURE WORKSHEET

Well No. : 16/4-2 — Rig : Vildkat — Date : 23 July 1990

Pressure Units : Bar — RKB-MSL : 25 m — Witnessed by : Fearn

Run No. / Test No.	Depth (MD)	Depth TVD(RKB)	Initial Hydrostatic Press Strain	Initial Hydrostatic Press HP	Formation Pressure Strain	Formation Pressure HP	Final Hydrostatic Press Strain	Final Hydrostatic Press HP	Time Set	Time Retract	Remarks
1	1920	1920	247.2	-	192.6	-	247.2	-	16.45	16.50	T=65.0. Good perm.
2	1950	1950	251.0	-	195.7	-	251.0	-	17.06	17.09	T=69.7. Good perm.
3	1975	1975	254.2	-	198.2	-	254.2	-	17.22	17.25	T=70.3. Good perm.
4	1996	1996	255.9	-	200.3	-	255.8	-	17.36	17.40	T=70.5. Good perm.
5	2428	2428	311.9	-	244.7	-	311.9	-	18.20	18.22	T=82.0. Good perm.
6	2450	2450	314.7	-	246.9	-	314.7	-	18.36	18.40	T=82.4. Good perm.
7	2476	2476	317.9	-	249.6	-	317.9	-	18.54	18.56	T=83.0. Good perm.
8	2502	2502	321.3	-	252.2	-	321.3	-	19.10	19.12	T=83.5. Good perm.
9	2546	2546	326.9	-	255.8	-	326.8	-	19.30	19.32	T=84.0. Good perm.
10	2576	2576	330.7	-	259.8	-	330.6	-	19.48	19.50	T=84.5. Good perm.
11	3111.5	3111.5	398.8	-	-	-	398.7	-	20.39	20.40	T=102.8. Tight.
12	3110	3110	398.4	-	-	-	398.4	-	20.46	20.47	T=103.0. Tight.

Page : 1 of 1