Searched File

SCHLUMBERGER

FOUR-ARM
HIGH RESOLUTION
CONTINUOUS DIPMETER

COUNTRY Norway North Sea
FIELD C O D
WELL 7/11 - 2 X
COMPANY Phillips Petroleum Cy

COMPANY PHILLIPS PETROLEUM Cy
PPCo. 0510
WELL 7/11 - 2 X
FIELD C O D
LOCATION
STATE NORWAY
COUNTRY North Sea

Location of Well
54° 04' 15,2" N
02° 04' 26,5" E

CENTRAL FILE

Elevation : R.T. :
D.F. :
K.B. :
or G.L. :

FILING No.

RUN No.	ONE	TWO	THREE
DATE	September 5,1968		
Casing Depth Schlumberger	6384'		
" " Driller	6385'		
Total Depth Schlumberger	10816'		
" " Driller	10810'		
" " Reached	10816'		
Bit Size	17-½" to 6500 &	12-¼" to 9700	to
	8-½" to T.D.	to T.D.	to T.D.
Mud Nature	Salt Sat.		
" Density | viscosity	13.1 | 54	|	|
" Resistivity	.097 at 68 °F.	at °F.	at °F.
B.H.T.	250 °F	°F	°F
Logging Speed	60 ft/min.		
First Reading	10805'		
Last Reading	6384'		
Interval measured	4421'		
Equipment	C/4		
Truck number	2105		
Observer	Dillehay		
Correlated by	EMR - 6050		
Computed by	EMR - 6050		
Plotted by	565		
Magnetic Declination	8° West		
Reference	241 - 2		

Correlation interval = 12' x 12'
Normal exploitation = 2° x 35
digital recording.

SCHLUMBERGER

HIGH RESOLUTION DIPMETER

COMPANY	PHILLIPS PETROLEUM
FIELD	C.O.D
WELL	7/11-2X
DATE	SEPTEMBER 5 1968
RUN	*1

NORMAL EXPLOITATION 35 DEGREES X 2

CORRELATION INTERVAL 12 FEET X 12 FEET

REFERENCE 2412

PLOT 2412 STANDARD PLOT INCLUDING ALL RESULTS

EXPLANATION OF THE LAST FIVE COLUMNS OF THE LISTING

LOGI = ** = MEAN DIP DETERMINATION USING 4 CURVES

BLANK = DIP DETERMINATION USING 3 CURVES

Q = RATING OF RESULT

A-B-C-D = COHERENCE FACTOR(FROM VERY GOOD TO POSSIBLE)

* = DIAGONAL CORRELATION AND/OR SPEED CORRECTION COULD NOT BE MADE(COHERENCE FACTOR COULD NOT BE COMPUTED)

PLA = COPLANEITY INDEX(0 TO 100)

IF NO PLANEITY AND WHEN QUALITY IS HIGH 4 DIPS ARE GIVEN IN ADDITION TO THE MEAN DIP

CLO = CLOSURE OF THE PAD-CORRELATIONS RETAINED FOR COMPUTATION (0 TO 100)

MAX = LIKENESS FACTOR(MAXIMUM OF THE WORST CORRELATION CURVE RETAINED)

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LG GI	Q	PLA	CLG	MAX
10775	8.9	262	3.0	43	8.4	8.4	**	C	100	100	74
10763	11.0	248	3.0	44	8.4	8.4		A	100	100	75
10751	14.3	270	3.0	42	8.4	8.5	**	D	100	100	94
10739	11.0	280	2.9	42	8.4	8.4	**	D	14	61	53
10739			4 DIPS	9.5	289	12.7	287	12.8	272	9.6	269
10727	11.2	273	3.0	42	8.4	8.5	**	D	13	100	79
10727			4 DIPS	12.8	266	9.9	264	9.7	281	12.6	280
10703	10.6	260	2.9	40	8.6	8.6	**	A	100	100	81
10691	9.8	272	3.0	40	8.6	8.6	**	C	100	100	66
10667	76.7	115	2.9	30	8.6	8.6		D	0	100	22
10655	7.1	249	2.8	27	8.5	8.6	**	A	13	100	86
10655			4 DIPS	4.9	249	7.5	265	9.3	248	7.4	230
10631	13.1	271	2.8	23	8.5	8.5	**	C	100	91	70
10619	6.3	290	2.8	21	8.5	8.6		*	0	27	55
10607	16.2	260	2.9	20	8.5	8.6	**	C	43	100	76
10607			4 DIPS	19.2	261	16.8	249	13.1	258	16.1	271
10595	9.4	266	2.8	18	8.5	8.5	**	C	100	100	83
10583	12.7	222	2.8	17	8.5	8.5	**	C	27	100	72
10583			4 DIPS	16.6	234	16.7	209	9.8	199	9.7	244
10571	67.3	230	2.7	13	8.5	8.5	**	C	100	100	25
10559	17.3	262	2.7	8	8.3	8.4		B	100	100	76
10547	32.1	242	2.6	4	8.5	8.5		*	0	0	43
10535	54.6	170	2.6	10	8.5	8.5		D	0	100	48
10523	14.0	236	2.7	9	8.5	8.5		*	31	100	74
10511	27.3	221	2.2	3	8.5	8.5	**	C	58	69	25
10499	14.1	85	2.3	1	8.5	8.6		*	0	10	49
10487	39.3	356	2.2	3	8.5	8.5		C	0	100	21
10475	16.0	240	2.6	3	8.5	8.6		*	80	25	50
10463	21.6	253	2.2	4	8.5	8.4		C	0	92	34
10451	12.5	223	2.2	4	8.3	8.2		C	54	100	70
10439	16.0	264	2.4	8	8.3	8.3		D	0	61	73
10427	16.3	262	2.6	8	8.7	8.9		*	0	32	81
10415	30.3	20	2.2	3	8.9	8.9		D	0	100	65
10403	14.7	244	2.3	359	8.6	8.7	**	D	14	100	29
10403			4 DIPS	17.3	281	24.3	245	18.6	209	4.2	234
10391	32.8	287	2.3	1	8.8	8.9		*	0	21	54
10379	6.4	188	2.1	359	8.7	8.6	**	D	10	86	54
10379			4 DIPS	14.4	347	22.6	248	25.8	177	19.8	161
10367	44.4	152	2.2	355	8.6	8.6		C	0	100	15
10355	17.8	220	2.0	358	8.6	8.6	**	C	12	70	35

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LØ GI	Q	PLA	CLØ	MAX
10355			4 DIPS	20.7 215	16.4 209			15.0 227		19.7 229	
10343	27.3	250	2.0	356	8.5	8.5		C	26	100	45
10331	16.4	277	2.0	355	8.6	8.4	**	D	35	62	4
10331			4 DIPS	17.8 266	13.3 271			15.5 288		19.4 280	
10319	4.9	216	1.9	355	8.6	8.5		*	13	15	40
10307	16.1	276	2.1	354	8.5	8.5	**	C	49	100	45
10307			4 DIPS	15.5 285	18.5 278			17.1 266		13.7 272	
10295	10.6	153	2.0	351	8.6	8.5		*	0	15	29
10283	15.6	288	2.1	351	8.6	8.5		*	0	0	10
10271	68.7	240	1.9	350	8.6	8.6		*	0	0	21
10259	26.4	12	2.0	350	8.6	8.5		*	0	0	39
10247	21.6	313	1.9	349	8.6	8.6		C	0	100	28
10235	7.2	305	2.0	346	8.6	8.6	**	B	10	83	33
10235			4 DIPS	10.9 6	16.5 311			13.1 287		3.2 161	
10223	32.1	316	2.3	341	9.0	8.7		*	0	20	32
10211	42.7	139	2.2	340	8.8	8.8		*	0	40	38
10199	8.2	46	1.8	343	8.7	8.7		*	0	10	24
10187	23.1	316	1.7	343	8.6	8.6		C	0	74	38
10175	31.3	173	1.6	340	8.5	8.5		D	0	55	50
10163	17.8	230	1.7	340	8.4	8.4		C	0	100	83
10151	18.6	301	1.6	339	8.2	8.4		D	89	100	71
10139	27.2	328	1.7	333	8.4	8.5	**	D	68	100	35
10127	25.7	311	1.6	330	8.6	8.6		*	0	0	0
10115	38.3	255	1.7	329	8.6	8.7		D	0	100	34
10103	7.2	243	1.4	328	8.5	8.6		*	0	0	58
10091	15.3	287	1.4	327	8.5	8.5	**	C	28	100	41
10091			4 DIPS	15.1 307	20.1 290			17.2 269		10.4 280	
10079	11.5	247	1.4	322	8.4	8.5		*	0	38	50
10067	8.9	247	1.4	324	8.5	8.5	**	C	10	100	66
10067			4 DIPS	6.6 259	10.6 260			11.4 239		7.9 228	
10055	12.0	227	1.4	320	8.4	8.4		C	19	67	72
10043	12.3	195	1.3	321	8.5	8.5	**	D	66	53	69
10031	12.9	234	1.5	321	8.4	8.4	**	C	11	100	68
10031			4 DIPS	10.8 240	14.2 243			15.0 229		11.9 223	
10019	10.0	228	1.4	321	8.6	8.6		*	100	24	70
10007	10.8	232	1.4	317	8.5	8.5	**	D	100	54	70
9995	12.3	268	1.3	319	8.4	8.5		C	0	59	46
9983	7.0	234	1.2	320	8.2	8.4		C	0	100	53
9971	11.9	203	1.3	316	8.3	8.4		C	0	100	43
9959	16.0	245	1.3	317	8.3	8.4		*	0	29	53

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LG DI	Q	PLA	CLG	MAX
9947	7.0	251	1.3	316	8.5	8.5		*	0	38	75
9935	5.9	227	1.4	317	8.9	8.7		A	100	100	58
9923	6.8	228	1.3	317	8.7	8.7		C	0	100	44
9911	6.3	247	1.3	311	8.7	8.6	**	A	100	100	22
9899	11.8	202	1.2	313	8.7	8.7		*	0	33	26
9887	13.4	206	1.2	313	8.7	8.7	**	B	100	86	36
9875	5.7	269	1.3	305	8.7	8.6		A	100	100	41
9863	8.2	238	1.2	302	8.6	8.6		A	100	100	72
9851	6.2	249	1.3	304	8.7	8.7	**	A	100	100	55
9839	7.7	249	1.3	301	8.7	8.7	**	A	100	100	86
9827	7.0	249	1.3	302	8.7	8.7	**	A	100	100	80
9815	9.0	253	1.3	299	8.7	8.7		B	100	100	57
9803	10.1	248	1.3	297	8.7	8.7	**	A	100	100	56
9791	8.5	239	1.7	293	8.7	8.7	**	C	100	100	59
9779	8.6	174	2.6	297	9.2	9.0	**	D	100	100	80
9767	6.0	157	1.5	295	9.6	8.6	**	B	100	100	66
9755	8.5	164	1.3	284	10.0	9.0	**	A	51	100	62
9743	10.9	173	1.4	276	9.9	8.8		B	100	100	43
9731	12.9	230	1.2	266	9.9	8.8		*	0	0	46
9719	7.2	263	1.9	269	10.7	8.9		*	100	47	60
9707	9.8	214	2.0	258	12.0	10.3		*	0	42	47
9695	14.1	213	1.6	237	13.3	12.5		A	0	94	42
9683	8.2	231	1.1	233	13.3	12.5		A	100	100	36
9671	17.7	268	1.1	227	13.4	12.8		*	13	38	33
9659	6.9	221	1.5	230	13.3	12.6		*	0	10	23
9647	13.6	206	1.3	227	13.4	12.6		B	22	100	52
9635	3.9	94	1.1	225	13.4	12.6		*	0	18	33
9623	7.4	191	1.1	225	13.6	12.8	**	A	24	53	28
9623			4 DIPS		9.6 187	7.3 171		5.2 196		8.3 207	
9611	10.6	165	1.1	227	13.4	12.6		B	0	100	43
9599	12.4	206	1.4	223	13.2	12.6	**	C	12	70	43
9599			4 DIPS		6.5 226	16.1 230		18.5 198		12.1 171	
9587	9.4	215	1.1	226	12.9	12.6		*	10	100	44
9575	10.6	254	1.2	222	13.0	12.6	**	C	11	100	27
9575			4 DIPS		9.6 266	12.8 259		12.1 243		8.6 244	
9563	11.4	242	1.3	223	12.6	12.3	**	D	10	65	37
9563			4 DIPS		12.3 237	10.5 236		10.6 247		12.4 245	
9551	13.5	182	1.2	223	13.1	12.7	**	B	32	100	54
9551			4 DIPS		18.4 187	16.0 163		8.6 171		13.0 206	
9539	15.0	65	1.7	224	13.1	12.5		*	10	15	41

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LØ GI	Q	PLA	CLØ	MAX
9527	40.0	74	1.4	222	13.1	12.6		*	0	0	53
9515	10.0	199	1.4	223	13.3	12.5	**	B	30	100	50
9515		4 DIPS	13.8	200	11.2	177			6.2	194	10.4 222
9503	4.5	251	1.3	222	13.3	12.4		B	0	100	35

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LG GI	Q	PLA	CLO	MAX
9708	10.7	217	1.7	270	9.9	11.7		C	0	100	45
9696	12.5	236	1.3	246	12.4	13.3	**	A	40	60	33
9696			4 DIPS		16.4 239	14.0 219			8.6 228	12.2 253	
9672	17.1	263	.7	234	12.7	13.4		B	0	51	42
9660	36.3	136	.8	232	12.7	13.4		*	0	0	29
9648	15.1	215	.8	232	12.6	13.5		C	45	100	44
9636	2.6	121	1.0	226	12.7	13.5		*	0	19	37
9624	6.8	193	.8	223	12.8	13.8	**	A	100	65	30
9612	9.7	210	.8	221	12.6	13.5	**	A	100	86	29
9600	13.4	203	.9	215	12.6	13.3	**	B	30	52	45
9600			4 DIPS		12.8 174	8.1 218			16.7 224	18.9 196	
9588	69.3	137	.8	213	12.5	13.0		*	0	10	38
9576	11.5	237	.9	212	12.6	13.1	**	C	100	94	46
9564	9.9	242	.9	213	12.5	12.7		*	0	28	37
9552	8.8	180	1.3	212	12.6	13.1		*	0	40	59
9540	8.9	127	1.1	216	12.4	13.2		*	0	13	43
9528	4.0	170	1.1	216	12.5	13.1		*	30	22	42
9516	13.7	206	1.3	217	12.5	13.4	**	C	25	100	47
9516			4 DIPS		15.2 231	19.3 206			15.0 180	7.8 206	
9504	10.4	226	1.1	215	12.4	13.3		D	0	100	44
9492	7.4	209	1.3	214	12.3	13.6		C	0	100	22
9480	7.6	209	1.5	214	12.3	13.5	**	B	100	64	52
9468	5.7	275	1.1	213	12.2	13.5		B	0	100	24
9456	14.8	233	1.6	213	12.3	13.8		C	55	74	70
9444	26.8	89	1.2	215	12.4	13.9		D	0	61	33
9432	4.3	232	1.2	211	12.4	13.7		*	0	18	43
9420	9.9	209	1.4	213	12.3	13.2	**	C	48	100	57
9420			4 DIPS		10.3 195	7.7 208			10.1 223	12.1 209	
9408	5.3	156	1.3	215	12.3	13.3		*	100	13	52
9396	5.0	185	1.4	215	12.3	13.4		B	0	100	35
9384	29.5	171	1.7	214	12.2	13.2		*	0	25	21
9372	35.8	142	1.5	213	12.3	13.3		*	0	0	38
9360	8.8	173	1.3	213	12.3	13.3	**	C	19	94	33
9360			4 DIPS		7.7 190	11.0 179			10.5 159	6.7 161	
9348	50.5	82	1.5	212	12.3	13.2		B	0	100	13
9336	28.0	155	1.5	211	12.2	13.5		D	0	100	30
9324	31.4	205	1.4	213	12.1	13.6		C	100	100	45
9312	18.7	202	1.5	212	12.1	13.6	**	C	30	100	40
9312			4 DIPS		20.4 182	12.7 199			19.3 223	24.2 203	
9300	22.2	227	1.7	211	12.2	13.4	**	B	100	100	37

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LØ GI	Q	PLA	CLØ	MAX
9288	22.2	200	1.7	211	12.0	13.7		*	0	22	36
9276	13.7	175	1.6	212	12.1	13.8	**	C	13	100	58
9276			4 DIPS	11.7 202		18.3 183		17.7 157		9.5 156	
9264	10.9	187	1.8	212	12.6	13.6		*	0	30	22
9252	3.5	241	1.9	212	12.3	13.3		*	22	0	67
9240	11.7	199	1.8	212	12.2	13.5		*	0	0	32
9228	29.7	146	1.7	209	11.8	13.5		C	10	100	53
9216	17.0	106	1.8	207	12.1	13.4		*	0	0	20
9204	10.7	166	1.8	206	12.2	13.3		B	0	100	19
9192	9.9	149	1.7	207	12.2	13.3		*	0	0	24
9180	17.8	192	1.8	203	12.3	13.6	**	C	73	100	48
9168	8.5	236	1.7	204	12.0	13.4		*	0	22	22
9156	4.9	253	1.7	204	12.2	13.3		B	39	78	46
9144	22.1	292	2.0	207	12.4	13.6		C	0	100	38
9132	4.6	140	1.9	201	12.6	13.5	**	C	100	68	37
9120	7.8	140	1.8	204	12.5	13.8		*	0	100	28
9108	34.2	248	1.8	207	12.3	13.9		*	0	24	29
9096	18.5	144	1.7	205	12.2	13.6		*	0	37	44
9084	12.6	163	1.9	205	12.7	13.8		C	0	100	48
9072	11.9	166	1.7	202	12.5	13.9	**	B	60	100	56
9060	16.6	142	1.7	206	12.2	13.4	**	C	39	79	37
9060			4 DIPS	15.6 148		18.2 145		17.8 136		15.1 137	
9048	12.7	205	1.8	203	12.5	13.7		D	0	72	24
9036	25.5	176	1.8	202	12.2	13.8	**	C	100	100	46
9024	38.3	155	1.9	201	12.5	14.0		*	0	40	30
9012	27.3	236	2.1	204	12.6	14.2		*	0	22	21
9000	23.1	109	2.0	199	12.2	15.4		*	0	10	45
8988	12.7	319	2.2	199	11.7	12.0		*	0	0	19
8976	17.4	254	2.4	201	12.8	13.3	**	D	11	100	35
8976			4 DIPS	7.4 292		23.8 281		27.8 248		17.3 213	
8964	31.3	79	2.1	201	13.0	11.3		*	0	10	13
8952	79.0	258	2.0	195	13.1	11.1		*	0	35	28
8940	13.2	157	1.8	196	14.8	11.3		*	0	0	14
8928	12.8	32	2.2	194	15.2	12.8		*	0	42	24
8916	54.4	271	2.3	195	14.2	12.1		D	0	100	16
8904	8.0	186	1.9	201	14.5	12.8		B	0	100	10
8892	10.3	278	1.8	201	14.1	12.9		C	0	63	23
8880	15.8	200	1.7	203	14.1	12.6	**	C	20	52	15
8880			4 DIPS	13.2 207		18.0 210		18.6 194		14.4 186	
8868	15.5	173	1.6	201	14.3	12.3		B	100	97	49

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LØ GI	Q	PLA	CLØ	MAX
8856	37.8	53	1.8	200	14.5	12.1	**	B	10	100	17
8856			4 DIPS		47.9	27	18.4	3	35.8	92	53.9 63
8844	24.1	158	1.7	194	14.2	11.8	**	D	25	100	8
8844			4 DIPS		13.8	147	25.0	190	33.2	161	29.4 131
8832	12.0	88	1.6	197	14.7	12.2		*	0	10	41
8820	13.5	217	2.5	193	14.6	12.2		*	0	45	35
8808	69.7	158	1.9	193	14.5	12.2		*	0	47	40
8796	20.0	150	2.4	192	14.0	12.1		D	0	100	52
8784	10.3	175	1.9	191	14.6	12.7	**	A	100	100	35
8772	6.8	158	1.9	189	14.6	13.3		*	0	0	26
8760	11.5	178	2.1	189	14.4	12.8		C	0	83	34
8748	12.1	171	2.1	189	14.3	12.9		B	0	100	32
8736	6.7	223	2.0	188	14.2	12.5		A	0	100	35
8724	9.5	157	2.1	187	14.0	12.5		*	0	17	19
8712	.5	250	2.2	186	14.2	12.6		*	0	0	36
8700	6.7	154	2.1	186	14.4	12.5		*	0	0	14
8688	32.2	295	2.3	186	14.3	12.5		B	0	100	31
8676	10.6	176	2.3	185	14.4	12.4		A	0	100	29
8664	15.8	192	2.3	185	14.6	12.4	**	C	16	100	21
8664			4 DIPS		8.3	209	20.5	218	23.1	186	16.0 155
8652	30.1	70	2.2	184	15.3	12.3		*	0	0	25
8640	26.0	286	2.3	184	14.7	12.3		*	0	45	26
8628	26.0	144	2.4	182	15.3	12.3		*	0	0	26
8616	26.7	289	2.3	180	15.1	12.2		*	0	22	28
8604	67.2	195	2.3	180	15.1	12.1		B	0	73	31
8592	41.0	158	2.4	179	15.1	10.9		D	0	100	23
8580	NØ-CØRR		2.4	182	15.7	10.1					
8568	34.1	268	2.4	182	16.1	11.3		*	0	0	33
8556	38.4	113	2.7	181	15.7	11.4		C	0	100	32
8544	59.7	82	2.6	182	15.8	9.0		*	0	10	10
8532	45.3	162	2.6	182	16.0	10.1		*	0	22	22
8520	71.7	255	3.0	177	16.1	11.8		*	0	12	10
8508	48.4	282	3.4	180	15.4	10.6		*	0	0	11
8496	22.7	132	2.9	184	16.0	10.5		B	0	80	9
8484	15.3	91	2.8	181	15.6	10.7		*	0	10	19
8472	62.1	99	3.0	181	15.5	10.8		*	0	19	13
8460	70.6	216	2.6	186	15.6	9.3	**	D	10	100	8
8460			4 DIPS		78.8	209	78.0	146	38.0	303	81.3 265
8448	20.2	186	2.9	182	15.4	11.2		*	0	0	31
8436	33.7	84	3.0	182	14.8	10.4		*	0	0	7

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LØ GI	Q	PLA	CLØ	MAX
8424	59.3	307	2.9	184	15.3	10.7		*	0	0	6
8412	13.1	174	2.9	184	15.1	10.6		D	0	100	28
8400	9.2	355	2.9	185	14.5	10.5		*	0	26	30
8388	21.8	206	2.8	181	14.3	9.7		*	0	26	40
8376	57.4	268	2.9	183	14.1	10.0		*	0	0	38
8364	68.4	101	2.9	181	13.8	8.7		*	0	0	33
8352	70.4	336	2.9	183	14.2	9.2		D	0	67	37
8340	29.0	179	2.9	183	13.7	9.2		C	0	100	42
8328	69.5	274	2.8	182	13.2	8.8	**	D	10	100	0
8328			4 DIPS	72.7	249	40.6	221	70.4	306	78.7	282
8316	69.2	241	2.9	188	13.6	8.1		*	0	10	7
8304	79.4	122	2.9	188	14.4	9.0		*	0	0	36
8292	63.8	252	3.0	185	14.1	10.6		*	0	100	19
8280	69.3	115	2.9	188	13.8	9.2		*	0	52	19
8268	39.7	255	3.0	186	13.7	9.1	**	A	10	63	12
8268			4 DIPS	47.3	324	67.3	272	56.8	218	42.8	123
8256	76.4	151	3.1	185	14.4	9.3		*	0	0	14
8244	22.9	161	3.1	186	14.7	10.6		D	0	100	49
8232	55.4	304	3.1	186	14.3	10.3		D	0	100	28
8220	NØ-CØRR		3.0	185	14.2	9.6					
8208	6.0	267	3.2	185	14.6	10.1		*	0	20	24
8196	73.7	98	3.2	185	14.4	8.9		D	0	100	18
8184	81.2	109	3.3	186	14.3	8.6		*	0	11	22
8172	21.8	267	3.3	185	15.2	9.5		C	0	100	38
8160	25.4	133	3.4	185	15.2	10.7	**	D	34	78	13
8160			4 DIPS	29.9	148	34.9	123	22.7	112	16.1	159
8148	76.2	202	3.3	187	15.5	12.0		*	0	100	18
8136	NØ-CØRR		3.4	186	15.6	12.2					
8124	18.1	147	3.4	184	16.3	12.6		*	0	0	19
8100	80.4	311	3.3	186	14.7	9.1		*	0	14	22
8088	81.6	266	3.2	187	15.0	8.8		*	0	17	0
8076	NØ-CØRR		3.6	186	15.7	10.7					
8064	42.1	233	3.3	184	14.8	10.8		*	0	36	26
8052	39.9	129	3.3	185	14.9	10.4		*	0	15	12
8040	79.2	295	3.2	189	14.0	8.5		*	0	0	18
8028	64.7	312	3.4	186	14.1	9.9		*	0	0	19
8016	57.8	313	3.5	186	14.3	9.3		*	0	35	5
8004	23.8	139	3.4	185	14.2	8.8		*	0	0	23
7992	19.8	271	3.5	183	14.7	9.1		*	0	26	10
7980	39.6	307	3.5	183	14.1	8.9		D	0	100	33

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LØ GI	Q	PLA	CLØ	MAX
7968	28.4	351	3.4	184	14.4	9.1		*	0	0	16
7956	27.5	299	3.6	185	15.4	9.8		C	0	66	23
7944	4.4	203	3.7	187	15.8	10.8		*	0	0	47
7932	18.8	185	3.7	185	15.2	9.9		*	0	100	11
7920	81.6	10	3.8	185	14.7	9.9		*	0	0	26
7908	34.5	31	4.0	186	14.9	9.6		D	0	100	8
7896	NØ-CØRR		4.0	189	15.4	9.9					
7884	60.3	326	4.0	189	14.9	8.6		*	0	0	37
7872	77.2	51	3.6	186	9.8	8.2		*	0	0	15
7860	66.1	194	4.0	183	10.0	8.9		D	0	100	3
7848	73.5	191	4.2	187	10.0	13.9		D	0	100	29
7836	39.7	192	4.3	195	9.5	14.3		*	0	28	24
7824	45.7	69	4.2	197	9.1	14.9	**	D	10	57	29
7824			4 DIPS	72.8 108		70.9	46	67.3 323		42.6 176	
7812	NØ-CØRR		4.2	196	10.3	16.1					
7800	11.7	197	4.2	195	10.5	15.4		*	0	18	8
7788	35.4	217	4.2	197	11.3	14.9		*	0	0	0
7776	34.9	262	4.0	199	11.4	14.5		*	0	0	9
7764	15.8	3	3.9	203	11.4	14.8		*	0	0	25
7752	71.9	349	4.0	203	11.2	14.7		D	0	100	17
7740	71.2	256	4.0	204	11.8	14.6		*	0	10	14
7728	55.0	358	4.0	204	10.3	14.5		C	0	100	26
7704	37.5	267	4.2	199	9.0	14.8		*	0	0	11
7692	72.2	91	4.3	200	12.0	15.7		D	0	100	12
7680	34.0	193	4.2	200	12.3	15.9	**	C	11	84	42
7680			4 DIPS	46.5 159		16.1	156	37.0 244		47.7 201	
7668	46.9	82	4.1	200	10.9	14.7		*	0	14	7
7656	25.0	287	4.2	198	10.0	14.3		*	0	10	20
7644	39.8	103	3.9	200	10.8	14.8		*	0	19	13
7632	76.4	171	4.4	197	11.9	15.8		D	10	100	51
7620	12.8	29	4.1	197	11.8	15.9		*	0	40	37
7608	NØ-CØRR		4.0	199	11.3	14.5					
7596	57.1	163	3.8	197	11.1	13.9		*	0	23	25
7572	66.0	42	3.7	197	10.9	13.6		*	0	0	19
7560	67.5	106	3.5	196	10.9	13.9		*	0	0	51
7548	48.4	120	3.6	195	11.8	14.4		*	0	0	23
7536	16.7	252	3.4	198	12.3	14.6		*	0	0	35
7524	31.5	14	3.6	195	11.5	14.5		*	0	12	34
7512	21.4	168	3.7	194	11.6	14.2		*	0	31	35
7500	36.4	233	3.7	191	12.4	14.4		*	0	20	21

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LG GI	Q	PLA	CLG	MAX
7488	51.8	179	3.5	192	12.7	15.2	**	*	100	100	32
7476	48.5	222	3.6	191	15.2	17.4		*	0	0	4
7464	28.8	21	3.5	195	13.5	15.6		C	0	100	49
7452	22.4	222	3.6	192	14.3	15.4		D	0	100	31
7440	70.4	232	3.6	190	13.1	15.4		D	0	100	23
7428	67.9	88	3.9	188	12.0	15.1		D	100	100	47
7416	57.1	199	3.8	190	11.7	15.1		C	0	100	29

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LØ GI	Q	PLA	CLØ	MAX
7429	70.6	90	4.1	189	12.2	15.3	**	D	52	100	44
7417	70.4	230	3.8	190	12.0	15.3		*	0	10	33
7405	54.8	24	3.7	183	11.3	15.1		*	0	10	27
7393	34.5	130	3.6	185	11.3	15.3		*	0	0	37
7381	36.8	218	3.6	188	11.5	15.4		C	0	100	6
7369	19.0	200	3.5	188	11.8	15.2		*	0	10	24
7357	10.3	207	3.6	187	11.9	14.6	**	C	60	100	33
7345	17.4	187	3.4	188	11.9	13.7		*	0	26	7
7333	37.5	119	3.5	188	12.0	13.5		*	0	10	30
7321	71.9	203	3.5	187	12.2	14.0		*	0	28	39
7309	8.0	208	3.2	185	12.3	13.6		*	0	30	22
7297	22.6	290	3.5	185	12.2	13.9		*	0	18	10
7285	2.7	327	3.2	184	12.4	14.1		*	0	10	16
7273	16.2	226	3.3	184	12.7	13.8		C	0	100	41
7249	25.2	164	3.3	184	12.8	13.8		*	0	0	41
7237	11.3	353	3.3	184	12.6	13.6		*	0	10	37
7225	25.2	52	3.4	185	12.5	13.0		D	0	88	26
7213	NØ-CØRR		3.4	185	12.3	13.3					
7201	NØ-CØRR		3.5	185	12.0	13.4					
7189	25.2	292	3.5	183	11.5	13.7		*	0	17	5
7177	25.2	18	3.4	183	11.5	13.0		*	0	0	51
7165	32.4	218	3.5	182	12.1	13.5		*	0	0	50
7153	53.1	101	3.4	183	11.6	13.1		C	0	100	39
7141	74.4	294	3.3	182	11.9	13.2		D	0	100	16
7129	20.8	192	3.4	181	12.1	14.0	**	C	84	100	13
7117	20.8	146	3.4	179	12.0	13.7	**	C	100	100	20
7105	71.3	134	3.5	180	11.4	13.5	**	D	13	52	11
7105			4 DIPs	76.6	108	59.7	114	70.1	171	76.3	141
7093	36.5	272	3.5	182	12.0	14.8		*	0	44	21
7081	37.3	187	3.8	182	11.8	15.5		*	0	0	28
7069	39.7	62	4.0	184	12.8	15.7		*	0	10	40
7057	22.3	310	3.7	185	15.2	16.2		*	0	47	27
7045	58.3	89	3.6	184	13.1	15.4		*	0	10	25
7033	41.4	25	3.7	187	13.2	15.4		*	0	0	49
7021	31.6	218	3.6	186	11.1	14.7		*	0	0	23
7009	33.4	289	3.7	185	11.7	15.5		*	0	0	9
6997	30.8	30	3.7	183	11.6	15.4		D	0	100	28
6985	34.9	139	3.8	183	11.4	15.5		*	0	14	34
6973	9.2	180	4.0	184	11.4	15.6		*	0	0	4
6961	73.3	130	4.1	186	10.8	15.3		*	0	0	17

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LØ GI	Q	PLA	CLØ	MAX
6949	78.7	280	4.2	187	10.4	15.2		*	0	43	7
6937	19.4	250	4.1	191	10.5	15.7		*	0	0	14
6925	40.9	307	4.3	193	10.3	16.3		D	0	75	38
6913	62.6	148	4.2	193	9.0	16.6		D	0	100	1
6901	79.1	123	4.5	190	9.5	16.9		D	0	100	22
6889	20.9	217	4.4	188	12.9	17.7		*	0	0	21
6877	20.3	49	4.4	191	14.9	17.8		*	0	0	22
6865	6.3	152	4.3	191	16.8	18.0		*	0	0	48
6853	4.5	328	4.2	199	16.1	17.2		*	13	17	70
6841	NØ-CØRR		4.4	198	13.5	17.7					
6829	34.3	258	4.7	196	12.7	18.0		*	0	13	22
6817	65.0	231	4.6	199	16.6	17.9		*	0	26	33
6793	81.3	124	4.5	198	14.0	17.5		*	0	0	79
6781	2.5	336	4.4	198	15.6	16.4		*	0	29	65
6769	31.9	145	4.6	189	14.2	14.3		*	0	45	20
6757	17.2	337	4.5	186	12.3	14.4		*	0	44	46
6745	73.0	131	4.4	188	10.9	15.7		*	0	21	17
6733	69.9	256	4.5	189	13.1	16.1		*	0	29	49
6721	68.1	10	4.6	190	14.6	17.8		C	0	100	52
6709	58.0	41	4.6	191	11.7	17.2		*	0	0	43
6697	70.3	207	4.7	194	12.5	18.0	**	D	100	100	19
6685	55.7	274	4.5	192	14.3	17.4		D	0	100	48
6673	7.0	114	4.4	191	13.3	15.9		*	0	16	25
6661	19.9	208	4.7	194	15.3	16.5		*	0	0	40
6649	30.4	156	4.1	196	15.6	17.9		*	0	0	19
6637	48.9	30	4.5	189	12.0	14.8		*	0	100	19
6625	NØ-CØRR		4.3	186	10.6	14.1					
6613	NØ-CØRR		3.7	192	8.9	11.1					
6601	70.2	229	4.0	195	11.8	14.5		*	0	0	42
6589	16.8	75	4.5	198	12.7	13.4		*	10	29	42
6577	70.8	178	4.2	190	14.3	14.2		D	35	70	54
6565	33.2	238	4.1	193	13.3	13.5		*	0	0	52
6553	1.9	136	4.2	186	15.7	14.8		*	0	13	47
6541	21.9	255	4.2	195	14.0	14.0		*	0	0	12
6529	43.1	53	4.1	186	15.2	15.2		*	0	37	47
6517	25.6	43	4.0	188	15.2	15.1		*	0	10	39
6505	28.4	175	4.2	187	13.9	13.8		*	0	28	56
6493	7.0	240	4.2	187	12.8	15.5		*	0	10	29
6481	22.9	294	3.6	195	12.6	17.2		*	0	0	33
6469	23.8	177	3.0	197	15.1	18.0	**	D	15	52	67

DEPTH	DIP	DIP AZM	DEV	DEV AZM	DIAM 1-3	DIAM 2-4	LØ GI	Q	PLA	CLØ	MAX
6469			4 DIPS	27.6 219	36.1 180			31.5 141		8.9 159	
6457	NØ-CØRR		2.4	204	11.9	18.0					
6445	NØ-CØRR		1.7	207	11.9	18.0					
6433	NØ-CØRR		1.9	204	10.1	18.0					
6421	64.8	346	1.8	202	14.8	18.0		*	0	17	6
6409	36.8	199	2.5	201	14.8	17.9	**	D	45	63	22
6409			4 DIPS	39.6 216	43.2 197			36.6 180		29.1 203	
6397	18.9	217	2.8	193	12.3	17.3		*	0	40	19