SIMON PETROLEUM TECHNOLOGY

WELL: 1/9-2

Print: 1844 M | Units: (M) F | Top 145 | Bottom 3455 | Scale 1/500 | TD 3459

Length: 27 FT | Initials: HPC

DIGITAL WIRELINE LOGS PACKAGE
1994
This image may not be used or reproduced without written permission from
SIMON PETROLEUM TECHNOLOGY

COMPLETION LOG

Completion - M

statoil / PHILLIPS, PETROFINA, AGIP

1/9-2
COMPLETION LOG
Scale 1:500

COORDINATES: 56° 23' 52.77" N
02° 55' 34.63" E

K.B.: 24.7m

WATER DEPTH: 75.8m

TOTAL DEPTH: 3459m

DEEPEST FORM. PEN.: Hod Fm. (Coniacian)

SPUD DATE: 1 June, 1977

RIG RELEASE DATE: 12 August, 1977

WELL STATUS: P & A

RIG: Ross Rig

CONTRACTOR: Ross Drilling Co. A/S

GEOLOGISTS: B. Rasmussen, O. Aga, A. Hage, E. Asphaug, E. Lie, S.M. Aasheim

PREPARED BY: S.M. Aasheim

LOCATION PLAT



DATE: 12 Jan. 1978

CASING DATA:

30" at 152.5m
20" at 433m
13 3/8" at 1375m
9 5/8" at 2856m
7" liner at 3458m

VELOCITY SURVEY:

43 checkshots, levels from 550 to 3459m by Schlumberger. Two-way times from seismic calibration log.

LOGS RUN (depths in meters/Schlumberger)

ISF/SONIC, GR-SP	FDC-CAL-GR-CNL	HDT - FIL	DLL-MSFL-CAL-SP-GR	IES-SP	CBL-VDL-GR	
Run 1 153.5 - 436.2 2 432 - 1388.6 3 1325 - 2864 4 2856.6 - 3434 only Sonic-GR	Run 1 432 - 1389.4 2 1377.3 - 2865 3, 1 2856.6 - 3459 Run 1 CNL	Run 1 2856.6 - 3459 only HDT 1 2856.6 - 3459 only FIL	Run 1 2856.6 - 3459	Run 1 2856.6 - 3459	Run 1 125 - 1377.5 only CBL 2 800 - 2829 CBL-VDL 3 2750 - 3397.5 1 2856.6 - 3440 VDL in open hole.	

LITHOLOGIC SYMBOLS

SAND/SANDSTONE, LIMESTONE, ANHYDRITE, FORAMINIFERA, PYRITE, MICA
SILT/SILTSTONE, CHALK, COAL/LIGNITE, WOOD FRAGS, GLAUCONITE, STYLOLITES
CLAY/CLAYSTONE, DOLOMITE, TUFF, FOSSILS, GEN'L, CHERT, BURROWS
SHALE, MARL, SALT, SHELL FRAGS, SIDERITE, FRACTURES

SHOW OR STAIN | HYDROCARBON CUT | FLUORESCENCE | GAS SHOW

SIDEWALL CORES: REC. / REC. W/SHOW / NO REC. | CORES: CORE NO. | DST | F.I.T. | CASING SHOE/LINER | BIT

SYSTEM	SERIES	STAGE	GROUP	FORMATION	SPONTANEOUS POTENTIAL millivolts / GAMMA RAY api units	RESISTIVITY ohms - m: DEEP INDUCTION R; SPHERICALLY FOCUSED RESITIVITY; COND. (mmho.) / INTERVAL TRANSIT TIME Δt microsecond per foot

Two-way times from seismic calibration log