

PL 044

D-16

Poor Quality

Denne rapport
tilhører


 STATOIL

LTEK DOK.SENTER

LINN: 12477070011

KODE Well 1/9-3 nr. 2

Returneres etter bruk



statoil

WELL 1/9-3

GEOLOGICAL PROGNOSIS

DRILLING PROGRAM

DRILLING CONSIDERATIONS

DATE: 7 JULY 1977

Den norske stats oljeselskap a.s

WELL 1/9-3
GEOLOGICAL PROGNOSIS
DRILLING PROGRAM
DRILLING CONSIDERATIONS
DATE: 7 JULY 1977

STATOIL

DRILLING PROGRAM

WELL 1/9-3

NOTE: This program is designed to supplement Statoil's JACK-UP DRILLING OPERATIONS MANUAL and JACK-UP BLOWOUT PREVENTION MANUAL.

The procedures as presented in this program will be followed in cases where differences exist between this program and the abovementioned procedures.

P H I L L I P S P E T R O L E U M C O M P A N Y N O R W A Y

G E O L O G I C W E L L P R O G N O S I S

WELL NO. 1/9-3 (Obligatory Jurassic Test)

PROSPECT: Block 1/9 Alpha structure

GENERAL DATA

LOCATION

Country Norway

Area North Sea

Licence No. 044

Block No. 1/9

Coordinates: 56° 24' 57,00" N
02° 54' 13,25" E

Seismic: Shotpoint No. 476 Line No. 404 - 404

5,94 Km west of east Boundary

9,51 Km south of north Boundary

285 Km southwest of Norwegian Coast

3,23 Km from N/UK Median Line

1,58 Km N of nearest well (1/9-1)

11,52 Km S-W of nearest field (Edda)

WATER DEPTH 76 Meters

AIR GAP 18.2 Meters } 16.8

K.B.E. 35 Meters

PROJECTED

TOTAL DEPTH 5000 Meters

All depths are given with reference to K.B.E. unless otherwise specified

CONTRACTORS

Drilling Contractor Dyvi Drilling Co.

Drilling Rig "Dyvi - Gamma"

Mud Logging Contractor Exploration Logging

Type Logging Unit GEMDAS

Electric Logging Contractor Dresser-Atlas

Rig Positioning Contractor Decca

Bottom Survey Contractor Bliksem

Helicopter Service Helicopter Service A/S

Supply Boats Phillips

Core Analysis Statex or Core Lab.

Velocity Survey

Paleontology Robertson Research

MUD Baroid

CEMENTING Halliburton

| <u>Contents</u> | <u>Page</u> |
|---|-------------|
| Geological Program..... | 5 |
| Stratigraphic Prognosis..... | 6 |
| Drilling Program..... | 10 |
| Drilling Considerations (Remarks) | 11 |
| Mud Program..... | 13 |
| Hydraulics/Bits..... | 14 |
| Casing..... | 15 |
| Abnormal Pressure Detection..... | 16 |
| Kick Control Calculations..... | 18 |
| Casing Calculations..... | 19 |
| Cement Calculations..... | 35 |

Figures

| | |
|--|----|
| Fig. 1 Comparison between the wells 1/9-1 and 1/9-3..... | 47 |
| Fig. 2 Well 1/9-1 Formation Pore Pressure and Fracture Pressure Evaluation..... | 48 |
| Fig. 3 Formation Temperature Profile..... | 49 |
| Fig. 4 Kick Control Calculations..... | 50 |

GEOLOGICAL PROGRAM
WELL NO. 1/9 - 3

PURPOSE OF TEST

Well 1/9-3 is an obligatory Jurassic test to evaluate the Jurassic structure at Alpha. The well will be drilled through the Jurassic into older formations or to 5,000 m, whichever is shallower. It is planned to do this in a 2 stage operation. Phase 1 will drill and set 9 5/8" casing in the Lower Cretaceous. Phase 2 will drill to proposed depth of 5,000 m.

OBJECTIVES

The primary objective is to drill, evaluate and test the Jurassic sandstones if hydrocarbon shows are encountered. The secondary objective is to confirm and further evaluate the hydrocarbon bearing zones encountered in 1/9-1 in the Danian-Maastrichtian.

DRILLING HAZARDS

Swelling clays are expected from 400 m down to top of Danian. Drilling rate should be controlled to avoid mud rings and sticking problems. Increasing formation pore pressures can be expected in the lower Cretaceous shales with further increases in the Jurassic.

Bright spots found on the site survey and on the seismic could indicate high pressured gas-pockets at 547 m and 1750 m. We can expect small gas pockets throughout this interval as seen in 1/9-1. These depths are subject to a \pm 50 m error. Changes in the casing program due to pore pressure or other reasons will be at the discretion of the Drilling Superintendent with consultation and agreement from Statoil.

SURVEY AND POSITIONING

Rig will be positioned by Satnav. Rig location accuracy is requested within a 50 m radius of shot point location. Preferred direction of error is SE.

STRATIGRAPHIC PROGNOSIS

| <u>UNIT</u> | <u>DEPTH</u> |
|----------------------|--|
| | (Meters sub-sea) |
| Upper Miocene | 960 |
| Mid. Miocene | 1140 |
| Lower Miocene | 1710 |
| Oligocene | 1800 |
| Eocene | 2360 |
| Lower Eocene | 2710 |
| Paleocene | 2880 |
| Danian Marl | 3020 |
| Danian Limestone Pay | 3050 |
| Maastrichtian | 3105 |
| Cenomanian | 3665 |
| Lower Cretaceous | 3745 |
| Jurassic | 3870 (+50m) - could be as low as 4175 m due to poor seismic correlations. |

All depths are in an accuracy of \pm 30 m down to the Maastrichtian. The above structural depths have been derived from seismic line 404 - 404, and results from well 1/9-1. The Cenomanian and Lower Cretaceous depths may be in error by \pm 50 m. The top Triassic and top salt are believed to be below proposed TD but could be as high as 4175 m.

MAIN ZONES OF INTEREST

| | | |
|----------------------|--------|------------------------------|
| Danian Limestone Pay | 3050 m | 390' KB |
| Maastrichtian Chalk | 3105 m | |
| Jurassic Formation | 3870 m | - possible as low as 4175 m. |

GEOLOGICAL WELL LOGGING AND SAMPLING PROGRAM.

Mud logging Contractor: Exploration Logging. A GEMDAS Logging Unit will be employed to log the well for hydrocarbon shows, collect samples, prepare sample logs and conduct certain other services throughout drilling operations.

Samples will be collected at 10 m intervals down to 2500 m. Thereafter 3 m intervals or less will be collected. Sample interval could be changed at the discretion of the well site geologist.

At each sample point there will be six sets of washed and dried samples collected and three sets of unwashed samples ($\frac{1}{2}$ kg).

One composite sample of unwashed cuttings, for petrochemical studies, will be canned at 30 m intervals from the top of Lower Cretaceous (Est. 3745m) to T.D. of well.

One set of washed and dried samples will be retained on the rig until the well is finished. On the wellsite geologist's instructions the remaining samples will be sent to Statex, Stavanger, periodically during drilling. Storage and distribution to partners and N.P.D. will be handled by Statex as per instructions from Phillips.

LOGGING PROGRAM

| <u>RUN</u> | <u>HOLE SIZE</u> | <u>TYPE LOG</u> |
|------------|------------------|--|
| 1. | 17 1/2" | IES, Integrated Acoustic-GR. |
| 2. | 17 1/2" | IES, Integrated Acoustic-GR, CDL-GR-CAL |
| 3. | 14 3/4" | IES, Integrated Acoustic-GR, CDL-GR-CAL |
| 4. | 12 1/4" | IES, Integrated Acoustic-GR, CDL/CNL-GR-CAL, DLL/MLL, Dipmeter SWC*, <u>Velocity Survey</u> |
| 5. | 8 1/2" | IES, Integrated Acoustic-GR, CDL/CNL-GR-CAL, DLL/MLL, Dipmeter, SWC*, Velocity Survey |

* Approximately 30 SWC total required, primarily for paleontological shale cores in L. Cretaceous and Jurassic shales. Velocity Survey will be run at 9 5/8" casing depth and T.D.

Open hole logs must be quality checked and approved by the field geologist prior to his signing of the service order.

CORING PROGRAM

A minimum of one 18 m core will be cut if sands are encountered in the Jurassic. If Jurassic sands indicate hydrocarbons, the coring will be extended throughout the pay zone. A minimum of one 18 m core will be taken in the Danian and in the Maastrichtian zones.

TESTING PROGRAM

Prior to any Drill Steam Tests/Production Tests a separate testing program will be forwarded, but testing is planned in intervals with substantial shows.

COMMUNICATION PROCEDURE

Confidentiality:

All data are considered confidential and will be released to third parties only by decision of Statoil.

Delivery to participants:

A daily well report will be sent by telex by the operator (Statoil) to all partners and to the Norwegian Petroleum Directorate. All other wells site data, including field prints of logs, will be sent by post or messenger.

A final well report will be prepared for distribution to Statoil, partners and to the appropriate Norwegian Government agencies no later than six months after completion of the well.

ATTACHMENTS

No 1. Seismic Profile, Line 404 - 404

No. 2 Structure Map: Top Danian and Jurassic

No. 3. Anticipated Lithology Log

DRILLING PROGRAM

Well Designation : 1/9-3
Vessel : Dyvi Gamma
Air Gap : 18.2 m
KBE to MSL : 35m
Water Depth : 76m
Depths : Referred to KBE except where specified otherwise.

I LOCATION

See Geological Program

II MOVE, PRELOADING AND JACKING UP

As per general procedures

III GEOLOGICAL PROGNOSIS

See Geological Program

IV GENERAL DRILLING

Estimated total depth Phase I : 3800 m

Estimated total depth Phase 2 : 5000 m

Operational phase for Phase 1:

Drill 44" hole with 26" x 44" H.O. to 160m. Run 36" casing.

Drill out 36" casing with 17½" bit to 445m. Log and open hole with 26" H.O. (26" underreamer in case of gas problems). Set 20" casing.

Drill 17½" hole to 1365m. Log and open with 19½" underreamer. Set 16" casing.

Drill 14 3/4" hole to 2800m. Log and open with 17½" underreamer. Set 13 3/8" casing.

Drill 12 1/4" hole to 3800+ m. (T.D. Phase 1). Core and log as programmed. The 9 5/8" casing is to be set into the pressure transition zone in the Lower Cretaceous in order to drill the Jurassic formations safely (Phase 2).

REMARKS (DRILLING CONSIDERATIONS)

The nearest off-set well is 1/9-1 which was drilled on the same structure as the proposed well 1/9-3. Mud weights used, casing depths, and formation lithology for the well 1/9-1 and the prognosis for the deliniation well 1/9-3 are shown in Fig. 1 p. 47

The formation pore pressure - and the formation integrity plot for the well 1/9-1 versus depth is shown in Fig. 2 p. 48. Since the well 1/9-3 is on the same level on the structure, the pore pressures are expected to be essentially the same. Additional informations will be gained from the well 1/9-2 before the well 1/9-3 is spudded.

When drilling out the 20" casing, the mud weight should be approx. 1.30 g/cm^3 . From the seismic a possible gas zone is indicated at 557 m.

The 16" casing is to be set into the pressure transition zone in order to obtain the best possible formation integrity below the 16" casing shoe (approx. 0.20 bar/m or 2.04 g/cm^3 equiv.) *16.3 ppf*

The 16" casing is to be drilled out with approx. 1.70 g/cm^3 mud weight, which is to be increased to $1.80 - 1.84 \text{ g/cm}^3$ at 1725m. *14.2 ppf* On the seismic there is a bright spot, indicating possible gas pocket at 1760 m. *15.3 ppf*

It is an absolute necessity that the yield point of the mud is kept under control to minimize the equivalent circulating density in order to avoid lost circulation.

The 13 3/8" casing point at 2800 m is may be reduced somewhat, due to lost circulation problems encountered at this depth.

The underreaming from $17\frac{1}{2}"$ to $19\frac{1}{2}"$ hole and from $14\frac{3}{4}"$ to $17\frac{1}{2}"$ hole is to be done under the supervision and quidance of a trained operator.

Who?

10/11/74

The Danian and Maastrichtian formations are to be drilled with approx. 1.68 g/cm^3 mud weight, which should provide sufficient overbalance. The formation pore pressures obtained from the 1/9-1 Drill Stem Tests varied from 0.156 bar/m to 0.160 bar/m (1.59 - 1.63 sp.gr.)

A pressure transition zone starting at Cenomanian/Lower Cretaceous can be expected. In order to obtain a sufficient formation integrity for drilling the Jurassic formations, (Phase 2), the 9 5/8" casing is to be set into this transition zone. This should be safely accomplished within the allowable mud weight tolerance from $1.68 - 1.78 \text{ g/cm}^3$ for this section of the hole.

HVA
slip

The single shot directional survey will be run every bit run below the 20" casing shoe, and every 90 m after setting the 16" casing if hole conditions permit.

Whom,

The mud is to be checked for H_2S content at intervals of 100m below the 13 3/8" casing shoe, using the H_2S Gas Train.

*H₂S on optional mudlogger.
slipper system periodical.*

V MUD PROGRAM

| Interval (m) | Hole size | Mud type | Weight (g/cm ³) | PV | YP | H.T.H.P. W.C. | PH |
|--------------|------------------|---|-----------------------------|-----|-------|---------------|-------|
| 111 - 160 | 4 4" | Sea water w/gel slugs | | | | | |
| 160 - 445 | 17 1/2", 26" | Sea water, gel, CMC extra high vis. | | | | | |
| 445 - 1350 | 17 1/2", 19 1/2" | Sea water, gel, CMC/Dextrid-Dripac if required. | 1.30-1.45 | LOW | 15-20 | | 8-9 |
| 1350 - 2800 | 14 3/4" 17 1/2" | Lime, surfactant | 1.70-1.84 | LOW | 15-20 | 25 or less | 12 |
| 2800 - 3800 | 12 1/4" | Low lime surfactant | 1.65-1.79 | LOW | 10-15 | 15 or less | 10-12 |

Remarks: - Rheology properties will be tested and reported at 50° C.

- Maintain drill solids content at a minimum by means of the desander, desilter and mud cleaner (150 and 120 mesh screens).

- Utilize the centrifuge for viscosity control and for barite salvage.

VI HYDRAULICS/BITS

| Interval (m) | Hole size | Bit type | Nozzles (32 nds) | WOB (tons) | RPM | Circ. (m^3/min) | Pump press (bars) |
|--------------|-----------|------------------------|------------------|------------|---------|---------------------|-------------------|
| 111 - 160 | 44" | H.O. | | | 0-5 | 50-70 | |
| 160 - 445 | 17½" | DSJ | 3 x 16 | 2.5-7.5 | 50-110 | 3.8 | |
| 160 - 445 | 26" | H.O. | | 0-7.5 | 110 | 3.8 | |
| 445 - 1365 | 17½" | DSJ | | | 130 | 3.2 | 205 |
| 445 - 1365 | 19½" | Underreamer | 3 x 18 | 0-13 | | | |
| 1365 - 2800 | 14 3/4" | DSJ, S4j4, OSC1GJ, WVJ | 3x16 (15) | 2.5-25 | 120-140 | 2. -2. | 205 |
| 1365 - 2800 | 17½" | Underreamer | | | | | |
| 2800 - 3800 | 12½" | X1G, XV, J22 | 3x16 (15) | 15-120 | 80-120 | 2.4-2.1 | 205 |

Remarks: Hydraulics and Drilling Parameters will be optimized on the rig according to actual mud properties and hole conditions.

Underreaming parameters will be optimized by the service company operator at the rig site.

VIII CASING

Set casing as per general procedures

Casing Program:

| Size (inches) | Depth (m) | Weight (lbs/ft) | Grade | Tread |
|---------------|------------|---------------------------------------|-------|-----------|
| 36 | 0 - 160 | 1½" wall | X-52 | Vetco ALT |
| 20 | 0 - 430 | 133 | K-55 | Buttress |
| 16 | 0 - 1350 | 75 | N 80 | Buttress |
| 13 3/8 | 0 - 2800 | 72 | N 80 | Buttress |
| 9 5/8 | 0 - 2950 | 47 | N 80 | Buttress |
| | 2950-3300 | 53.5 ^{Spec} _{On ft} | N 80 | Buttress |
| | 3300-3800+ | 47 8.50' | N 80 | Buttress |

Note:- 9 5/8", N 80, 53.5lb/ft with special drift 8.50".

-9 5/8", Casing is to be set into the pressure transition zone above the Jurassic formations, Depth: 3 800 m+.

IX CEMENTING

As per general procedures. See "cement Calculations" for slurry composition and slurry amounts. A cement bond log will be run to check the quality of the cement for the 16"
13 3/8" and 9 5/8" casings.

X BOP TESTING

As per general procedures

XI PRESSURE INTEGRITY TESTS

As per general procedures

~~13 3/8~~ 72⁰ NNE, ID: 12.377

16", 72⁰ NNE, ID: 15.124

10", 72⁰ NNE, 86° bias


Total 9⁵/₈ = 525.00 - lbs. 1.20 min.

8.681

9 5/₈

525.00
110.00
415.000

0.29



4.82

72.515

59.14

15.81

For eng. 9⁵/₈ km billets
locking feature.

821 lbs

13 3/8 eng radius operation 9.80 in
no shank. 30 mph. 100 m x 330 ft

Material length: 532 x 12 = 3982

Venturi width: 3982 / 1.8 = 823

$$P = \frac{117.000}{1 + \left(\frac{1}{3400}\right)\left(\frac{L}{r}\right)^2} \quad 14$$

$$117.000 - 14.69$$

$$1 + \frac{1}{3400}$$

$$201.18$$

$$85.50 \quad 165$$

16" End of gyration 5.52

$$\text{Structure} \quad \frac{3960}{5.52} = 712.$$

$$P = \frac{117.000 - 26.50}{1 + \frac{1}{3400} \cdot (712^2)} + 16527$$

$$\text{Unit length app. } 112 \mu \quad 15 \text{ 1/16 } 165$$

666.9

154.23

8.2

200.26
129.46

6.17

119.54

104.69

7.56

21.50

0.52

0.44

XIII ABNORMAL PRESSURE DETECTION

The most effective abnormal pressure detection operation will be the result of team effort involving the Drilling Supervisor, Drilling Engineer, Wellsite Geologist, and Mud Logging Engineer. Pressure indicators will be monitored continuously and any deviation investigated immediately. The reliability of each abnormal pressure indicator will have to be established during the course of operation.

A Mud Logging Unit will be utilized below the 30 inch casing shoe to collect and monitor abnormal pressure parameters. This unit will be programmed to record and plot the following parameters relating to abnormal pressure:

- a) On a depth scale:
 - 1. Drillability
 - 2. ROP
 - 3. "d" exponent

- b) On a time scale
 - 1. Rotary torque
 - 2. Mud temperature in
 - 3. Mud temperature out
 - 4. Lagged differential temperature
 - 5. Mud flow in
 - 6. Mud flow out
 - 7. Mud weight in
 - 8. Mud weight out
 - 9. Pit volume
 - 10. Pit volume total change
 - 11. Mud gas

In addition, below the 20" casing shoe, manual plots will be recorded and reviewed continuously by the Drilling Engineer and Drilling Supervisor. These plots will include ROP, "d"-exp., Gas Units, and Shale Density.

Abnormal pressure detection data will be forwarded into the Stavanger Operations Office twice daily on a routine basis and more frequently if drilling a suspect transition zone. Any change in abnormal pressure detection parameters will be immediately reported by the rig to the Stavanger Operations Office.

XIV PRODUCTION TESTS

As per production test manual. A detailed testing program will be issued prior to each production test.

XV PLUG AND ABANDONMENT

As per general procedures.

Approved:

Expl. Manager Statoil

Drilling and Production
Manager

✓54

CALCULATIONSKICK CONTROL

20" Casing: The normal procedure of not shutting in the well will be used.

16" Casing: Setting depth: 1350 m. Formation integrity: equiv. 0.20 bar/m. From Fig. 4 p. 50 it can be seen that a 106 m column of gas (equiv. volume 10.3m^3) is the maximum that can be circulated out at the 16" casing shoe if the required mud weight increase is 0.05 g/cm^3 , $(1.84+0.05) \text{ g/cm}^3$.

13 3/8" Casing: Setting depth: 2800 m. Formation integrity: equiv. 0.185 bar/m. From Fig. 4 p.50 it can be seen that a 78m column of gas (equiv. volume: 5m^3) is the maximum that can be circulated out at the 13 3/8" casing shoe if the required mud weight increase is 0.05 g/cm^3 , $(1.78+0.05) \text{ g/cm}^3$.

Note: The pore pressure in the Danian/Maastrichtion pays is known to be $0.157 - 0.160 \text{ bars/m}$. The only place kick could possibly occure with a 1.78 g/cm^3 mud weight is in the transition zone above Jurassic.

9 5/8" Casing: Setting depth: 3800 +m. Formation integrity: 0.210 bar/m. From Fig. 4 p.50 it can be seen that a 170 m column of gas (equiv. volume: 4.1 m^3) is the maximum that can be circulated out at the 9 5/8" casing shoe if the required mud weight increase is 0.05 g/cm^3 , $(2.00 + 0.5) \text{ g/cm}^3$.

Note: The control wells 2/7-1, 2/7-9 and 2/8-3 all drilled Jurassic with mud weights less or equal to 2.00 sp. gravity. There is no reason to believe that a higher mud weight than 2.00 sp. gravity should be necessary for this well.

CASING CALCULATIONS

Co = Collapse load (bars)
Co' = Collapse load at top of fluid column (0') (bars)
Co" = Collapse load at seat while cementing (bars)
Gf = Fracture gradient (bars/m)
G_{gas} = Gas gravity gradient (bars/m)
Gi = Mud gradient at casing setting depth (bars/m)
G'i = Maximum mud gradient below casing shoe (bars/m)
G_p = Normal pore pressure gradient (burst) = 0.1 bars/m
G'_p = Normal pore pressure gradient (collapse) (bars/m)
G"_p = Actual pore pressure gradient (bars/m)
Mc = Casing mass-gradient (coupled) (kg/m)
P_{bs} = Burst load at seat (bars)
P_{bw} = Burst load at well-head (bars)
RES_b = Burst resistance (bars)
RES_c = Collapse resistance (bars)
REST = Tension resistance (10^3 daN)
S.F.b. = Safety factor, burst = 1.10
S.F.c. = Safety factor, collapse = 1.25 (1.30 for 13 3/8" CSG)
S.F.t. = Safety factor, tension = 1.50
T = Tension (10^3 daN)
T% = Longitudinal tension stress % of YSm
T_{o'} = Tensile stress at 0' (N/mm²)
Wd = Well depth (m)
X = Casing seat depth (m)
Y = Depth (m) to top of fluid column if mud is lost to formation at the bit
YSm = Min. yield strength (n/mm²)

16" CASING

Wd = 2800
 Wd* = 2100m (max pore pressure gradient)
 X = 1350m
 Gp = 0.10 bar/m (sea water)
 $G''p,2100 = 0.177 \text{ bar/m (1.80 sp.gr.)}$
 Gi = 0.140 bar/m (1.43 sp.gr.)
 $G'i = 0.181 \text{ bar/m (1.84 sp.gr.)}$
 Gf = 0.204 bar/m (2.08 sp.gr.)

BURST

A design kick of 15 m^3 volume necessitating 0.10 sp.gr. mud weight increase is assumed at Wd. Maximum casing burst pressure is equal to the internal pressure at the mud/gas interface when circulating out the kick, less the hydrostatic pressure of sea water (back-up).

Select N80, 75 lbs/ft casing which has the following properties:

$\text{RES}_c = 70 \text{ bars}$
 $\text{RES}_b = 264 \text{ bars}$
 $\text{RES}_t = 762 \cdot 10^3 \text{ daN}$
 $M_c = 110.39 \text{ kg/m}$

Annular Capacity 14 3/4" hole-5" DP: 98 l/m

Height of kick: (H_k):

$$H_k = \frac{15 \text{ m}^3}{0.098 \text{ m}^3/\text{m}} = \underline{153 \text{ m}}$$

$$\begin{aligned}\text{BHP after kick: } P_p &= (G'i + 0.01) \cdot Wd^* \\ &= (0.18 + 0.01) \cdot 2100 \\ &= \underline{\underline{401 \text{ bars}}}\end{aligned}$$

Determination of internal casing pressure while circulating out the kick using equations from the BOP-manual.

$$1. \quad Pg + (Wd^* - Hg) \cdot G'i = Pp$$

$$2. \quad \frac{P_p \cdot V_1}{T_1 \cdot Z_1} = \frac{Pg \cdot V_g}{T_2 \cdot Z_2}$$

where

- P_g = pressure of gas bubble at surface (bars)
- H_g = height of gas bubble at surface (m)
- V_g = Volume of gas bubble at surface (m^3)
- V_1 = Volume of influx = $15m^3$
- T_1 = Bottom hole temp: 72°C (345°K)
- T_2 = Surface temp. : 25°C (298°K)
- Z_1 = Gas compr. factor at bottom: 1.06
- Z_2 = Gas compr. factor at surface: 0.83

Equation 2:

$$\frac{401 \cdot 15}{345 \cdot 1.06} = \frac{P_g \cdot V_g}{298 \cdot 0.83}$$

$$\text{where } V_g = H_g \cdot 0.098$$

$$\begin{aligned}H_g &= \frac{401 \cdot 15 \cdot 298 \cdot 0.83}{345 \cdot 1.06 \cdot P_g \cdot 0.098} \\ &= \frac{41513}{P_g}\end{aligned}$$

Substitute for H_g in equation 1

$$P_g + (2100 - \frac{41513}{P_g}) \cdot 0.18 = 401$$

$$P_g^2 - 20.9 P_g - 7514 = 0$$

$$\underline{P_g \approx 98 \text{ bars}}$$

$$H_g = \frac{41513}{98} = \underline{424 \text{ m}}$$

From graphical solution $P_b \text{ max} = 173 \text{ bars at } 1350 \text{ m}$

$$\begin{aligned} SF_b &= \frac{RES_b}{P_b} \\ &= \frac{264}{173} = \underline{1.52 (>1.10)} \end{aligned}$$

Collapse

Maximum collapse load:

$$\begin{aligned} C_o &= x \cdot (G_i - G_p) \\ &= 1350 (0.140 - 0.10) \\ &= \underline{54 \text{ bars}} \end{aligned}$$

$$\begin{aligned} SF_c &= \frac{RES_c}{C_o} \\ &= \frac{70}{54} = 1.30 (\geq 1.30) \end{aligned}$$

Tension


$$\begin{aligned} T &= M_c \cdot x \cdot \frac{0.98}{1000} \\ &= 110.39 \cdot 1350 \cdot \frac{0.98}{1000} \\ &= \underline{146.2 \cdot 10^3 \text{ daN}} \end{aligned}$$

$$\begin{aligned} SF_t &= \frac{REST}{T} \\ &= \frac{762 \cdot 10^3}{146.2 \cdot 10^3} \\ &= \underline{5.2 (>1.50)} \end{aligned}$$

Result:

The selected casing N80, 75lb/ft full fills all requirements.

24)



13 3/8" CASING

$$W_d = 3800 \text{ m}$$

$$X = 2800 \text{ m}$$

$$G_p = 0.10 \text{ bar/m (sea water)}$$

$$G''_p \text{ Danian} = 0.157 \text{ bar/m (1.60 sp.gr.)}$$

$$G_{\text{gas}} \text{ Danian} = 0.027 \text{ bar/m } (\bar{p} = 440 \text{ bar}, \gamma = 0.70, \bar{T} = 80^\circ \text{ C})$$

$$G_i = 0.180 \text{ bar/m (1.83 sp.gr.)}$$

$$G'_i = 0.175 \text{ bar/m (1.78 sp.gr.)}$$

$$G_f = 0.185 \text{ bar/m (1.88 sp.gr.)}$$

Burst

A design kick of $15m^3$ volume necessitating a 0.10 sp. gr. mud weight increase is assumed at W_d . Maximum casing burst pressure is equal to the internal pressure at the mud/gas interface when circulating out the kick, less the hydrostatic pressure of sea water (back-up).

Select N80, 72 lb/ft Buttress casing which has the following properties:

$$RES_c = 184 \text{ bars}$$

$$RES_b = 371 \text{ bars}$$

$$RES_t = 738 \cdot 10^3 \text{ daN}$$

$$M_c = 107.42 \text{ kg/m}$$

Annular capacity $12\frac{1}{2}$ " hole-5"DP: 63.4 l/m

$$\begin{aligned} \text{Height of kick: } H_k &= \frac{15m^3}{0.0634 \text{ m}^3/\text{m}} \\ &= \underline{\underline{237 \text{ m}}} \end{aligned}$$

$$\begin{aligned} \text{BHP after kick: } P_p &= (G'_i + 0.01) \cdot W_d \\ &= (0.175 + 0.01) \cdot 3800 \\ &= \underline{\underline{703 \text{ bars}}} \end{aligned}$$

Determination of internal casing pressure while circulating out the kick using equations from the BOP-manual.

$$1. \quad P_g + (W_d - H_g) \cdot G'_{i'} = P_p$$

$$2. \quad \frac{P_p \cdot V_1}{T_1 \cdot z_1} = \frac{P_g \cdot V_g}{T_2 \cdot z_2}$$

where P_g = pressure of gas bubble at surface (bars)

H_g = height of gas bubble at surface (m)

V_g = volume of gas bubble at surface (m^3)

V_1 = volume of influx ($15m^3$)

T_1 = Bottom hole temp: $130^\circ C$ ($403^\circ K$)

T_2 = Surface temp.: $45^\circ C$ ($318^\circ K$)

z_1 = Gas compr. factor at bottom: 0.80

z_2 = Gas compr. factor at surface: 1.44

Equation 2:

$$\frac{712 \cdot 15}{403 \cdot 1.44} = \frac{P_g \cdot V_g}{318 \cdot 0.80}$$

$$\text{where } V_g = H_g \cdot 0.0634$$

$$\begin{aligned} H_g &= \frac{712 \cdot 15 \cdot 318 \cdot 0.80}{403 \cdot 1.44 \cdot P_g \cdot 0.0634} \\ &= \frac{73847}{P_g} \end{aligned}$$

Substitute for H_g in equation 1.

$$P_g + (3800 - \frac{73847}{P_g}) \cdot 0.175 = 703$$

$$P_g^2 - 38P_g - 12923 = 0$$

$$\underline{P_g \approx 134 \text{ bars}}$$

$$H_g = \frac{73847}{134} = \underline{551 \text{ m}}$$

From graphical solution P_b max = 303 bars at 2800 m

$$SF_b = \frac{RES_b}{P_b}$$

$$= \frac{371}{303} = \underline{1.22 (> 1.10)}$$

Collapse

Top of fluid column if circulation is lost to a formation with pore pressure equal to the Danian reservoir pressure gradient.

$$y = w_d - \frac{w_d \cdot G''_p \text{ Danian}}{G'_i}$$

$$y = 3800 - \frac{3800 \cdot 0.157}{0.175}$$

$$= \underline{391 \text{ m}}$$

The collapse load at 391 m

$$C_o' = G_i \cdot y$$

$$= 0.180 \cdot 391$$

$$= \underline{70.4 \text{ bars}}$$

Tension in casing at depth O' (casing set in 1.83 sp.gr. mud)

$$T_{O'} = M_c \cdot (x-y) \cdot \frac{0.98}{1000} \cdot 0.77$$

$$= 107.42 (2800 - 391) \cdot \frac{0.98}{1000} \cdot 0.77$$

$$= \underline{195 \cdot 10^3 \text{ daN}}$$

$$T\% = \frac{T_{O'}}{RES_t}$$

$$= \frac{195}{738} = 26\%$$

Biaxial stress curve gives collapse reduction by 17% i.e.

$$\text{RES}_C = 171 \cdot 0.83 \\ = \underline{\underline{142 \text{ bars}}}$$

$$\text{SF}_C = \frac{\text{RES}_C}{C_o} \\ = \frac{142}{70.4} = \underline{\underline{2.01 (>1.25)}}$$

Tension

Weight of casing in air:


$$T = M_C \cdot X \cdot \frac{0.98}{1000} \\ = 107.42 \cdot 2800 \cdot \frac{0.98}{1000} \\ = \underline{\underline{295 \cdot 10^3 \text{ daN}}}$$

$$\text{SF}_t = \frac{\text{RES}_t}{T} \\ = \frac{738 \cdot 10^3}{295 \cdot 10^3} \\ = \underline{\underline{2.50 (>1.50)}}$$

The selected 13 3/8" N80, 72 lb/ft casing fulfills all requirements.

29)

Well 119-3 Burst Calc.
13 3/8" Casing, 1180, 72 kpsi



9 5/8" CASING

Wd = 3 800 m and 5 000 m

X = 3 800 m

Gp = 0.10 bar/m (sea water)

G" p Danian = 0.157 bar/m (1.60 sp.gr.)

G gas Danian = 0.027 bar/m (\bar{p} = 440 bars, γ = 0.70, \bar{T} = 80°C)

G_i = 0.175 bar/m (1.78 sp.gr.)

G_i = 0.196 bar/m (2.00 sp.gr.)

G_f , 3 800 = 0.210 bar/m (2.14 sp.gr.)

G"p, Jurassic = 0.190 bar/m (1.94 sp.gr.)

The 9 5/8 casing calculations are done for two cases:

- a) Production casing for Danian/Maastrichtian.
- b) Intermediate casing for drilling the Jurassic formations.
- a) Production casing for the Danian/Maastrichtian pays

Select the following 9 5/8" production casing: 0 - 2 950 m, N 80 47 lb/ft, 2 950 - 3 300 m, N 80, 53.5 lb/ft, 3 300 - 3 800 m, N 80 47 lb/ft, all Buttress.

9 5/8" casing properties:

| | N 80, 47 lb/ft | N 80 53.5 lb/ft |
|------------------|----------------|-----------------|
| RESc, bars | 328 | 456 |
| RESb' bars | 474 | 547 |
| REST, 10^3 daN | 482 | 552 |
| Mc, kg/m | 69.89 | 79.74 |

Burst

The casing is designed to withstand the static wellhead burst pressure over the entire length, i.e.

$$P_{bw} = (G''p, \text{Danian} - G_{gas}, \text{Danian}) \cdot X \text{ Danian}$$

$$= (0.157 - 0.027) \cdot 3070 = \underline{\underline{399 \text{ bars}}}$$

$$SF_b = \frac{RES_b}{P_{bw}} = \frac{474}{399} = 1.19 (> 1.10)$$

Collapse

The part of the casing above a production packer is designed to withstand the hydrostatic difference between mud and sea water.

$$\begin{aligned} Co, 2950 \text{ m} &= (G_i - G_p) \cdot X, (\text{N } 80, 47 \text{ lb/ft}) \\ &= (0.175 - 0.01) \cdot 2950 = \underline{221 \text{ bars}} \end{aligned}$$

$$SF_c = \frac{RES_c}{Co, 2950} = \frac{328}{221} = 1.48 (> 1.25)$$

The part of the casing between a production packer and the plug back depth (2950 - 3300 m) is designed for a minimum allowable flowing pressure for N 80, 53.5 lb/ft casing).

$$\begin{aligned} P_{wf, min} &= P_{mud} - \frac{RES_c}{SF_c} = \\ 0.175 \cdot 3300 - \frac{456}{1.25} &= \\ \underline{213 \text{ bars which is equivalent to 275 bars drawdown at 3200 m}} \end{aligned}$$

Tension

$$\begin{aligned} T &= Mc \cdot X \cdot \frac{0.981}{1000} \\ &= 69.89 \cdot (2950 - 0) + (3800 - 3300) \cdot \frac{0.981}{1000} \\ &\quad + 79.74 (3300 - 2950) \cdot \frac{0.981}{1000} \\ &= 236.5 + 27.4 \\ &= \underline{264 \cdot 10^3 \text{ daN}} \end{aligned}$$

$$\begin{aligned} SF_t &= \frac{RES_t}{T} (\text{N } 80, 47 \text{ lb/ft}) \\ &= \frac{482 \cdot 10^3}{264 \cdot 10^3} \\ &= \underline{1.83 (> 1.50)} \end{aligned}$$

The proposed 9 5/8" production casing:

0 - 2950 m, N 80, 47 lb/ft Buttress
 2950 - 3300 m, N 80, 53.5 lb/ft, Buttress
 3300 - 3800 m, N 80, 47 lb/ft, Buttress
 fullfills all requirements.

b) Intermediate casing for drilling the Jurassic formations

Burst

A design kick of 15 m^3 volume necessitating a 0.10 sp.gr. mud weight increase is assumed at T.D. Maximum casing burst pressure is equal to the internal pressure at the mud/gas interface when circulating out the kick less the hydrostatic pressure of the mud the casing was set in. (in this case the danian pore pressure gradient 0.157 bar/m or 1.60 sp.gr. is used)

Annular capacity 8.5" hole - 5" DP: 24 l/m

$$\text{Height of kick: } H_K = \frac{15 \text{ m}^3}{0.024 \text{ m}^3/\text{m}} = 625 \text{ m}$$

$$\begin{aligned}\text{BHP after kick: } P_p &= (G'i + 0.01) \cdot Wd \\ &= (0.196 + 0.01) \cdot 5000 \\ &= \underline{\underline{1030 \text{ bars}}}\end{aligned}$$

Determination of internal casing pressure while circulating out the kick using equations from the BOP Manual:

$$1. \quad Pg + (WD - Hg) \cdot G'i = Pp$$

$$2. \quad \frac{P_p \cdot V_1}{T_1 \cdot Z_1} = \frac{Pg \cdot Vg}{T_2 \cdot Z_2}$$

Where Pg = pressure of gas bubble at surface, bars

Hg = height of gas bubble at surface, m

Vg = volume of gas bubble at surface, m^3

Pp = pressure of gas bubble at bottom, 1020 bars

V_1 = volume of inflow , 15 m^3

T_1 = bottom hole temperature, 170°C , (443°K)

T_2 = surface temperature, 50°C , (323°K)

Z_1 = gas compr. factor at bottom, 1.55

Z_2 = " surface, 0.85

$$\text{Equation 2: } \frac{1030 \cdot 15}{443 \cdot 1.55} = \frac{Pg \cdot Vg}{323 \cdot 0.85}$$

where $Vg = Hg \cdot 0.024$

$$Hg = \frac{1030 \cdot 15 \cdot 323 \cdot 0.85}{443 \cdot 1.55 \cdot Pg \cdot 0.024}$$

$$= \frac{257397}{Pg}$$

Substitute for H_g in equation 1:

$$P_g + (5\ 000 - \frac{257397}{P_g}) \cdot 0.196 = 1\ 030$$

$$P_g^2 - 50\ P_g - 50\ 450 = 0$$

$$\underline{P_g = 251 \text{ bars}}$$

$$H_g = \frac{257393}{P_g} = \frac{257397}{251} = \underline{1\ 025 \text{ m}}$$

From graphical solution, p.

P_b max = 310 bars at 3 800 m

$$SF_b = \frac{RES_b}{P_{bmax}} \quad (\text{N } 80, 47 \text{ lb/ft})$$

$$= \frac{474}{310}$$

$$= \underline{1.53 (> 1.10)}$$

Collapse

See collapse calculations for production casing p. 31 which is stricter than for an intermediate casing.

Tension

See calculations for production casing p. 31 which are the same as for an intermediate casing.

Result


The proposed 9 5/8" casing:

0 - 2950 m, N 80, 47 lb/ft, Buttress

2950 - 3300 m, N 80, 53.5 lb/ft, Buttress

3300 - 3800 m, N 80, 47 lb/ft, Buttress

Full fills all requirements for Danian/Maastrichtian production casing and for an intermediate casing for drilling the Jurassic formations to T.D. (5000 m).



36" CASING CEMENT CALCULATIONS

The cement volume is calculated on the basis of theoretical hole volume, the casing being cemented to the surface with 150% excess volume.

The ratio between dry-mixed and prehydrated gel is taken to be 4:1 when using fresh water for hydrating.

Data

| | | |
|--------------------------------------|---------|------------------------|
| Depth KB- Seabed | : | 111m |
| Depth KB- 36" shoe | : | 160 m |
| Hole size | : | 44" |
| Annulus capacity 44" hole - 36" csg: | 324 l/m | |
| Mud weight | : | 1.09 g/cm ³ |
| BHST | : | 10°C |

Cement data using sea water

| | <u>Class G+8%</u> equiv.gel+2%CaCl ₂ | <u>Class G</u> +3% CaCl ₂ |
|---|--|---|
| mix water, l/100 kg, (gal/sx) | 88 (10.0) | 44 (5.0) |
| Slurry weight, g/cm ³ (ppg) | 1.58 (13.2) | 1.92 (16.0) |
| Slurry yield, l/100kg (ft ³ /sx) | 120 (1.82) | 77 (1.16) |
| Thickening time, hrs | 4+ | 3+ |
| 8 hr compr. strength, bars (psi) | - | 17 (250) |
| 24 hr. " " " bars (psi) | 7 (100) | 28 (450) |

Note: For prehydrating Wyoming bentonite, 50% of the total mixing water volume of fresh water is needed to hydrate the bentonite. Once hydrated, the other 50% of the water to be added can be sea water. Add the Calcium Chloride to the total volume after hydrating the bentonite.

Volume calculations

Annular volume: $0.324 \text{ m}^3/\text{m} \cdot (160-111)\text{m} = 15.88\text{m}^3$

| | |
|-------------------|---------------------------|
| Shoe joint volume | <u>0</u> |
| Total | <u>15.88m³</u> |

Volume + 150% excess: 39.7 m³

Use:

Preflush: 3m³ sea water

Lead: Class G +8% equiv. gel +2% CaCl₂: 25000 kg (586sx).
equal to 30.0m³ slurry.

Tail in: Class G +3% CaCl₂: 13000 kg (305 sx) equal
to 10.0m³ slurry.

20" CASING CEMENT CALCULATIONS

The cement volume is calculated on the basis of theoretical annulus volume, the casing being cemented to the mudline with 10% excess volume. The ratio between dry mixed and prehydrated gel is taken to be 4:1. The bentonite is prehydrated in fresh water and sea water is added as required.

DATA

| | | |
|-------------------------------------|---|------------------------|
| Depth KB - sea bed | : | 111 m |
| Depth KB - 36" shoe | : | 160 m |
| Depth KB - 20" shoe | : | 430 m |
| Annulus capacity 36"-20" | : | 349 l/m |
| Annulus capacity 26"-20" | : | 140 l/m |
| Internal capacity 20", 133 lb/ft | : | 178 l/m |
| Mud weight | : | 1.09 g/cm ³ |
| Formation integrity at 20" shoe | : | 0.150 bar/m |
| BHST | : | 27°C |

Cement data using sea water.

| | Class G+8% equiv.gel+2% CaCl ₂ | Class G+ 1% CaCl ₂ |
|--|--|----------------------------------|
| Mix water, 1/100 kg (gal/sx) | 88 (10.0) | 44 (5.0) |
| Slurry weight, g/cm ³ (ppg) | 1.58 (13.2) | 1.92 (16.0) |
| Slurry yield, 1/100 kg (ft ³ /sx) | 120 (1.82) | 77 (1.16) |
| Thickening time, hr.: min | 3:00+ | 3:10 |
| 8hr compr. strength, bars (psi) | - | 30 (450) |
| 24 hr compr.strength, bars (psi) | 20 (450) | 100 (1500) |

Volume calculations

| | |
|--|---------------------------|
| Open hole : 0.140 m ³ /m · (430-160) = | 37. 8 m ³ |
| Open hole excess: 150% | = 56. 7 m ³ |
| Cased annulus: 0.349 m ³ /m (160-111) = | 17. 1 m ³ |
| 12m shoe joint vol: 0.178m ³ /· 12 = | <u>2. 1 m³</u> |
| Total slurry volume | = 113. 7 m ³ |

Use:

Preflush: 3 m³ (20 bbl) mud flush

Lead : Class G+8% equiv. gel + 2% CaCl₂:
80 000 kg (1833 sx) equal to 96m³ slurry.

Tail in : Class G+ 1% CaCl₂: 22000 kg (516 sx)
equal to 15.94m³ slurry.

Displacement: 0.178m³/m · (430-12)m = 74.4 m³

Pressure gradient at the 20" shoe

$$\text{Pressure of tail in: } 0.189 \text{ bar/m} \cdot \frac{(17.0-2.1)\text{m}^3}{0.140\text{m}^3/\text{m}} = 20.0 \text{ bars}$$

$$\text{Pressure of lead: } 0.155 \text{ bar/m (430-106)} = \underline{\underline{50.2 \text{ bars}}}$$

$$\text{Pressure at 20" shoe} = 70.2 \text{ bars}$$

$$\text{Pressure gradient: } 70.2 \text{ bars/430m} = \underline{\underline{0.163 \text{ bar/m}}}$$

$$\text{Estimated formation integrity} = \underline{\underline{0.150 \text{ bar/m}}}$$

Note: There is a possibility to loose cement to the formation.

16" CASING CEMENT CALCULATIONS

The cement volume is calculated on the basis of theoretical annulus volume, the casing being cemented 100 m into the 20" casing shoe with 50% excess for the open hole section. The ratio dry-mixed/prehydrated gel is 4:1.

Data

| | | |
|--------------------------------|---|------------------------|
| Depth KB - sea bed | : | 111 m |
| Depth KB - 20" shoe | : | 430 m |
| Depth KB - 16" shoe | : | 1350 m |
| Annulus capacity 20" csg-16" | | |
| csg. | : | 48 l/m |
| Annulus capacity 19½" hole-16" | | |
| csg. | : | 63 l/m |
| Internal capacity 16" csg. | : | 116 l/m |
| Mud weight: | : | 1.40 g/cm ³ |
| Formation integrity 16" shoe | : | 0.20 bar/m |
| BHST | : | 45°C |

Cement data using fresh water for the gel cement and sea water for the neat cement.

| | Class G + 8% equiv. gel + 0.5% CFR-2 | Class G+1% CFR-2 + 0.1 % HR-7 |
|--|---|----------------------------------|
| mix water , 1/100 kg (gal/sx) | 88 (10.0) fresh | 44 (5.0) sea |
| Slurry weight, g/cm ³ (ppg) | 1.58 (13.2) | 1.89 (15.8) |
| Slurry yield, 1/100 kg (ft ³ /sx) | 120 (1.82) | 76 (1.15) |
| Thickening time(hr:min) | 5:00 | 4:00 |
| 16 hr. comp. strength 45°C,bars(psi) | - | 100 (1500) |
| 24 " " " " | 35 (500) | 170 (2500) |

Volume calculations

| | | |
|---|---|---------------------|
| Open hole: 0.063m ³ /m · (1350-430)m | = | 58.0 m ³ |
| Open hole excess 50% | = | 29.0 m ³ |
| Cased hole annulus: 0.048m ³ /m · 100m | = | 4.8 m ³ |
| 24 m shoe joint: 0.116m ³ · 24 m | = | 2.8 m ³ |
| Total slurry volume | = | 94.6 m ³ |

Use:

Preflush: 1.5 m³ sea water.

Lead: Class G +8% equiv. gel + 0.5% CFR-2 : 65000 kg
(1525sx) equal to 78.0 m³ slurry

Tail in: Class G + 1% CFR2 + 0.1% HR7: 22000 kg
(516 sx) equal to 16.7m³ slurry

Displacement: 0.116 m³/m (1350-12) m = 155.2m³

Pressure gradient at the 16" shoe.

$$\text{Pressure of tail in: } 0.186 \text{ bar/m} \cdot \frac{(16.7 - 2.8) \text{ m}^3}{0.063 \text{ m}^3/\text{m}} = 41.1 \text{ bars}$$

$$\text{Pressure lead: } 0.155 \text{ bar/m} \cdot (1350 - 221) \text{ m} = 175.0$$

$$\text{Pressure at 16" shoe} \quad 216.1 \text{ bars}$$

$$\text{Pressure gradient at 16" shoe: } 216.1 \text{ bar/1350m} \\ = 0.150 \text{ bar/m}$$

Estimated formation integrity: 0.20 bar/m

13 3/8" CASING CEMENT CALCULATIONS

The casing is to be cemented in two stages, 2800 - 1450 m and 1450 - 850 m. The cement volumes are calculated on the basis of theoretical annulus volume with 25% excess.

Data

| | | |
|--------------------------------|---|------------------------|
| Depth KB - sea bed | : | 111 m |
| Depth KB - 16" shoe | : | 1350 m 1345 |
| Depth KB - DV-tool | : | 1450 m |
| Depth KB - 13 3/8" Shoe | : | 2800 m |
| Annulus capacity : 17½" hole - | | |
| 13 3/8" csg. | : | 64.5 l/m |
| Annulus capacity: 16" csg. | | |
| - 13 3/8" csg. | : | 25.2 l/m |
| Internal capacity 13 3/8" csg | | 77.2 l/m |
| Mud weight: | : | 1.84 g/cm ³ |
| BHST: | : | 110°C |

Cement data

| | Class G+0.7% CFR-2 +0.1% HR-7 | Class G+0.7% CFR-2 +0.2% HR-7 |
|---|----------------------------------|----------------------------------|
| <i>i_{cu} - i_{mn} = 46-7</i> <i>,11-5 %</i> | | |
| Mix water, fresh, l/100 kg (gal/sx) | 44 (5.0) | 44 (5.0) |
| Slurry weight, g/cm ³ (ppg) | 1.89 (15.8) | 1.89 (15.8) |
| Slurry yield, l/100kg (ft ³ /sx) | 76 (1.15) | 76 (1.15) |
| Thickening time, hr: min | 4:00+ | 4:00+ |
| 12 hrs compr. strength, bars (psi) | 70 (1000), 45°C | 240 (3500), 110°C |
| 24 hrs compr. strength, bars (psi) | 150 (2200), 45°C | 255 (3700), 110°C |

radio telex from dyvi gamma / lfqx 3.10.77

to: telex no 33349 statoil base, stavanger

attn. ed diamond and paul gautreaux

7th floor
re: 13-3/8" cementing job.

we have reviewed the coming cmt.-job, and have the following comments:

- 1: would like to have a telex stating what percentages of additives should be used on each stage.
- 2: also need the new thickening times stated.
20 sec/m
-10 min
suppose fresh water only being used for this job.
- 3: first stage seems to be rather unrealistic in volume.
a: mixing time for 3300 sx of cmt will be at least 1,5 hrs.
b: displacing this stage at 8 bbl/min will take about 3 hrs.
we consider this pumping rate being close to maximum.
c: conclusion: need at least 4,5 hrs to do this job if 6.7
everything works fine.
d: we do not recommend pumping top of cement up to d.v. tool,
as this may create problems with the latter.

suggestions:

first stage: bring cmt 500 m above shoe of 13-3/8" csg.
no additional cmt.

second stage: use calculated volume to bring cmt 500 m above 16" csg shoe. no excess cmt to be added.

re: balling of drillpipe and drillcollars.

due to excessive balling on the drillstring which may create problems for the underreaming, we would like to try to reduce this by adding a chemical to the mud.

suggest: magcobar: lub-coat, 4 ppb.
this is a graphite product.

regards

pilow/kjeldstad

19-3. D4VI GAMMA.

Cementing program 13 $\frac{7}{8}$ " casing.

Add him to drilling program.

VOLUME REQUIREMENTS.

First stage 2750 - 2250 m

Assume 18" hole (based on caliper from 14 $\frac{3}{4}$ " hole)

Open hole: $0.02 \text{ m}^3/\text{m} \times (2750 - 2250) = 34.2 \text{ m}^3$

Open hole excess 25% = 8.6 "

24 m shoe joint: $0.072 \text{ m}^3/\text{m} \times 24 = 1.9 \text{ "}$

Total slurry volume stage one: 44.7 m³

Total ^{dry} cement requirement: 60000 kg (1390 sc)

Second stage 1450 - 250 m

Open hole: $0.02 \text{ m}^3/\text{m} \times (1450 - 1205) = 2.3 \text{ m}^3$

Washout: $0.16 \text{ m}^3/\text{m} \times 15 \text{ m} = 2.3 \text{ "}$

Cased annulus: $0.0282 \times (1205 - 245) = 27.7 \text{ "}$

Excess cement: 0% = 0.0 "

Total slurry volume stage two: = 32.3 m³

Total dry cement requirement: 50000 kg (1155 sc)

2

CHEMICALS.

First stage: 0.7% CFR-2
 % HRZ

Second stage: 0.7% CFR-2
 % HRZ

Note! With red CFR 2 add defoamer NF1
to mix water at a concentration
of 2 pints NF1 / 10 gallons mix water.

From W. Christensen

0.2 102 0.5 102

S. 2 gabs/salt fresh water

5.8 102

116 1.16 ft

5.5 obs in fish net

2.3. + thick fine

4 102. thick 5.38 m.

24 hr 5 102 13. 4200 ps
115 sec

4 102

Ind stay 2-CP o. to He 2.

S. 2 gabs/salt

66. 38 m. no return; 56m 2m.

24 hr 102 2825 psi | 66 30 m.
51 20 m

PWC 5/10-72.

19-3. DYVI GOMMA.

CEMENTING PROGRAM 13 3/8" CASING.

8/10 - 82

14-3 Dry Gamma

Cementing 13³/₈" csg.Variations from caliper.

1st stage : 2250 - 2250 m

| | |
|---------------|---------|
| 2250 - 2200 : | 16 " |
| 2200 - 2150 : | 15.5 " |
| 2150 - 2050 : | 15.25 " |
| 2050 - 2000 : | 15.25 " |
| 2000 - 1950 : | 15.25 " |
| 1950 - 1900 : | 15.5 " |
| 1900 - 1850 : | 16 " |
| 1850 - 1800 : | 16 " |
| 1800 - 1750 : | 16.5 " |
| 1750 - 1700 : | 17.5 " |

Average, 16 "

2nd stage (open hole)

| | |
|----------------|------------------------|
| 14150 - 1400 : | 17 " |
| 1400 - 1365 : | 17 " |
| 1365 - 1345 : | Assume 30' Factor 4.0. |

Volume requirement

1. stage

2250 - 2250

Assume 18" hole

$$\text{Open hole} : 0.0645 \left(\frac{18}{12.5}\right)^2 \times (2250 - 2250) = 34.2 \text{ m}^3$$

$$\text{Open hole excess} 25\% = 8.6 \text{ m}^3$$

$$24 \text{ cm slurry joint} : 0.0722 \frac{\text{m}^3}{\text{m}} \times 24 = 1.9 \text{ m}^3$$

$$\text{Total slurry volume stage one} : = 44.7 \text{ m}^3$$

2. stage

$$\text{Open hole} : 0.0645 \left(\frac{18}{12.5}\right)^2 \times 100 = 6.87 \text{ m}^3$$

$$\text{Cased annulus} : 0.0252 \times (1345 - 245) = 27.7$$

$$\text{Excess cement} : 0 \% = 0$$

$$\text{Total slurry volume stage two} : = 34 \text{ m}^3$$

"a:

First stage: Rebar weight per meter, $1.87 \frac{\text{ton}}{\text{m}^3}$

Cement quantity: 60000 kg (1390 sacs)

Class G + 0.8% (FR-2) + % HRF.

Second stage quantity

Cement weight: 45000 kg (1020 sacs)

Class G + 0.8% (FR-2) + % HRF

AWR. 3/10 - 77

CEMENT. 16 13 3/8" csg, 1/2" S Dyn Gamma.

1. Stage

Open hole: $0.0045 \text{ m}^2/\text{m} \cdot 500 = 32.25 \text{ m}^3$

Open hole excess, 25% - 8.06 -

24 m shot joint: $0.0322 \text{ m}^2/\text{m} \cdot 24 = \underline{1.9}$

Total stirring for stage one: $\underline{42.2 \text{ m}^3}$
- 258 8815

2. Stage

BS before : 23,85 m³
- 145 8815

USE:

1. stage: 56 000 kg

(1302 sec equal to 42.2 m^3)

2. stage: BS before.

Deframer NF1 W/ red CFR 2 : 2 pints/1000
mix water

1522 - 34

1584 - 29

1620 - 85

1666 - 24

1728 - 40

1980 - 84

3176 - 82

2552 - 56

2402 - 10

3580 - 32

2523 - 27

2680 - 83

3222 - 40

2843 - 51

Grasshopper

Slight probability.

Grasshopper

Grasshopper

Rev.

Our.

Crust is our
Our. for candidate.

Depth m

1610 - 1665

PROBABLE PERM

SD → SD/LSH Max. 280 Units.
Logs clear. Lith. clear.

{ 1755 - 1770

SD or LIMESTONE POSSIBLE PERMEABILITY
Logs not clear, but indication. Max. 470 units

1725 ± 2 1/2

SD described on lith. description.

1810

POSSIBLE PERM
No indications on logs
or lith. LS - streaks from Max. 665 units
Lith.

1950

PROBABLE PERM.
No indications on logs Max. 280 units.
~~or lith.~~ Only claystone

1990

PROBABLE
No SD indications on logs Max. 980 units.
~~or lith.~~ Silty, slight
carbonaceous shale.

2100

PROBABLE
Indications of SD on logs Max. 560 Units.
(caliper, gamma ray)
Nothing on lith.

2220 - 2300

SOME SD. Shaly PROBABLE Max. 200 units.

2320

Possible ?
SOME LIMEST from Lith. ? Max. 200 "

?

2400 - 2410

Limestone, shdr, ?

2520

Limest. Trig. gas.

2625

Max. 180 "

2715 - 35

PROBABLE
LS/LS - from logs
Coring, + densities

RWL 10/10/72

1/2-3. TEMPORARY ABANDONMENT. OPEN HOLE PLUGS.

Washout 1350-
1365 m

16" CSG 1345 m
9,332.4 gal/m
0.116 m³/m

Assume av. hole
size 18";
 $\approx 0.185^3/m$
 $\approx 13,219.2 \text{ gal}/\text{ft}$
17 1/2" HOLE 2114 m

2721

2771

Average hole size
from caliper: 16"
 $\approx 0.13^3/m$
 $\approx 10,444 \text{ gal}/\text{ft}$

14 3/4" HOLE 2771 m

HWC 11.10.77.

1/9-3. TEMPORARY ABANDONMENT. OPEN HOLE PLUGS.

Washout 1350 - 1365 m

280 ← Max 280 { 1615
280 ← Av. 200 { 1665

480 ← 1770 m
665 ← 1810 m Max 665 { 1760
Av. 400 { 1825

200 ← 1900 m

380 ← 1990 m Max 980 {
560 ← 2100 m Av. 180 {
250 ← 2185 m 2200

200 ← 2320 m

170 ← 2620 m

~ 0.126 m³/m

10 15.124°, 9.3324 gal/ft.

16" C59 1345 m

17 1/2" hole 2114 m

Assume average hole
size 18" ~ 0.16 m³/m
~ 13.2192 gal/ft.

14 3/4" hole 2771 m

Average hole size 16" from
caliper ~ 0.13 m³/m
~ 10.4448 gal/ft

Volume calculations:1. stage

| | | |
|--|---|---------------------------------------|
| Open hole: $0.0645 \text{ m}^3/\text{m} \cdot (2800-1450)\text{m}$ | = | 87.1 m^3 |
| Open hole excess, 25% | = | 21.8 m^3 |
| 24 m shoe joint: $0.0772 \text{ m}^3/\text{m} \cdot 24\text{m}$ | = | 1.9 m^3 |
| Total slurry for stage one: | | <u>110.8 m^3</u> |

2. stage

| | | |
|--|---|---------------------------------------|
| Open hole: $0.0645 \text{ m}^3/\text{m} \cdot (1450-1350)\text{m}$ | = | 6.45 m^3 |
| Cased annulus: $0.0252 \text{ m}^3/\text{m} \cdot 500 \text{ m}$ | = | 12.6 m^3 |
| Excess cement: $25\% \cdot (6.45+12.6)$ | = | 4.8 m^3 |
| Total slurry for stage two: | = | <u>23.85 m^3</u> |

Use:First stage

Preflush: 3.0 m^3 weighted spacer, 1.87 g/cm^3

Cement: Class G + 0.7% CFR-2 + 0.2% HR7: 146000 kg
 (3425 sx) equal to 111 m^3 slurry

Turbulent rate: $0.65 \text{ m}^3/\text{min}$ (4 bbls/min)
 Displacement: $0.0772 \text{ m}^3/\text{m} \cdot (2800-24)\text{m} = 214.3 \text{ m}^3$

Second stage

Preflush: 1.5 m^3 weighted spacer, 1.87 g/cm^3
 Cement: Class g + 0.7% CFR-2 + 0.1% HR-7:
 32000 kg (750 sx) equal to 24.2 m^3 slurry.

Turbulent rate: $0.65 \text{ m}^3/\text{min}$ (4 bbls/min)

Displacement: $0.0772 \text{ m}^3/\text{m} \cdot 1450 \text{ m} = 112 \text{ m}^3$

Estimated formation integrity for the open hole section: 0.20 bar/m which is greater than 0.186 bar/m cement gradient.

9 5/8" CASING CEMENT CALCULATIONS

The casing is to be cemented 500 m above the 13 3/8" casing shoe. The cement volume is calculated on the basis of theoretical annulus volume with 20% excess.

Data

| | | |
|--|---|-------------------------------|
| Depth KB - 13 3/8" shoe | : | 2 800 m |
| Depth KB - 9 5/8" shoe | : | 3 800 m |
| Annulus capacity 12 1/4" hole - 9 5/8" csg | : | 29.1 l/m |
| " " 13 3/8" csg - 9 5/8" csg | : | 30.3 " |
| Internal capacity 9 5/8" csg. 47 lb/ft | : | 38.2 " |
| " " 9 5/8" csg. 53.5 lb/ft | : | 36.9 " |
| Mud weight | : | 1.68 - 1.78 g/cm ³ |
| BHST | : | 135°C |

Cement data

Class G + 35% SSA - 1
+ 0.7% CFR-2, + 0.5% Halad 9
+ 0.1% HR 12

| | | |
|--|---------|---------|
| Mix water, fresh, l/100kg (gal/sx): | 46 | (5.2) |
| Slurry weight, g/cm ³ (ppg): | 1.90 | (15.86) |
| Slurry yield, l/lookg (ft ³ /sx): | 102 | (1.53) |
| Fluid loss, cm ³ /30 min: | 120-150 | |
| Thickening time, hr: min: | 4:30+ | |
| 12 hr compr. strength at 135°C, bars (PSI): | 225 | (3250) |

Volume calculations

| | | | |
|---------------------|---------------------------------------|---|---------------------|
| Open hole: | 0.0291 m ³ /m (3800-2800)m | = | 29.1 m ³ |
| Cased annulus: | 0.0303 m ³ /m · 500 m | = | 15.2 " |
| 20% excess: | (29.1 + 15.2) · 0.20 | = | 8.9 " |
| 24 m shoe joint: | 0.0382 m ³ /m · 24 | = | 0.9 " |
| Total slurry volume | | = | 54.1 m ³ |

Use:

Preflush: 3.0 m³ weighted spacer, 1.80 g/cm³

Cement: Class G + 35% SSA - 1 + 0.7% CFR - 2
 + 0.5% Halad 9 + 0.1% HR 12:
 53 000 kg (1243 sx) equal to 54.1 m³ slurry

Turbulent rate: 1.1 m³/min. (7 bbls/min)

Formation pressure integrity

The critical interval is Paleocene, approx. 100 m below the 13 3/8" casing shoe. Pressure while cementing at this point:

| | | |
|---------------------|----------------------|-----------------|
| Pressure of mud: | 0.175 bar/m · 2300 m | = 403 bars |
| Pressure of cement: | 0.187 bar/m · 600 m | = 112 " |
| Pressure at 2900 m: | | <u>515 bars</u> |

| | | |
|--------------------------------|-----------------|---------------|
| Pressure gradient: | 515 bars/2900 m | = 0.178 bar/m |
| Estimated formation integrity: | | 0.185 bar/m |

NOTE

The following additives from Halliburton are used:

| | | |
|------------|---|--|
| CFR - 2 | : | Friction reducer/water loss control additive |
| HR - 7 | : | Cement retarder |
| HR - 12 | : | Cement retarder |
| Halad - 12 | : | Water loss control additive |
| SSA - 1 | : | Silica Flour |



statoil
Den norske stats oljeselskap a.s.

46)

0m RKB



REF LEVEL

WELL NO. 1/9-3 PHASE I

NOT TO SCALE


36" grade B, $1\frac{1}{2}$ " thickness. Cement to sea floor + 150%

20", K-55, 133 lbs/ft. Cement to sea floor + 150%

16" N 80, 75 lbs/ft. Cement 100 m into 20" shoe + 50%

13 3/8", N 80, 72 lbs/ft
Cement 2 stages: 2800 - 1450 m
and 1450 - 850 m
Excess: 25%

9 5/8", N 80: 0 - 2950 m: 47 lbs/ft
2950 - 3300 m: 53.5 lbs/ft
3300 - 3800 m: 47 lbs/ft
Cement 500 m into 13 3/8" shoe + 20%



ORIGINAL
CEMENT



ABANDONMENT
CEMENT
PLUG

Fig. 1. Comparison between 119-1 and 119-3

Depth below sea - meters




Fig. 2. Well 1/9-1 Formation Pore Pressure and Fracture Pressure Evaluation.




Figure 3

491

FORMATION TEMPERATURE
PROFILE FOR 1/9 BASED ON
INFORMATIONS FROM ADJACENT
WELLS.

DEPTH
RKB x 1000

m ft
0 0

1

0.5
2

3

1.0
4

1.5
5

6

2.0
7

2.5
8

9

3.0
10

11

3.5
12

13

4.0
14

4.5
15

Control wells: 2/6-2

2/7-2, -7, -9, -10

2/8-3

2/10-1

2/11-2

Note: o = Log Values

x = DST Values

\otimes = 1/9-DST Values

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

0 000

60 100 140 180 220 260 300 °F

20 40 60 80 100 120 140 160 °C

Temperature


Fig. 4. Kick Control Calculations.


Capacities:

$$14\frac{3}{4}'' - 5'' : 97.6 \text{ l/m}$$


$$12\frac{1}{4}'' - 5'' : 63.4 \text{ "}$$

$$8\frac{1}{2}'' - 5'' : 23.9 \text{ "}$$






| WELL | 1/6-2 | 2/7-4 | 1/9-1 |
|-----------------------|---------|-----------|------------|
| DEPTH (MSL) | -2988m | -3066m | -309m |
| V _s (TRUE) | 207m/s | 2035m/s | 1987m/s |
| T (TRUE) | 2.962s | 3.03s | 3.039 sec |
| T (SEISMIC) | 2.982s | 3.03s | 3.066 sec |
| V (SEISMIC) | 2004m/s | 2022m/s | 1989 m/sec |
| LAG | 0.020s | 0.020 sec | 0.027 sec |



The Statoil logo consists of a stylized oil drop icon followed by the word "statoil" in lowercase, with the tagline "Den norske oljemagasinet" underneath.



SCENE THREE

100