SCHLUMBERGER WELL SERVICES, INC.
RUN NO. ONE DATE 10-15-74
API SERIAL NO. 50-029-20276
COMPUTATION NO.

AMOCO NORWAY OIL CO.

40/10-4

FIELD EKOFISK

LOCATION: 57° 30' 58.5" N
2° 43' 29.5" E
OTHER SERVICES: DIL-BHC-GR
LDT-CNL-GR
HDT
RFT
WST
DIPLOG
DATA AVAILABLE: 10-15-74

PERMANENT DATUM	ELEV. 0
LOG MEASURED FROM	RT 72 FT ABOVE PERM. DATUM
DRILLING MEASURED FROM	RT

RUN NO.	ONE	
DATE	10-15-74	
TYPE LOG	DIL	
DEPTH-DRILLER	11,000	
DEPTH-LOGGER	11,000	
BTM. LOG INTERVAL	10,998	
TOP LOG INTERVAL	10,000	
CASING-DRILLER	13 3/8 @ 10,000	
CASING-LOGGER	10,000	
BIT SIZE	12 1/4	
TYPE FLUID IN HOLE	LIGNOSULFONATE	
DENS. VISC.	10.2 LB/G 40 S	
PH	10.5	
FLUID LOSS	4.2 C3	
SOURCE OF SAMPLE	FLOWLINE	
RM @ MEAS. TEMP.	.14 @ 150 °F	
RMF @ MEAS. TEMP.	.12 @ 150 °F	
RMC @ MEAS. TEMP.	.18 @ 150 °F	
SOURCE RMF	MEASURED	
SOURCE RMC	MEASURED	
RM @ BHT	.07 @ 250 °F	
TIME SINCE CIRC.	12 HRS	
MAX. REC. TEMP.	250 °F	
EQUIP. LOCATION	4054	
RECORDED BY	HOLLAND	
WITNESSED BY	MR. MOSS	

RUN NO.	ONE	
DATE	10-15-74	
TYPE LOG	LDT-CNL-GR	
DEPTH-DRILLER	11,000	
DEPTH-LOGGER	11,000	
BTM. LOG INTERVAL	10,998	
TOP LOG INTERVAL	10,000	
CASING-DRILLER	13 3/8 @ 10,000	
CASING-LOGGER	10,000	
BIT SIZE	12 1/4	
TYPE FLUID IN HOLE	LIGNOSULFONATE	
DENS. VISC.	10.2 LB/G 40 S	
PH	10.5	
FLUID LOSS	4.2 C3	
SOURCE OF SAMPLE	FLOWLINE	
RM @ MEAS. TEMP.	.14 @ 150 °F	
RMF @ MEAS. TEMP.	.12 @ 150 °F	
RMC @ MEAS. TEMP.	.18 @ 150 °F	
SOURCE RMF	MEASURED	
SOURCE RMC	MEASURED	
RM @ BHT	.07 @ 250 °F	
TIME SINCE CIRC.	12 HRS	
MAX. REC. TEMP.	250 °F	
EQUIP. LOCATION	4054	
RECORDED BY	HOLLAND	
WITNESSED BY	MR. MOSS	

RUN NO.	ONE	
DATE	10-15-74	
TYPE LOG	HDT	
DEPTH-DRILLER	11,000	
DEPTH-LOGGER	11,000	
BTM. LOG INTERVAL	10,998	
TOP LOG INTERVAL	10,000	
CASING-DRILLER	13 3/8 @ 10,000	
CASING-LOGGER	10,000	
BIT SIZE	12 1/4	
TYPE FLUID IN HOLE	LIGNOSULFONATE	
DENS. VISC.	10.2 LB/G 40 S	
PH	10.5	
FLUID LOSS	4.2 C3	
SOURCE OF SAMPLE	FLOWLINE	
RM @ MEAS. TEMP.	.14 @ 150 °F	
RMF @ MEAS. TEMP.	.12 @ 150 °F	
RMC @ MEAS. TEMP.	.18 @ 150 °F	
SOURCE RMF	MEASURED	
SOURCE RMC	MEASURED	
RM @ BHT	.07 @ 250 °F	
TIME SINCE CIRC.	12 HRS	
MAX. REC. TEMP.	250 °F	
EQUIP. LOCATION	4054	
RECORDED BY	HOLLAND	
WITNESSED BY	MR. MOSS	

RUN NO.	ONE	
DATE	10-15-74	
TYPE LOG	WST	
DEPTH-DRILLER	11,000	
DEPTH-LOGGER	11,000	
BTM. LOG INTERVAL	10,998	
TOP LOG INTERVAL	10,000	
CASING-DRILLER	13 3/8 @ 10,000	
CASING-LOGGER	10,000	
BIT SIZE	12 1/4	
TYPE FLUID IN HOLE	LIGNOSULFONATE	
DENS. VISC.	10.2 LB/G 40 S	
PH	10.5	
FLUID LOSS	4.2 C3	
SOURCE OF SAMPLE	FLOWLINE	
RM @ MEAS. TEMP.	.14 @ 150 °F	
RMF @ MEAS. TEMP.	.12 @ 150 °F	
RMC @ MEAS. TEMP.	.18 @ 150 °F	
SOURCE RMF	MEASURED	
SOURCE RMC	MEASURED	
RM @ BHT	.07 @ 250 °F	
TIME SINCE CIRC.	12 HRS	
MAX. REC. TEMP.	250 °F	
EQUIP. LOCATION	4054	
RECORDED BY	HOLLAND	
WITNESSED BY	MR. MOSS	

RUN NO.	ONE	
DATE	10-15-74	
TYPE LOG	DIPLOG	
DEPTH-DRILLER	11,000	
DEPTH-LOGGER	11,000	
BTM. LOG INTERVAL	10,998	
TOP LOG INTERVAL	10,000	
CASING-DRILLER	13 3/8 @ 10,000	
CASING-LOGGER	10,000	
BIT SIZE	12 1/4	
TYPE FLUID IN HOLE	LIGNOSULFONATE	
DENS. VISC.	10.2 LB/G 40 S	
PH	10.5	
FLUID LOSS	4.2 C3	
SOURCE OF SAMPLE	FLOWLINE	
RM @ MEAS. TEMP.	.14 @ 150 °F	
RMF @ MEAS. TEMP.	.12 @ 150 °F	
RMC @ MEAS. TEMP.	.18 @ 150 °F	
SOURCE RMF	MEASURED	
SOURCE RMC	MEASURED	
RM @ BHT	.07 @ 250 °F	
TIME SINCE CIRC.	12 HRS	
MAX. REC. TEMP.	250 °F	
EQUIP. LOCATION	4054	
RECORDED BY	HOLLAND	
WITNESSED BY	MR. MOSS	

RUN NO.		
DATE		
TYPE LOG		
DEPTH-DRILLER		
DEPTH-LOGGER		
BTM. LOG INTERVAL		
TOP LOG INTERVAL		
CASING-DRILLER		
CASING-LOGGER		
BIT SIZE		
TYPE FLUID IN HOLE		
DENS. VISC.		
PH		
FLUID LOSS		
SOURCE OF SAMPLE		
RM @ MEAS. TEMP.		
RMF @ MEAS. TEMP.		
RMC @ MEAS. TEMP.		
SOURCE RMF		
SOURCE RMC		
RM @ BHT		
TIME SINCE CIRC.		
MAX. REC. TEMP.		
EQUIP. LOCATION		
RECORDED BY		
WITNESSED BY