

WELL : 25/1-4

REMARKS CONCERNING LOG INTERPRETATION BY PICARDIA

- 1) - The log raw data of SCHLUMBERGER'S CERT tape n° 113-7715 have been used for this study. One thousand levels have been computed (depth step-interval : .2 meter).
- 2) - Resistivity and GAMMA-RAY readings are corrected for bore hole size, mud and mud-cake effects. Invasion (Di) effect has been estimated according to the available charts for Dual-laterolog - MLL combination to obtain Rxo and Rt. For Di > 150", Rt values are unrealistic. In this case (intervals 2068 - 2100 and 2114 - 2125 m) the deep Laterolog readings are taken as Rt values.
- 3) - The salinity of the formation water as obtained through cross plots (I/\sqrt{Rt} versus ρ_b , ϕ_N or Δt) is in good agreement with the known field data.

A recalibration of the density log is necessary, as indicated by the Neutron - Density plot in the water zone :

$$\rho_b = f_{FDC} + .04$$

- 4) - Shaliness values given by the GAMMA-RAY and the Density-Neutron indicators (after hydrocarbon corrections) agree.

Resistivity shaliness indicators (Rt and Rxo) remain too high.

The base line of the S.P. curve cannot be clearly established, even in the water-zone ; so the SP shaliness indicator has not been taken into consideration.

The log readings in front of the shaly sections at the top are affected by big caves.

.../...

SHALE parameters, read in front of the shaly zone : 2 500 - 2 525 are :

$$\begin{aligned}\rho_{sh} &= 2.36 \\ \phi_{Nsh} &= .38 \text{ (limestone porosity units)} \\ R_{sh} &= 1.5 \\ GR &= 75 \text{ API units}\end{aligned}$$

GR reading in front of clean zones : 22 API units

5) -

5-1 In the water zone, the sub-program LITHO computes :

$$V_{sh}, \rho_{ma}, \phi, S_w$$

In this case, the value of the residual hydrocarbon density is imposed to be :

$$\rho_h = .82$$

5-2 In the hydrocarbon zone (1967.7 - 2009.1 m), the sub-program NEUDER computes :

$$V_{sh}, \phi, S_w, \rho_h$$

In this case ρ_{ma} is taken equal to the average value (2.68) of the matrix-density calculated into the water zone. The ρ_h values obtained in this manner do not check perfectly with the measured field data ($\rho_{gas} = .14$ and $\rho_{oil} = .82$). However it is easy to distinguish between gas and oil bearing sections and to establish the following contacts between fluids :

Gas/oil contact at : 2005.5 m

Oil/water contact at : 2008.1 m

6) - In the hydrocarbon zone, a summation of $h \phi (1 - S_w)$ is made, with and without the following cut-off values :

$$\begin{aligned}\phi &\geq .13 \\ S_w &\leq .55 \\ V_{sh} &\leq .33\end{aligned}$$

Between 2009 and 2050 m, in the water zone, a summation of $h \phi$ is made with and without the same shaliness and porosity cut-off values.

LOG DATA SOURCES

SCHLUMBERGER EDIT TAPE

UNITS USED

DEPTH = METER
TEMPERATURE = DEGREE FAHRENHEIT

AVAILABLE LOGS

MICROLATERCLOGG
LATERCLOG 95
LATERCLOG 90
INDUCTION 6
GAMMA RAY
S.P.
B.H.CCMP.SCNIC LOG
CCMP. DENSITY LOG
DENSITY CORRECTION
CNL
MICROCALIPER

CORE DATA

NO DATA USED

ANALYSIS METHOD

CONTINUOUS SAMPLING

ZONE FROM 1950.00 TO 1967.50

GENERAL PARAMETERS

BORE HOLE

BIT SIZE = 8.50 INCHES

TEMPERATURE = 128.6 DEGREES F (TOP OF ZONE)

TEMP. = .0351847 DEPTH + 59.9648100

MUD

RM = .1354

RMF = .0597

RMC = .3209

MUD DENSITY = 1.250 GR/CC

FILTRATE DENSITY = 1.023 GR/CC

FILTRATE SALINITY = 38800. PPM

NATURAL

FORMATION FLUID

WATER

	RW	DENSITY	SALINITY (PPM)
FIRST DATUM	.0667	1.0396	61800.
SECOND DATUM	*****	*****	*****
THIRD DATUM	*****	*****	*****
SP METHOD	*****	*****	*****
PICKET METHOD	*****	*****	*****
ACTIVITIES METHOD	*****	*****	*****
DUNLAP-SCHLUM. METHOD	*****	*****	*****

RW SELECTED = .0667

HYDROCARBON

COMPUTED PARAMETERS

LITHOLOGY

CLAY

RESISTIVITY = 1.50 OHMS

DENSITY = 2.000

G.R. = 60.0

NEUTRON = .52

DELTA-T = 107.0

COMPACTION INDEX(C) = 1.0

MATRIX

NATURE = SANDSTONE

DENSITY = 2.680

G.R. = 22.0

NEUTRON = ****

DELTA-T = 52.0

COMPUTATION PROCESS

RESISTIVITY-INVASION
COMPUTATION FROM
MICROCLATEROLOG
LATERCLOG 95
LATERCLOG 90

CLAY CONTENT
CLAY CONTENTS IMPOSED

POROSITY
COMPUTATION FROM
CNL
COMP. DENSITY LCG
NEUTRON CALIBRATION PHIN = 1.000000 NEU.API + .0200
FORMATION FACTOR (A) = 1.00
(M) = 2.00

SATURATION
SATURATION FORMULA
PCUPCA
SATURATION EXPONENT (N) = 2.00
SKO/SW EXPONENT (E) = 5.00

ZONE FROM 1967.50 TO 2008.90

GENERAL PARAMETERS

BORE HOLE

BIT SIZE = 8.50 INCHES

TEMPERATURE = 129.2 DEGREES F (TOP OF ZONE) TEMP. = .0351847 DEPTH + 59.9648100

MUD

RM = .1348

RMF = .0993

RMC = .3195

MUD DENSITY = 1.250 GR/CC

FILTRATE DENSITY = 1.023 GR/CC

FILTRATE SALINITY = 38800. PPM

NATURAL

FORMATION FLUID

WATER

RW SELECTED = .0667

HYDROCARBON

COMPUTED PARAMETERS

LITHOLOGY

CLAY

RESISTIVITY = 1.50 OHMS

DENSITY = 2.400

G.R. = 73.0

NEUTRON = .38

DELTA-T = 107.0

COMPACTION INDEX(C) = 1.0

MATRIX

NATURE = SANDSTONE

DENSITY = 2.680

G.R. = 22.0

NEUTRON = ****

DELTA-T = 52.0

COMPUTATION PROCESS

RESISTIVITY-INVASION
COMPUTATION FROM
MICRCLATEROLCG
LATERCLOG 95
LATERCLOG 90

CLAY CONTENT
COMPUTATION FROM
VSP G.R.

POROSITY
COMPUTATION FROM
CAL
CCMP. DENSITY LCG
NEUTRON CALIBRATION PHIN = $1.000000 \text{ NEU-API} + .0200$
FORMATION FACTOR (A) = 1.00
(#) = 2.00

SATURATION
SATURATION FORMULA
PCUPCK

SATURATION EXPONENT (N) = 2.00
SXO/SW EXPONENT (E) = 5.00

ZONE FROM 2008.90 TO 2149.90

GENERAL PARAMETERS

BORE HOLE

BIT SIZE = 8.50 INCHES

TEMPERATURE = 130.7 DEGREES F (TCP OF ZONE) TEMP. = .0351847 DEPTH + 59.9648100

MUD

RM = .1334

RMF = .0982

RMC = .3161

MUD DENSITY = 1.250 GR/CC

FILTRATE DENSITY = 1.023 GR/CC

FILTRATE SALINITY = 38800. PPM

NATURAL

FORMATION FLUID

WATER

PW SELECTED = .0667

HYDROCARBON

SUPPOSED NATURE = OIL

DENSITY = .820

NEUTRON HYDROGEN INDEX = 1.1164

LITHOLOGY

CLAY

RESISTIVITY = 1.50 OHMS

DENSITY = 2.400

G.R. = 73.0

NEUTRON = .38

DELTA-T = 107.0

COMPACTION INDEX(C) = 1.0

MATRIX

COMPUTED

COMPUTATION PROCESS

RESISTIVITY-INVASION
COMPUTATION FROM
MICRCLATEROLOG
LATERCLOG 95
LATERCLOG 9D

CLAY CONTENT
COMPUTATION FROM
VSF G.R.

POROSITY
COMPUTATION FROM
CAL
CCMP. DENSITY LOG
NEUTRON CALIBRATION PHIN = $1.000000 \text{ NEU-API} + 0.0000$

FORMATION FACTOR (A) = 1.00
(M) = 2.00

SATURATION
SATURATION FORMULA
PCUPCA

SATURATION EXPONENT (N) = 2.00
SXO/SW EXPONENT (E) = 5.00

RT	Z=GR
.150**	1
.189**	
.245**	
.330**	1
.469**	1
.718**	4
1.236**	16
2.608**	28
8.711**	53
293.000**	121

* * * * *	2112111131	111131	2	114988A8F9FLKLILCALMJIICFCC8EE67ACCBCCDFD6AC6624685115221	1	11
* * * * *	* * * * *	* * * * *	* * * * *	* * * * *	* * * * *	* * * * *
5	5	6	6	7	7	8
0	5	0	5	0	5	0
0	0	0	0	0	0	0
0	0	0	0	0	0	0

NIVEAU	TCIT	ARG.	POR.	SXC	SW	C.HY.	C.MAT.	NEU	DEN	SCN	SEC	VST-GR
1	1949.9	100.01	0.0	*****	*****	****	2.680	49.4	35.5	75.8	****	C.C
2	1950.1	100.01	0.0	*****	*****	****	2.680	50.0	35.8	76.7	****	C.C
3	1950.3	100.01	0.0	*****	*****	****	2.680	50.0	34.0	77.8	****	C.C
4	1950.5	100.01	0.0	*****	*****	****	2.680	50.8	34.2	79.0	****	C.C
5	1950.7	100.01	0.0	*****	*****	****	2.680	50.0	36.2	80.1	****	C.C
6	1950.9	100.01	0.0	*****	*****	****	2.680	50.4	37.3	81.1	****	C.C
7	1951.1	100.01	0.0	*****	*****	****	2.680	50.7	37.7	81.3	****	C.C
8	1951.3	100.01	0.0	*****	*****	****	2.680	49.9	36.9	82.0	****	C.C
9	1951.5	100.01	0.0	*****	*****	****	2.680	50.6	37.5	83.5	****	C.C
10	1951.7	100.01	0.0	*****	*****	****	2.680	51.6	37.2	84.3	****	C.C
11	1951.9	100.01	1.0	100.0	96.4	****	2.680	53.0	37.3	83.4	****	C.C
12	1952.1	91.C	*****	*****	*****	****CF	2.680ER	53.9	36.2	83.4	****	C.C
13	1952.3	100.01	1.5	100.0	99.3	****	2.680	53.5	38.1	82.8	****	C.C
14	1952.5	100.01	1.5	100.0	110.9	****	2.680	53.5	39.8	82.6	****	C.C
15	1952.7	100.01	2.1	100.0	122.1	****	2.680	54.1	40.1	81.6	****	C.C
16	1952.9	100.01	2.6	100.0	111.1	****	2.680	54.6	39.8	85.0	****	C.C
17	1953.1	100.01	1.7	100.0	108.9	****	2.680	53.7	39.1	81.2	****	C.C
18	1953.3	100.01	1.9	100.0	101.2	****	2.680	53.8	38.8	81.5	****	C.C
19	1953.5	100.01	2.0	100.0	121.9	****	2.680	54.0	38.9	81.4	****	C.C
20	1953.7	100.01	1.0	100.0	134.0	****	2.680	53.0	39.3	79.9	****	C.C
21	1953.9	100.01	0.0	*****	*****	****	2.680	52.2	39.0	80.7	****	C.C
22	1954.1	100.01	0.0	*****	*****	****	2.680	50.8	39.2	84.5	****	C.C
23	1954.3	100.01	0.0	*****	*****	****	2.680	52.3	39.7	81.4	****	C.C
24	1954.5	100.01	2.1	100.0	89.6	****	2.680	54.1	41.0	81.6	****	C.C
25	1954.7	100.01	1.4	100.0	96.6	****	2.680	53.4	40.7	81.8	****	C.C
26	1954.9	100.01	0.0	*****	*****	****	2.680	51.6	41.8	81.8	****	C.C
27	1955.1	100.01	0.0	*****	*****	****	2.680	51.5	42.0	81.2	****	C.C
28	1955.3	100.01	0.0	*****	*****	****	2.680	51.4	40.7	80.7	****	C.C
29	1955.5	100.01	0.0	*****	*****	****	2.680	50.9	40.2	80.5	****	C.C
30	1955.7	100.01	0.0	*****	*****	****	2.680	49.7	38.4	81.0	****	C.C
31	1955.9	100.01	0.0	*****	*****	****	2.680	50.0	38.4	81.3	****	C.C
32	1956.1	100.01	0.0	*****	*****	****	2.680	51.4	38.8	81.8	****	C.C
33	1956.3	100.01	0.0	*****	*****	****	2.680	51.7	40.5	81.6	****	C.C
34	1956.5	100.01	.7	100.0	116.2	****	2.680	52.7	40.8	81.3	****	C.C
35	1956.7	100.01	0.0	*****	*****	****	2.680	51.4	41.4	81.2	****	C.C
36	1956.9	100.01	0.0	*****	*****	****	2.680	49.7	40.0	81.2	****	C.C
37	1957.1	100.01	0.0	*****	*****	****	2.680	49.0	38.2	80.2	****	C.C
38	1957.3	100.01	0.0	*****	*****	****	2.680	50.3	38.4	79.1	****	C.C
39	1957.5	100.01	0.0	*****	*****	****	2.680	51.9	38.5	78.3	****	C.C
40	1957.7	100.01	0.0	*****	*****	****	2.680	50.4	39.2	79.0	****	C.C
41	1957.9	100.01	0.0	*****	*****	****	2.680	48.6	38.7	85.5	****	C.C
42	1958.1	100.01	0.0	*****	*****	****	2.680	48.6	38.2	82.1	****	C.C
43	1958.3	100.01	0.0	*****	*****	****	2.680	48.8	38.2	82.6	****	C.C
44	1958.5	100.01	0.0	*****	*****	****	2.680	49.0	39.4	96.6	****	C.C
45	1958.7	100.01	0.0	*****	*****	****	2.680	51.1	40.2	97.5	****	C.C
46	1958.9	100.01	0.0	*****	*****	****	2.680	51.5	40.7	98.7	****	C.C
47	1959.1	100.01	0.0	*****	*****	****	2.680	49.9	40.0	99.1	****	C.C
48	1959.3	100.01	0.0	*****	*****	****	2.680	48.8	39.1	99.6	****	C.C
49	1959.5	100.01	0.0	*****	*****	****	2.680	46.2	38.4	98.9	****	C.C
50	1959.7	100.01	0.0	*****	*****	****	2.680	46.7	37.2	98.1	****	C.C

NIVEAU	TOIT	ARG.	PGR.	SXC	SW	C.FY.	C.PAT.	NEU	GEN	SCN	SEC	VSTGR
51	1959.9	ICC.CI	0.0	*****	*****	***	2.68C	48.3	37.7	97.3	***	C.C
52	1960.1	ICC.CI	0.0	*****	*****	***	2.68C	49.4	40.4	95.7	***	C.C
53	1960.3	ICC.CI	0.0	*****	*****	***	2.68C	49.6	41.5	93.6	***	C.C
54	1960.5	ICC.CI	0.0	*****	*****	***	2.68C	49.2	35.8	91.4	***	C.C
55	1960.7	ICC.OI	0.0	*****	*****	***	2.68C	50.4	38.2	85.3	***	C.C
56	1960.9	O.CMA	*****CV	*****CV	*****	***	****CV	50.2	37.0	82.1	***	C.C
57	1961.1	O.CMA	*****CV	*****CV	*****	***	****CV	48.9	35.1	80.4	***	C.C
58	1961.3	O.CMA	*****CV	*****CV	*****	***	****CV	49.5	34.7	79.1	***	C.C
59	1961.5	O.CMA	*****CV	*****CV	*****	***	****CV	50.3	34.2	76.5	***	C.C
60	1961.7	O.CMA	*****CV	*****CV	*****	***	****CV	51.3	33.5	74.3	***	C.C
61	1961.9	ICC.CI	0.0	*****	*****	***	2.68C	51.7	33.8	68.8	***	C.C
62	1962.1	ICC.CI	0.0	*****	*****	***	2.68C	50.5	33.9	66.9	***	C.C
63	1962.3	O.CMA	*****CV	*****CV	*****	***	****CV	48.2	33.3	67.8	***	C.C
64	1962.5	O.CMA	*****CV	*****CV	*****	***	****CV	45.9	33.5	68.2	***	C.C
65	1962.7	ICC.CI	0.0	*****	*****	***	2.68C	44.8	34.5	67.4	***	C.C
66	1962.9	ICC.CI	0.0	*****	*****	***	2.68C	45.2	35.2	67.9	***	C.C
67	1963.1	ICC.CI	0.0	*****	*****	***	2.68C	46.4	34.7	73.5	***	C.C
68	1963.3	ICC.CI	0.0	*****	*****	***	2.68C	47.6	35.7	76.3	***	C.C
69	1963.5	ICC.CI	0.0	*****	*****	***	2.68C	47.3	35.8	78.1	***	C.C
70	1963.7	ICC.CI	0.0	*****	*****	***	2.68C	48.0	37.1	81.4	***	C.C
71	1963.9	ICC.CI	0.0	*****	*****	***	2.68C	50.0	38.0	83.5	***	C.C
72	1964.1	ICC.CI	0.0	*****	*****	***	2.68C	50.9	38.0	85.1	***	C.C
73	1964.3	ICC.CI	0.0	*****	*****	***	2.68C	48.4	39.5	84.2	***	C.C
74	1964.5	O.CMA	*****CV	*****CV	*****	***	****CV	48.2	40.9	81.0	***	C.C
75	1964.7	O.CMA	*****CV	*****CV	*****	***	****CV	48.7	41.4	79.6	***	C.C
76	1964.9	O.CMA	*****CV	*****CV	*****	***	****CV	48.6	40.5	75.5	***	C.C
77	1965.1	O.CMA	*****CV	*****CV	*****	***	****CV	46.1	39.2	65.5	***	C.C
78	1965.3	O.CMA	*****CV	*****CV	*****	***	****CV	44.2	35.9	65.5	***	C.C
79	1965.5	ICC.CI	0.0	*****	*****	***	2.68C	43.9	32.9	64.0	***	C.C
80	1965.7	O.CMA	*****CV	*****CV	*****	***	****CV	45.0	30.9	65.7	***	C.C
81	1965.9	O.CMA	*****CV	*****CV	*****	***	****CV	49.4	36.5	68.3	***	C.C
82	1966.1	ICC.CI	0.0	*****	*****	***	2.68C	51.6	42.3	67.4	***	C.C
83	1966.3	ICC.CI	0.0	*****	*****	***	2.68C	49.0	40.7	67.4	***	C.C
84	1966.5	ICC.OI	0.0	*****	*****	***	2.68C	47.3	36.8	67.2	***	C.C
85	1966.7	ICC.CI	0.0	*****	*****	***	2.68C	46.8	33.1	65.1	***	C.C
86	1966.9	79.0	*****	*****	*****	***CF	2.68ER	46.4	25.8	53.6	***	C.C
87	1967.1	79.0	*****	*****	*****	***CF	2.68ER	43.2	24.0	35.9	***	C.C
88	1967.3	79.0	*****	*****	*****	***CF	2.68ER	40.1	22.8	19.5	***	C.C
89	1967.5	79.0	*****	*****	*****	***CF	2.68ER	35.9	24.3	23.6	***	C.C
90	1967.7	27.4	20.9	38.9	36.0	.74	2.68C	31.8	27.9	37.2	***	27.4
91	1967.9	20.2	26.2	80.9	40.4	.12	2.68C	27.7	32.9	50.5	***	25.6
92	1968.1	11.3	28.3	90.8	44.3	-.15	2.68C	25.7	32.4	53.6	***	28.9
93	1968.3	.3	29.1	100.0	44.8	***	2.68C	29.1	29.8	56.3	***	32.7
94	1968.5	28.8	23.2	85.6	34.6	.16	2.68C	31.2	29.6	53.8	***	32.8
95	1968.7	26.0	22.3	65.6	25.9	.40	2.68C	28.7	28.9	50.4	***	26.0
96	1968.9	14.4	23.8	68.4	22.7	.19	2.68C	22.3	30.6	49.7	***	17.4
97	1969.1	O.C	27.1	99.2	22.1	-.15	2.68C	19.2	34.3	47.4	***	10.7
98	1969.3	7.0	28.8	74.5	15.8	-.03	2.68C	19.6	35.1	46.0	***	8.3
99	1969.5	4.8	27.5	48.5	8.7	.21	2.68C	17.9	36.1	42.8	***	4.8
100	1969.7	O.C	28.6	46.4	5.3	.15	2.68C	13.7	38.4	41.4	***	.9

NIVEAU	TOIT	ARG.	POR.	SXG	SW	C.HY.	C.MAT.	NEU	DEN	SCN	SEC	VST-CR
101	1969.9	.5	29.3	48.1	7.4	.01	2.68D	9.5	40.1	42.6	****	.5
102	1970.1	.3	28.9	48.7	12.5	.C3	2.68D	10.3	39.4	44.3	****	1.4
103	1970.3	3.9	30.8	64.7	13.3	-.15	2.68D	11.8	38.4	46.1	****	3.9
104	1970.5	4.0	30.0A	75.8	13.1	-.15	2.68C	13.2	36.9	46.9	****	4.0
105	1970.7	1.6	28.5	54.1	10.2	.05	2.68D	12.8	37.8	47.0	****	3.8
106	1970.9	3.8	29.7	50.4	7.5	-.04	2.68D	10.0	40.7	44.4	****	2.8
107	1971.1	3.9	30.6	47.8	5.1	-.06	2.68C	8.4	42.4	43.3	****	3.9
108	1971.3	5.8	31.0	46.1	4.7	-.12	2.68C	7.3	42.9	42.8	****	5.8
109	1971.5	7.2	30.5	45.9	4.9	-.15	2.68C	7.1	42.1	41.4	****	7.2
110	1971.7	7.0	30.1	48.2	5.3	-.15	2.68D	7.4	41.3	40.5	****	7.0
111	1971.9	7.7	29.5	47.1	7.2	-.15	2.68D	7.5	40.7	40.0	****	7.7
112	1972.1	8.4	27.1A	53.3	11.5	-.15	2.68C	7.8	39.4	39.4	****	10.4
113	1972.3	9.6	26.5	55.3	16.6	-.15	2.68C	8.8	38.0	37.9	****	13.2
114	1972.5	7.6	27.2	61.8	19.3	-.15	2.68C	10.1	37.2	35.5	****	14.8
115	1972.7	0.0	33.8A	62.0	15.2	-.15	2.68C	11.4	36.5	33.6	****	12.0
116	1972.9	8.8	25.3	48.8	14.1	.C4	2.68C	13.1	35.7	33.9	****	10.3
117	1973.1	9.9	24.9	53.6	9.5	-.02	2.68C	12.4	34.9	35.3	****	9.9
118	1973.3	7.1	24.9	54.1	6.9	-.05	2.68C	10.8	34.2	37.1	****	7.1
119	1973.5	7.4	24.9	54.7	7.3	-.09	2.68D	10.1	33.8	37.2	****	7.4
120	1973.7	10.2	25.4	58.2	11.0	-.15	2.68C	10.5	34.5	37.4	****	10.2
121	1973.9	0.0	33.7A	68.1	18.8	-.15	2.68C	11.8	34.3	40.4	****	11.6
122	1974.1	0.0	31.8A	77.0	35.6	-.15	2.68C	16.0	32.7	42.3	****	14.7
123	1974.3	4.4	28.7A	93.1	50.2	-.15	2.68D	21.9	31.2	46.2	****	21.7
124	1974.5	25.4	24.1	90.0	50.8	-.15	2.68C	27.7	30.4	46.5	****	28.2
125	1974.7	38.8	19.6	98.2	50.1	.30	2.68C	33.5	26.4	45.1	****	39.5
126	1974.9	46.6	19.4	93.2	41.6	.95	2.68C	37.2	22.3	41.2	****	46.6
127	1975.1	42.3	17.5	83.8	39.3	.95	2.68D	34.4	23.7	38.7	****	42.3
128	1975.3	34.4	19.2	80.3	32.6	.23	2.68D	29.1	27.0	38.1	****	35.4
129	1975.5	24.9	22.8	75.3	24.1	.04	2.68D	24.5	31.0	38.0	****	28.5
130	1975.7	16.4	25.8	53.5	18.9	.17	2.68C	21.1	35.7	42.3	****	22.0
131	1975.9	6.3	29.3	47.1	19.9	.18	2.68D	17.9	39.4	45.4	****	16.5
132	1976.1	13.5	29.3	58.3	28.1	-.02	2.68C	16.4	40.3	45.3	****	13.5
133	1976.3	14.8	29.4	71.5	38.4	-.15	2.68D	17.7	38.3	41.8	****	14.8
134	1976.5	18.8	26.3A	78.9	43.4	-.10	2.68C	21.7	34.5	39.3	****	18.8
135	1976.7	21.7	24.3	90.4	52.2	-.15	2.68D	26.7	29.9	38.9	****	23.0
136	1976.9	27.0	20.9	90.4	58.0	.33	2.68C	29.6	26.4	43.6	****	28.5
137	1977.1	30.0	19.8	91.2	58.4	.32	2.68D	29.8	25.7	43.3	****	31.2
138	1977.3	23.4	21.5	100.0	52.8	****	2.68C	29.8	25.4	42.7	****	27.5
139	1977.5	16.9	24.1	91.7	37.6	.20	2.68C	28.4	28.0	41.8	****	19.3
140	1977.7	10.3	26.0	61.6	27.8	.27	2.68C	22.7	33.0	43.7	****	12.5
141	1977.9	8.9	27.6	53.1	27.0	.20	2.68C	19.9	36.5	42.0	****	11.1
142	1978.1	13.3	27.6	78.4	31.1	-.08	2.68C	21.5	34.3	38.7	****	13.3
143	1978.3	6.1	28.0	89.0	38.4	-.08	2.68C	23.7	31.3	37.2	****	15.9
144	1978.5	.4	27.5	100.0	47.5	****	2.68C	25.0	29.4	37.7	****	19.5
145	1978.7	.6	28.2	97.3	49.1	-.15	2.68C	25.7	29.0	40.4	****	23.1
146	1978.9	0.0	27.5	100.0	43.0	****	2.68C	25.1	29.3	45.3	****	25.2
147	1979.1	13.5	26.1	89.4	31.1	-.15	2.68C	24.3	30.7	39.5	****	21.3
148	1979.3	14.8	27.2A	77.5	22.5	-.07	2.68D	20.8	34.9	34.9	****	14.8
149	1979.5	13.3	26.9	68.2	21.7	-.09	2.68C	16.7	35.3	30.0	****	13.3
150	1979.7	0.0	27.4	85.3	30.8	-.15	2.68D	16.9	34.5	34.6	****	15.5

NIVEAU	TOIT	ARG.	POR.	SXC	SW	D.HY.	C.MAT.	NEU	DEB	SCN	SEC	VSHCR
151	1979.9	18.0	23.8	55.9	38.0	.15	2.680	20.8	32.2	42.3	****	22.4
152	1980.1	29.2	21.9A	81.9	45.8	-.10	2.680	24.6	30.4	47.3	****	29.2
153	1980.3	28.6	21.9	91.5	47.4	-.15	2.680	28.1	28.2	48.2	****	35.8
154	1980.5	30.9	21.0	93.7	45.5	-.15	2.680	29.3	27.3	42.7	****	37.6
155	1980.7	0.0	27.6	100.0	43.4	****	2.680	28.1	28.1	44.6	****	32.4
156	1980.9	21.7	22.4	83.6	43.6	.14	2.680	26.4	28.4	47.7	****	25.3
157	1981.1	22.6	22.1	83.6	50.2	.07	2.680	25.7	28.4	48.2	****	26.4
158	1981.3	21.9	19.9	89.1	56.3	-.11	2.680	27.5	27.0	48.2	****	32.1
159	1981.5	21.9	19.8	91.1	58.2	.69	2.680	31.4	25.4	49.3	****	31.9
160	1981.7	26.0	21.9	91.0	54.3	.95	2.680	32.3	26.4	51.9	****	27.1
161	1981.9	15.0	25.5	100.0	45.0	****	2.680	30.8	28.1	54.7	****	27.5
162	1982.1	25.7	23.6	90.2	41.4	-.09	2.680	28.4	29.7	53.6	****	27.7
163	1982.3	22.7	24.9	79.5	39.1	.15	2.680	27.8	31.9	47.4	****	27.3
164	1982.5	22.2	25.2	71.8	23.1	.23	2.680	27.7	32.7	44.2	****	24.4
165	1982.7	9.0	28.9	58.1	10.5	.19	2.680	21.3	37.4	45.1	****	12.5
166	1982.9	0.0	31.5	49.3	8.4	.12	2.680	14.3	42.2	50.3	****	3.5
167	1983.1	3.1	31.4	51.9	8.7	-.02	2.680	10.8	42.9	52.9	****	3.1
168	1983.3	5.3	31.5	54.4	9.0	-.07	2.680	10.9	42.5	52.7	****	5.2
169	1983.5	5.4	31.9	56.2	9.3	-.06	2.680	11.8	42.7	53.5	****	5.4
170	1983.7	2.1	31.7	53.3	10.3	.02	2.680	12.3	42.7	54.7	****	3.0
171	1983.9	.8	*****	*****	*****	****	2.680	12.7	86.9	53.9	****	.8
172	1984.1	0.0	31.2	50.9	17.3	.10	2.680	13.9	41.4	50.7	****	3.6
173	1984.3	0.0	30.5	52.3	27.4	.14	2.680	15.6	40.0	49.6	****	7.1
174	1984.5	0.0	30.3	61.3	38.1	.14	2.680	17.7	37.9	52.0	****	7.9
175	1984.7	11.1	28.3	81.3	41.8	-.15	2.680	20.5	34.4	55.8	****	11.1
176	1984.9	0.0	29.0	92.1	46.6	-.15	2.680	22.8	31.2	54.7	****	19.7
177	1985.1	0.0	26.1	100.0	53.2	****	2.680	24.4	27.4	49.6	****	31.9
178	1985.3	32.9	18.5	93.9	53.5	-.15	2.680	28.2	24.9	46.5	****	42.3
179	1985.5	39.6	16.8	93.5	48.1	.07	2.680	30.3	24.2	49.1	****	40.8
180	1985.7	33.7	18.7	91.1	36.1	-.03	2.680	28.6	25.5	48.6	****	34.7
181	1985.9	25.5	22.8	81.3	15.2	-.11	2.680	24.1	30.1	46.4	****	25.5
182	1986.1	5.0	26.7	46.6	8.8	.17	2.680	16.0	36.0	44.5	****	13.5
183	1986.3	8.1	27.7	46.4	8.4	.01	2.680	11.7	39.6	45.2	****	8.1
184	1986.5	0.0	26.3	85.9	10.1	-.15	2.680	12.8	38.3	45.5	****	8.5
185	1986.7	8.0	29.5	71.2	11.9	-.15	2.680	14.5	38.0	45.1	****	12.4
186	1986.9	14.1	27.4	56.1	20.7	-.04	2.680	14.9	38.4	44.2	****	14.1
187	1987.1	16.3	26.8	65.5	28.9	-.12	2.680	16.5	35.7	44.5	****	16.3
188	1987.3	0.0	31.6A	85.4	32.1	-.15	2.680	20.7	33.2	47.7	****	22.4
189	1987.5	27.0	23.1	82.5	32.1	-.15	2.680	24.3	31.1	49.7	****	32.1
190	1987.7	33.0	21.7	83.0	27.8	-.15	2.680	26.0	30.4	50.8	****	36.4
191	1987.9	31.1	22.4	77.2	22.7	-.13	2.680	24.1	31.5	47.8	****	31.1
192	1988.1	22.9	24.3	71.4	19.1	-.12	2.680	15.8	33.0	47.3	****	22.9
193	1988.3	0.0	24.4	100.0	19.9	****	2.680	17.3	35.9	45.5	****	18.2
194	1988.5	4.6	29.6	74.6	12.6	-.15	2.680	16.2	36.0	45.6	****	17.2
195	1988.7	13.0	26.3	56.5	19.8	-.03	2.680	14.5	36.6	45.8	****	13.0
196	1988.9	0.0	31.7A	72.6	22.5	-.15	2.680	14.2	36.0	46.6	****	14.5
197	1989.1	0.0	33.7A	78.2	24.5	-.15	2.680	16.6	35.2	47.6	****	18.5
198	1989.3	13.7	30.0A	78.9	27.7	-.15	2.680	15.8	34.7	49.4	****	25.2
199	1989.5	25.2	25.6	77.4	33.3	-.15	2.680	22.6	34.8	50.6	****	31.2
200	1989.7	34.2	23.6	75.2	34.4	-.11	2.680	25.4	33.7	51.7	****	34.2

NIVEAU	TOIT	ARG.	POR.	SXC	SW	D.HY.	C.MAT.	NFU	CEN	SCN	SEC	VSHCR
201	1989.9	38.8	22.3	79.0	39.7	-.07	2.680	28.9	32.1	53.5	****	38.8
202	1990.1	45.3	20.2	83.5	41.2	-.12	2.680	30.8	30.1	56.4	****	45.3
203	1990.3	16.9	26.3	100.0	38.1	***	2.680	32.1	29.1	57.2	****	46.1
204	1990.5	39.6	22.5	86.2	27.9	-.12	2.680	31.2	31.3	54.7	****	39.6
205	1990.7	25.3	26.7	76.9	22.1	-.04	2.680	25.9	35.4	51.9	****	25.8
206	1990.9	0.0	34.7A	78.8	17.7	-.15	2.680	18.6	36.8	48.9	****	16.1
207	1991.1	8.5	29.4	75.2	11.9	-.15	2.680	16.6	37.1	48.1	****	11.6
208	1991.3	0.0	29.9	50.3	6.8	.10	2.680	13.3	40.0	46.4	****	7.6
209	1991.5	6.7	29.5	43.9	5.6	-.02	2.680	9.4	42.5	44.9	****	6.7
210	1991.7	6.9	29.7	46.1	5.7	-.08	2.680	8.6	41.9	44.0	****	6.9
211	1991.9	6.6	30.1	45.4	6.0	-.07	2.680	8.7	42.5	43.0	****	6.6
212	1992.1	7.3	31.2	46.9	6.6	-.11	2.680	8.7	43.1	42.5	****	7.3
213	1992.3	8.6	29.4	44.6	8.4	-.08	2.680	8.8	42.1	40.9	****	8.6
214	1992.5	8.3	29.9	47.4	10.3	-.10	2.680	9.1	41.5	39.1	****	8.3
215	1992.7	6.3	29.6	51.5	11.1	-.08	2.680	9.7	40.7	37.7	****	6.3
216	1992.9	7.0	29.3	48.7	11.7	-.05	2.680	10.1	41.0	37.7	****	7.0
217	1993.1	7.7	29.6	45.8	11.3	-.03	2.680	10.1	42.2	39.1	****	7.7
218	1993.3	7.0	29.8	42.9	10.3	-.03	2.680	9.1	43.3	40.1	****	7.0
219	1993.5	6.0	29.8	44.1	9.3	-.05	2.680	8.4	42.7	41.2	****	6.0
220	1993.7	6.3	29.5	44.7	7.6	-.06	2.680	8.5	42.1	42.2	****	6.3
221	1993.9	7.2	29.7	46.0	6.2	-.07	2.680	8.8	42.0	43.2	****	7.2
222	1994.1	8.1	28.9	46.8	6.0	-.08	2.680	9.2	40.9	43.9	****	8.1
223	1994.3	7.5	28.6	47.4	6.6	-.06	2.680	9.6	40.4	42.6	****	7.5
224	1994.5	5.7	29.1	48.3	7.2	-.03	2.680	10.2	40.7	42.0	****	5.7
225	1994.7	4.9	29.1	47.0	7.7	.00	2.680	10.6	40.8	43.1	****	4.9
226	1994.9	2.3	29.7	49.1	8.6	.02	2.680	11.0	40.9	44.9	****	3.2
227	1995.1	4.6	29.4	48.8	12.2	.03	2.680	11.8	40.9	45.3	****	5.5
228	1995.3	9.5	27.8	52.9	23.5	-.02	2.680	12.7	38.9	45.8	****	9.5
229	1995.5	11.9	26.4	53.3	36.4	.02	2.680	14.6	37.4	46.9	****	12.5
230	1995.7	18.5	26.2	69.3	39.7	-.12	2.680	18.1	35.3	47.2	****	18.5
231	1995.9	0.0	28.1	100.0	40.7	***	2.680	22.4	31.2	46.1	****	27.6
232	1996.1	0.0	27.3	100.0	32.2	***	2.680	24.9	29.5	45.0	****	35.4
233	1996.3	16.4	25.5	65.3	19.2	.15	2.680	22.8	33.7	47.4	****	26.3
234	1996.5	0.0	31.1	52.5	11.3	.16	2.680	16.6	40.3	49.3	****	13.2
235	1996.7	8.2	31.7	49.2	9.0	-.07	2.680	10.4	44.4	51.5	****	8.2
236	1996.9	5.6	32.3	52.7	9.3	-.07	2.680	10.4	44.0	49.3	****	5.6
237	1997.1	8.2	32.3	58.5	8.9	-.13	2.680	11.1	43.5	48.4	****	8.2
238	1997.3	8.4	30.5	49.8	9.3	-.02	2.680	12.3	42.7	48.2	****	8.4
239	1997.5	5.2	30.4	51.0	15.9	.03	2.680	13.2	41.8	48.7	****	6.5
240	1997.7	3.9	30.3	53.6	15.0	.02	2.680	12.9	41.0	48.5	****	4.9
241	1997.9	0.0	35.0A	70.7	22.4	-.15	2.680	13.2	40.3	49.5	****	5.1
242	1998.1	0.0	34.4A	85.5	27.4	-.15	2.680	15.1	39.0	48.8	****	8.6
243	1998.3	6.4	29.1	65.9	28.2	.04	2.680	17.8	37.2	46.8	****	10.0
244	1998.5	7.8	27.6	55.1	26.4	.19	2.680	19.5	36.1	38.3	****	11.3
245	1998.7	.4	32.3	80.4	25.1	-.15	2.680	17.7	37.6	33.4	****	13.0
246	1998.9	0.0	37.0A	74.1	25.6	-.15	2.680	16.9	36.7	32.6	****	11.1
247	1999.1	12.6	29.1	77.5	29.4	-.15	2.680	19.1	36.8	35.5	****	15.5
248	1999.3	19.4	27.1	75.2	24.3	-.15	2.680	20.7	35.0	42.5	****	19.4
249	1999.5	4.1	29.3	58.8	18.9	.17	2.680	19.4	37.1	44.5	****	17.4
250	1999.7	0.0	31.4	51.6	13.9	.16	2.680	16.7	40.7	46.2	****	11.2

NIVEAU	TOIT	ARG.	PCR.	SXC	SW	C.HY.	C.PAT.	NEU	DEN	SCA	SEC	VSHCR
251	1999.9	6.6	31.3	50.5	12.2	.02	2.680	13.2	43.5	46.3	****	7.4
252	2000.1	5.5	31.5	50.2	12.6	-.03	2.680	11.1	43.5	47.0	****	5.5
253	2000.3	5.4	30.9	51.5	14.0	-.05	2.680	10.7	42.4	47.2	****	5.4
254	2000.5	7.3	30.3	52.4	16.2	-.06	2.680	11.3	41.6	46.3	****	7.3
255	2000.7	8.2	29.5	50.6	18.9	-.04	2.680	11.7	41.1	44.5	****	8.2
256	2000.9	5.9	28.8	53.6	22.9	-.02	2.680	11.8	39.4	43.2	****	5.9
257	2001.1	5.3	29.4	61.8	27.6	-.09	2.680	12.3	38.3	42.7	****	5.3
258	2001.3	0.0	24.7	100.0	44.0	****	2.680	13.4	36.9	43.0	****	7.0
259	2001.5	0.0	28.0	53.5	51.2	.15	2.680	15.3	36.1	42.7	****	10.3
260	2001.7	16.1	24.9	65.2	17.9	-.04	2.680	17.5	34.0	42.2	****	16.1
261	2001.9	18.3	24.5	77.9	46.9	-.15	2.680	19.6	32.2	43.1	****	23.8
262	2002.1	28.8	21.3	66.3	42.1	-.05	2.680	21.1	31.2	43.4	****	28.8
263	2002.3	23.7	21.2	60.5	37.9	.12	2.680	21.6	30.5	44.0	****	28.0
264	2002.5	15.8	24.9	60.3	29.5	.02	2.680	17.7	34.7	44.2	****	17.5
265	2002.7	9.0	29.9	60.6	26.1	-.08	2.680	13.7	39.4	44.3	****	9.0
266	2002.9	7.6	30.1	60.7	28.5	-.10	2.680	12.5	39.6	43.5	****	7.6
267	2003.1	0.0	34.7A	69.2	28.6	-.15	2.680	13.2	38.9	43.8	****	8.4
268	2003.3	6.7	30.2	66.3	32.6	-.13	2.680	13.8	38.4	44.7	****	6.7
269	2003.5	0.0	30.0	56.6	33.5	.07	2.680	14.0	38.9	45.2	****	4.1
270	2003.7	0.0	31.1	56.4	30.7	.07	2.680	14.3	40.4	45.2	****	3.1
271	2003.9	1.3	31.5	59.5	31.9	.01	2.680	13.6	41.0	45.0	****	2.3
272	2004.1	3.7	31.2	61.4	36.9	-.06	2.680	12.8	40.3	45.2	****	3.7
273	2004.3	5.0	30.5	63.8	40.3	-.08	2.680	13.2	39.2	45.8	****	5.0
274	2004.5	0.0	20.3	100.0	70.4	****	2.680	14.1	37.7	46.0	****	4.0
275	2004.7	0.0	20.8	100.0	73.5	****	2.680	15.5	37.1	46.1	****	2.4
276	2004.9	0.0	22.7	100.0	72.0	****	2.680	16.9	36.0	45.5	****	3.1
277	2005.1	0.0	27.9	88.6	21.1	-.15	2.680	19.2	33.6	44.2	****	6.9
278	2005.3	6.8	25.9	82.5	69.3	.09	2.680	22.3	30.1	42.6	****	11.5
279	2005.5	12.1	23.8	80.3	69.5	.34	2.680	25.4	28.1	42.3	****	15.1
280	2005.7	14.1	25.2	79.6	22.6	.64	2.680	29.5	29.0	42.0	****	14.9
281	2005.9	7.3	29.1	81.5	57.2	.68	2.680	31.0	31.7	41.4	****	8.1
282	2006.1	5.8	29.4	83.6	21.4	.64	2.680	30.4	31.2	40.1	****	5.8
283	2006.3	6.4	28.6	83.7	69.9	.72	2.680	30.4	30.7	39.3	****	6.8
284	2006.5	8.0	27.5	88.3	28.5	.78	2.680	30.3	29.4	39.1	****	8.1
285	2006.7	5.4	27.6	91.8	26.4	.95	2.680	30.1	28.2	38.5	****	5.4
286	2006.9	1.9	28.9	93.2	24.0	.95	2.680	29.9	28.3	37.9	****	1.9
287	2007.1	2.6	28.6	92.3	28.5	.66	2.680	28.7	29.2	37.0	****	2.6
288	2007.3	1.1	29.1	92.3	32.1	.43	2.680	27.8	30.1	36.6	****	3.8
289	2007.5	1.3	29.2	92.7	35.9	.22	2.680	27.4	30.4	36.6	****	3.1
290	2007.7	.1	29.4	94.5	42.1	.33	2.680	27.4	30.4	36.4	****	1.5
291	2007.9	.7	29.5	93.8	77.7	.23	2.680	27.6	30.4	36.1	****	.7
292	2008.1	0.0	29.7	96.4	82.3	.27	2.680	27.9	30.4	35.8	****	1.0
293	2008.3	0.0	29.0	100.0	105.0	****	2.680	27.9	30.1	35.4	****	0.0
294	2008.5	0.0	29.5	100.0	94.4	****	2.680	28.3	29.8	34.5	****	0.0
295	2008.7	0.0	29.2	100.0	108.7	****	2.680	28.5	29.4	34.0	****	0.0
296	2008.9	0.0	28.9	100.0	106.9	****	2.680	28.4	28.8	33.8	****	0.0
297	2009.1	0.0	28.3	100.0	100.0	.82C	2.68	26.1	28.3	51.8	****	0.0
298	2009.3	1.6	27.8	100.0	100.0	.82C	2.68	26.0	28.1	****	****	1.6
299	2009.5	2.9	28.3	100.0	100.0	.82C	2.67	26.6	28.8	****	****	2.9
300	2009.7	1.6	28.7	100.0	100.0	.82C	2.67	26.6	28.9	****	****	1.6

NIVEAU	TCIT	ARG.	POR.	SXQ	SH	C.MY.	C.MAT.	NEU	DEB	SON	SEC	VSTGR
301	2009.9	0.0	29.4	100.0	100.0	.82C	2.67	26.6	29.4	****	****	C.0
302	2010.1	0.0	29.6	100.0	100.0	.82C	2.67	26.7	29.6	****	****	C.0
303	2010.3	.3	28.7	100.0	100.0	.82C	2.67	25.8	28.8	****	****	.3
304	2010.5	2.2	28.7	100.0	100.0	.82C	2.67	26.7	29.0	****	****	2.2
305	2010.7	4.3	28.3	100.0	100.0	.82C	2.67	27.1	29.0	****	****	4.3
306	2010.9	4.6	28.7	100.0	99.4	.82C	2.66	27.2	29.5	****	****	4.6
307	2011.1	2.2	29.5	100.0	97.5	.82C	2.67	27.3	29.8	****	****	2.2
308	2011.3	0.0	29.2	100.0	99.5	.82C	2.67	26.2	29.2	****	****	C.0
309	2011.5	0.0	29.4	100.0	99.4	.82C	2.67	26.3	29.4	****	****	C.0
310	2011.7	0.0	29.2	100.0	100.0	.82C	2.68	27.3	29.2	****	****	C.0
311	2011.9	.2	29.5	100.0	100.0	.82C	2.68	27.6	29.6	****	****	.2
312	2012.1	2.1	29.5	100.0	100.0	.82C	2.67	27.7	29.9	****	****	2.1
313	2012.3	2.6	29.3	100.0	100.0	.82C	2.66	26.9	29.7	****	****	2.6
314	2012.5	2.6	29.3	100.0	100.0	.82C	2.67	27.1	29.7	****	****	2.6
315	2012.7	2.1	29.8	100.0	100.0	.82C	2.68	28.4	30.1	****	****	2.1
316	2012.9	2.8	29.6	100.0	100.0	.82C	2.69	29.1	30.1	****	****	2.8
317	2013.1	4.7	28.8	100.0	100.0	.82C	2.68	28.7	29.6	****	****	4.7
318	2013.3	8.5	27.3	100.0	100.0	.82C	2.66	27.6	28.6	****	****	8.5
319	2013.5	12.5	25.6	100.0	100.0	.82C	2.67	28.2	27.7	****	****	12.5
320	2013.7	11.8	25.8	100.0	100.0	.82C	2.68	28.6	27.8	****	****	11.8
321	2013.9	12.3	26.0	100.0	100.0	.82C	2.68	29.9	28.1	****	****	12.3
322	2014.1	8.8	28.0	100.0	100.0	.82C	2.68	29.6	29.5	****	****	8.8
323	2014.3	4.8	29.0	100.0	100.0	.82C	2.68	28.6	29.8	****	****	4.8
324	2014.5	3.8	27.8	100.0	100.0	.82C	2.67	26.3	28.4	****	****	3.8
325	2014.7	3.5	27.0	100.0	100.0	.82C	2.67	25.3	27.5	****	****	3.5
326	2014.9	5.1	26.8	100.0	100.0	.82C	2.67	25.8	27.6	****	****	5.1
327	2015.1	8.4	26.1	100.0	100.0	.82C	2.66	25.8	27.4	****	****	8.4
328	2015.3	14.1	24.1	100.0	100.0	.82C	2.65	26.0	26.3	****	****	14.1
329	2015.5	19.2	21.6	100.0	100.0	.82C	2.68	27.4	24.8	****	****	19.2
330	2015.7	17.7	23.1	100.0	100.0	.82C	2.71	29.9	26.4	****	****	17.7
331	2015.9	11.0	26.8	100.0	100.0	.82C	2.68	29.4	28.7	****	****	11.0
332	2016.1	6.8	27.5	100.0	100.0	.82C	2.68	28.4	28.7	****	****	6.8
333	2016.3	2.6	28.8	100.0	100.0	.82C	2.67	27.3	29.2	****	****	2.6
334	2016.5	.5	29.0	100.0	100.0	.82C	2.66	25.5	29.1	****	****	.5
335	2016.7	0.0	28.9	100.0	100.0	.82C	2.66	25.4	28.9	****	****	C.0
336	2016.9	.9	28.6	100.0	100.0	.82C	2.67	26.0	28.7	****	****	.9
337	2017.1	0.0	28.4	100.0	100.0	.82C	2.67	25.3	28.4	****	****	C.0
339	2017.3	0.0	27.8	100.0	100.0	.82C	2.67	25.0	27.8	****	****	C.0
339	2017.5	0.0	27.1	100.0	100.0	.82C	2.68	24.8	27.1	****	****	C.0
340	2017.7	0.0	27.4	100.0	100.0	.82C	2.68	24.9	27.4	****	****	C.0
341	2017.9	0.0	28.3	100.0	100.0	.82C	2.67	25.5	28.3	****	****	C.0
342	2018.1	0.0	28.8	100.0	100.0	.82C	2.68	26.7	28.8	****	****	C.0
343	2018.3	0.0	28.9	100.0	100.0	.82C	2.68	26.8	28.9	****	****	0.0
344	2018.5	0.0	28.8	100.0	100.0	.82C	2.67	25.9	28.8	****	****	C.0
345	2018.7	1.4	28.2	100.0	100.0	.82C	2.68	26.4	28.5	****	****	1.4
346	2018.9	1.6	28.0	100.0	100.0	.82C	2.68	26.6	28.2	****	****	1.6
347	2019.1	1.7	28.3	100.0	100.0	.82C	2.67	26.3	28.6	****	****	1.7
348	2019.3	2.3	27.7	100.0	100.0	.82C	2.67	25.7	28.1	****	****	2.3
349	2019.5	3.0	27.3	100.0	100.0	.82C	2.68	26.1	27.8	****	****	3.0
350	2019.7	.7	28.5	100.0	100.0	.82C	2.68	26.5	28.6	****	****	.7

NIVEAU	TCIT	ARG.	POR.	SXC	SW	C.HY.	C.MAT.	NEU	DEN	SON	SEC	VST-GR
351	2019.9	1.0	28.4	100.0	100.0	.82C	2.68	26.7	28.6	****	****	1.0
352	2020.1	1.9	27.6	100.0	100.0	.82C	2.68	26.2	27.9	****	****	1.9
353	2020.3	1.2	27.4	100.0	100.0	.82C	2.68	25.5	27.6	****	****	1.2
354	2020.5	0.0	26.9	100.0	100.0	.82C	2.69	25.6	26.9	****	****	0.0
355	2020.7	1.4	25.6	100.0	100.0	.82D	2.70	25.4	25.9	****	****	1.4
356	2020.9	3.3	23.5	100.0RC	100.0	.82C	2.72	25.0	24.1	****	****	3.3
357	2021.1	0.0	21.3	100.0RC	100.0	.82C	2.75	22.5	21.7	****	****	1.9
358	2021.3	0.0	13.7	100.0RC	100.0	.82C	2.76	15.7	13.8	****	****	.2
359	2021.5	0.0	7.9	100.0RC	100.0	.82C	2.74	8.9	7.9	****	****	0.0
360	2021.7	0.0	8.6	100.0RC	100.0	.82C	2.72	9.0	8.6	****	****	0.0
361	2021.9	.2	13.2	100.0	100.0	.82C	2.71	13.4	13.3	****	****	.2
362	2022.1	1.4	16.5	100.0	100.0	.82C	2.73	17.8	16.8	****	****	1.4
363	2022.3	2.6	22.0	100.0RC	100.0	.82C	2.70	22.2	22.5	****	****	2.6
364	2022.5	4.1	26.0	100.0RC	100.0	.82C	2.67	24.8	26.7	****	****	4.1
365	2022.7	6.0	26.3	100.0RC	100.0	.82C	2.66	25.4	27.3	****	****	6.0
366	2022.9	10.0	25.5	100.0	100.0	.82C	2.65	25.9	27.1	****	****	10.0
367	2023.1	8.2	26.2	100.0	100.0	.82C	2.66	26.2	27.5	****	****	8.2
368	2023.3	5.1	27.2	100.0RC	100.0	.82C	2.67	26.4	28.0	****	****	5.1
369	2023.5	3.3	27.8	100.0RC	100.0	.82C	2.67	26.5	28.4	****	****	3.3
370	2023.7	2.8	27.8	100.0RC	100.0	.82D	2.67	25.9	28.2	****	****	2.8
371	2023.9	6.1	26.3	100.0RC	100.0	.82C	2.66	25.5	27.3	****	****	6.1
372	2024.1	8.4	25.7	100.0RC	100.0	.82C	2.65	25.0	26.9	****	****	8.4
373	2024.3	6.8	26.2	100.0	100.0	.82D	2.66	25.7	27.3	****	****	6.8
374	2024.5	3.7	27.4	100.0	100.0	.82C	2.67	26.2	28.0	****	****	3.7
375	2024.7	2.1	28.1	100.0	100.0	.82C	2.66	25.7	28.4	****	****	2.1
376	2024.9	1.0	28.4	100.0	100.0	.82C	2.67	25.7	28.5	****	****	1.0
377	2025.1	.2	28.6	100.0	100.0	.82C	2.67	25.8	28.6	****	****	.2
378	2025.3	0.0	28.3	100.0	100.0	.82C	2.68	26.3	28.3	****	****	0.0
379	2025.5	0.0	27.7	100.0	100.0	.82C	2.68	25.3	27.7	****	****	0.0
380	2025.7	.2	27.3	100.0	100.0	.82C	2.66	24.0	27.4	****	****	.2
381	2025.9	1.1	26.8	100.0	100.0	.82C	2.66	23.9	27.0	****	****	1.1
382	2026.1	.7	26.4	100.0	100.0	.82C	2.68	24.2	26.5	****	****	.7
383	2026.3	.4	26.5	100.0	100.0	.82C	2.68	24.2	26.6	****	****	.4
384	2026.5	2.3	26.3	100.0	100.0	.82C	2.66	23.6	26.6	****	****	2.3
385	2026.7	4.2	26.1	100.0	100.0	.82C	2.64	23.0	26.8	****	****	4.2
386	2026.9	3.1	26.7	100.0	100.0	.82C	2.64	23.3	27.1	****	****	3.1
387	2027.1	4.2	26.6	100.0	100.0	.82C	2.64	23.6	27.2	****	****	4.2
388	2027.3	4.7	26.5	100.0RC	100.0	.82C	2.65	24.3	27.2	****	****	4.7
389	2027.5	3.3	26.7	100.0RC	100.0	.82D	2.66	24.7	27.2	****	****	3.3
390	2027.7	.7	26.8	100.0	100.0	.82C	2.67	24.2	26.9	****	****	.7
391	2027.9	3.4	25.8	100.0RC	100.0	.82C	2.67	24.0	26.3	****	****	3.4
392	2028.1	7.0	25.7	100.0RC	100.0	.82C	2.65	24.3	26.7	****	****	7.0
393	2028.3	0.0	27.8	100.0RC	100.0	.82C	2.68	25.9	27.8	****	****	10.4
394	2028.5	16.9	22.5	100.0	98.4	.82C	2.68	27.3	25.4	****	****	16.9
395	2028.7	24.3	20.5	100.0	100.0	.82C	2.67	28.0	24.5	****	****	24.3
396	2028.9	18.1	22.9	100.0	100.0	.82C	2.68	28.1	25.9	****	****	18.1
397	2029.1	13.3	25.0	100.0RC	100.0	.82C	2.66	27.2	27.1	****	****	13.3
398	2029.3	8.4	26.1	100.0RC	100.0	.82C	2.66	25.9	27.4	****	****	8.4
399	2029.5	2.4	27.8	100.0	100.0	.82C	2.67	25.9	28.2	****	****	2.4
400	2029.7	0.0	28.5	100.0	100.0	.82C	2.68	26.4	28.5	****	****	0.0

NIVEAU	TOIT	ARG.	PGR.	SXD	SW	D.HY.	D.PAT.	NEU	DEN	SCN	SEC	VSHGR
401	2029.9	0.0	28.3	100.0RC	100.0	.82C	2.68	25.9	28.3	****	****	C.0
402	2030.1	0.0	28.1	100.0	100.0	.82C	2.68	25.8	28.1	****	****	C.0
403	2030.3	0.0	27.4	100.0	100.0	.82D	2.69	25.7	27.4	****	****	C.0
404	2030.5	0.0	26.9	100.0RC	100.0	.82C	2.69	25.5	26.9	****	****	C.0
405	2030.7	.4	27.1	100.0RC	100.0	.82C	2.70	26.2	27.2	****	****	.4
406	2030.9	0.0	27.4	100.0RC	100.0	.82C	2.70	26.4	27.4	****	****	C.0
407	2031.1	0.0	26.4	100.0	100.0	.82C	2.69	24.8	26.4	****	****	C.0
408	2031.3	0.0	27.2	100.0	100.0	.82D	2.68	24.8	27.2	****	****	C.0
409	2031.5	1.2	27.9	100.0	100.0	.82C	2.67	25.3	28.1	****	****	1.2
410	2031.7	2.8	27.8	100.0	100.0	.82C	2.67	26.0	28.2	****	****	2.8
411	2031.9	3.3	27.5	100.0	100.0	.82C	2.68	26.4	28.1	****	****	3.3
412	2032.1	2.1	28.0	100.0	100.0	.82C	2.67	26.3	28.3	****	****	2.1
413	2032.3	.9	28.4	100.0	100.0	.82C	2.67	25.6	28.6	****	****	.9
414	2032.5	0.0	28.4	100.0	100.0	.82C	2.67	25.4	28.4	****	****	0.0
415	2032.7	0.0	28.4	100.0	100.0	.82C	2.67	25.6	28.4	****	****	C.0
416	2032.9	1.0	27.6	100.0RC	100.0	.82C	2.67	25.1	27.8	****	****	1.0
417	2033.1	1.9	27.0	100.0	100.0	.82D	2.67	25.0	27.3	****	****	1.9
418	2033.3	3.2	26.7	100.0	100.0	.82C	2.66	24.6	27.2	****	****	3.2
419	2033.5	1.9	26.9	100.0	100.0	.82C	2.66	24.4	27.2	****	****	1.9
420	2033.7	1.4	26.8	100.0	100.0	.82C	2.67	24.6	27.1	****	****	1.4
421	2033.9	1.6	26.7	100.0	100.0	.82C	2.67	24.5	26.9	****	****	1.6
422	2034.1	3.7	26.3	100.0RC	100.0	.82D	2.66	24.4	26.9	****	****	3.7
423	2034.3	1.4	27.0	100.0	100.0	.82C	2.67	25.0	27.3	****	****	1.4
424	2034.5	.4	27.3	100.0	100.0	.82C	2.69	25.7	27.3	****	****	.4
425	2034.7	.9	27.2	100.0	100.0	.82C	2.68	25.5	27.3	****	****	.9
426	2034.9	1.1	27.5	100.0	100.0	.82C	2.68	25.5	27.7	****	****	1.1
427	2035.1	1.2	27.4	100.0	100.0	.82C	2.69	26.1	27.6	****	****	1.2
428	2035.3	.9	26.5	100.0RC	100.0	.82D	2.69	25.7	26.7	****	****	.9
429	2035.5	0.0	24.4	100.0RC	100.0	.82C	2.71	24.5	24.4	****	****	C.0
430	2035.7	0.0	21.1	100.0RC	100.0	.82C	2.74	22.0	21.1	****	****	0.0
431	2035.9	0.0	17.9	100.0RC	100.0	.82C	2.80	21.6	17.9	****	****	C.0
432	2036.1	0.0	18.4	100.0RC	100.0	.82C	2.78	21.4	18.4	****	****	C.0
433	2036.3	0.0	22.4	100.0	100.0	.82C	2.69	21.2	22.4	****	****	C.0
434	2036.5	.9	25.9	100.0RC	100.0	.82C	2.68	24.3	26.0	****	****	.9
435	2036.7	2.3	26.4	100.0RC	100.0	.82C	2.68	25.2	26.8	****	****	2.3
436	2036.9	4.6	26.2	100.0RC	100.0	.82C	2.67	25.3	27.0	****	****	4.6
437	2037.1	5.5	25.8	100.0RC	100.0	.82C	2.67	25.2	26.7	****	****	5.5
438	2037.3	5.1	25.9	100.0RC	100.0	.82C	2.67	25.3	26.8	****	****	5.1
439	2037.5	3.0	26.8	100.0RC	100.0	.82C	2.67	25.1	27.3	****	****	3.0
440	2037.7	4.0	27.0	100.0RC	100.0	.82C	2.66	25.0	27.6	****	****	4.0
441	2037.9	4.9	26.4	100.0RC	100.0	.82C	2.65	24.3	27.1	****	****	4.9
442	2038.1	7.1	24.8	100.0RC	100.0	.82C	2.66	24.2	26.0	****	****	7.1
443	2038.3	11.6	23.5	100.0RC	100.0	.82C	2.65	24.5	25.3	****	****	11.6
444	2038.5	9.8	24.1	100.0RC	100.0	.82C	2.66	25.0	25.7	****	****	9.8
445	2038.7	7.1	25.7	100.0RC	100.0	.82C	2.67	26.0	26.9	****	****	7.1
446	2038.9	3.8	26.9	100.0RC	100.0	.82C	2.66	24.9	27.5	****	****	3.8
447	2039.1	1.8	27.0	100.0RC	100.0	.82C	2.66	24.4	27.3	****	****	1.8
448	2039.3	.2	27.4	100.0RC	100.0	.82C	2.67	24.7	27.4	****	****	.2
449	2039.5	1.9	26.9	100.0RC	100.0	.82C	2.67	24.8	27.2	****	****	1.9
450	2039.7	3.5	26.5	100.0RC	100.0	.82C	2.67	25.3	27.1	****	****	3.5

NIVEAU	TOIT	ARG.	POR.	SXG	SH	D.FY.	C.PAT.	NEU	DEN	SCN	SEC	VSTGR
451	2039.9	2.8	26.4	100.GRC	100.0	.82C	2.68	25.5	26.9	****	****	2.8
452	2040.1	2.1	26.2	100.GRC	100.0	.82C	2.69	25.5	26.6	****	****	2.1
453	2040.3	4.3	25.7	100.GRC	100.0	.82C	2.68	25.1	26.4	****	****	4.3
454	2040.5	6.2	25.2	100.GRC	100.0	.82C	2.67	25.0	26.2	****	****	6.2
455	2040.7	7.0	25.0	100.GRC	100.0	.82C	2.68	25.5	26.1	****	****	7.0
456	2040.9	3.2	25.9	100.GRC	100.0	.82C	2.68	25.3	26.4	****	****	3.2
457	2041.1	1.6	26.3	100.GRC	100.0	.82C	2.69	25.2	26.6	****	****	1.6
458	2041.3	1.1	26.7	100.GRC	100.0	.82C	2.68	25.3	26.9	****	****	1.1
459	2041.5	.7	27.3	100.GRC	100.0	.82C	2.68	25.2	27.4	****	****	.7
460	2041.7	2.5	26.7	100.GRC	100.0	.82C	2.67	24.8	27.1	****	****	2.5
461	2041.9	4.2	26.5	100.GRC	100.0	.82C	2.65	24.3	27.1	****	****	4.2
462	2042.1	4.0	26.5	100.GRC	100.0	.82C	2.65	24.3	27.2	****	****	4.0
463	2042.3	4.0	26.7	100.GRC	100.0	.82C	2.66	24.5	27.3	****	****	4.0
464	2042.5	6.7	25.5	100.GRC	100.0	.82C	2.65	24.3	26.5	****	****	6.7
465	2042.7	8.4	24.5	100.GRC	100.0	.82C	2.67	25.1	25.8	****	****	8.4
466	2042.9	8.2	24.8	100.GRC	100.0	.82C	2.69	26.4	26.2	****	****	8.2
467	2043.1	9.5	24.7	100.GRC	100.0	.82C	2.68	26.7	26.4	****	****	9.5
468	2043.3	6.9	25.6	100.GRC	100.0	.82C	2.69	26.7	26.8	****	****	6.9
469	2043.5	3.2	26.6	100.GRC	100.0	.82C	2.68	25.8	27.1	****	****	3.2
470	2043.7	4.1	26.3	100.GRC	100.0	.82C	2.67	25.1	27.0	****	****	4.1
471	2043.9	7.0	25.7	100.GRC	100.0	.82C	2.66	25.0	26.8	****	****	7.0
472	2044.1	6.2	25.6	100.GRC	100.0	.82C	2.66	24.7	26.6	****	****	6.2
473	2044.3	7.5	25.4	100.GRC	100.0	.82C	2.65	24.6	26.6	****	****	7.5
474	2044.5	8.8	25.2	100.GRC	100.0	.82C	2.65	24.7	26.6	****	****	8.8
475	2044.7	10.9	24.4	100.GRC	100.0	.82C	2.65	24.9	26.1	****	****	10.9
476	2044.9	9.6	24.5	100.GRC	100.0	.82C	2.66	24.9	26.0	****	****	9.6
477	2045.1	8.9	24.5	100.GRC	100.0	.82C	2.65	24.3	25.9	****	****	8.9
478	2045.3	12.0	24.1	100.GRC	100.0	.82C	2.64	24.4	25.8	****	****	12.0
479	2045.5	9.7	24.4	100.GRC	100.0	.82C	2.65	24.6	25.9	****	****	9.7
480	2045.7	8.5	24.6	100.GRC	100.0	.82C	2.66	24.7	25.9	****	****	8.5
481	2045.9	9.0	24.9	100.GRC	100.0	.82C	2.66	25.4	26.3	****	****	9.0
482	2046.1	7.9	25.6	100.GRC	100.0	.82C	2.66	25.2	26.9	****	****	7.9
483	2046.3	3.9	26.7	100.GRC	100.0	.82C	2.66	25.0	27.3	****	****	3.9
484	2046.5	0.0	28.2	100.GRC	100.0	.82C	2.67	25.5	28.2	****	****	0.0
485	2046.7	0.0	29.1	100.GRC	100.0	.82C	2.68	26.3	29.1	****	****	0.0
486	2046.9	0.0	29.1	100.GRC	100.0	.82C	2.68	26.8	29.1	****	****	0.0
487	2047.1	.3	29.0	100.GRC	100.0	.82C	2.68	27.1	29.0	****	****	.3
488	2047.3	.7	29.0	100.GRC	100.0	.82C	2.68	27.3	29.1	****	****	.7
489	2047.5	1.9	27.8	100.GRC	100.0	.82C	2.69	26.9	28.1	****	****	1.9
490	2047.7	2.5	26.9	100.GRC	100.0	.82C	2.68	26.0	27.3	****	****	2.5
491	2047.9	1.1	27.4	100.GRC	100.0	.82C	2.68	25.3	27.6	****	****	1.1
492	2048.1	2.3	26.8	100.GRC	100.0	.82C	2.67	24.9	27.2	****	****	2.3
493	2048.3	2.0	26.3	100.GRC	100.0	.82C	2.67	24.5	26.6	****	****	2.0
494	2048.5	2.8	25.6	100.GRC	100.0	.82C	2.67	24.0	26.1	****	****	2.8
495	2048.7	4.6	24.9	100.GRC	100.0	.82C	2.66	23.4	25.6	****	****	4.6
496	2048.9	5.8	24.8	100.GRC	100.0	.82C	2.65	23.3	25.7	****	****	5.8
497	2049.1	6.9	24.3	100.GRC	100.0	.82C	2.66	23.5	25.4	****	****	6.9
498	2049.3	5.7	24.7	100.GRC	100.0	.82C	2.66	23.6	25.6	****	****	5.7
499	2049.5	5.3	24.9	100.GRC	100.0	.82C	2.66	23.6	25.8	****	****	5.3
500	2049.7	6.3	24.2	100.GRC	100.0	.82C	2.66	23.4	25.2	****	****	6.3

NIVEAU	TOIT	ARG.	POR.	SXC	SW	C.FY.	C.PAT.	NEU	GEN	SCN	SEC	VSHGR
501	2049.9	3.9	25.1	100.0RC	100.0	.820	2.67	24.0	25.8	****	****	3.9
502	2050.1	2.5	26.2	100.0RC	100.0	.820	2.68	24.8	26.6	****	****	2.5
503	2050.3	1.4	27.4	100.0RC	100.0	.820	2.67	25.4	27.7	****	****	1.4
504	2050.5	2.1	27.9	100.0RC	100.0	.820	2.69	27.0	28.3	****	****	2.1
505	2050.7	5.9	27.1	100.0RC	100.0	.820	2.67	26.5	28.0	****	****	5.9
506	2050.9	9.5	25.9	100.0RC	100.0	.820	2.64	25.5	27.4	****	****	9.5
507	2051.1	13.8	24.3	100.0RC	100.0	.820	2.64	25.3	26.3	****	****	13.8
508	2051.3	14.0	24.0	100.0RC	100.0	.820	2.66	26.3	26.2	****	****	14.0
509	2051.5	9.2	25.5	100.0RC	100.0	.820	2.67	26.8	27.1	****	****	9.2
510	2051.7	3.9	26.5	100.0RC	100.0	.820	2.69	26.4	27.2	****	****	3.9
511	2051.9	0.0	27.2	100.0RC	100.0	.820	2.69	25.7	27.2	****	****	0.0
512	2052.1	.9	27.1	100.0RC	100.0	.820	2.69	25.7	27.2	****	****	.9
513	2052.3	1.1	27.5	100.0RC	100.0	.820	2.69	26.3	27.6	****	****	1.1
514	2052.5	1.1	27.1	100.0RC	100.0	.820	2.68	25.3	27.3	****	****	1.1
515	2052.7	0.0	26.7	100.0RC	100.0	.820	2.68	24.8	26.7	****	****	0.0
516	2052.9	0.0	26.4	100.0RC	100.0	.820	2.69	24.7	26.4	****	****	0.0
517	2053.1	0.0	26.6	100.0RC	100.0	.820	2.69	25.0	26.6	****	****	0.0
518	2053.3	0.0	26.9	100.0RC	100.0	.820	2.69	25.4	26.9	****	****	0.0
519	2053.5	0.0	27.1	100.0RC	100.0	.820	2.68	24.9	27.1	****	****	0.0
520	2053.7	1.8	26.7	100.0RC	100.0	.820	2.67	24.7	27.0	****	****	1.8
521	2053.9	1.6	27.1	100.0RC	100.0	.820	2.67	24.7	27.3	****	****	1.6
522	2054.1	0.0	27.8	100.0RC	100.0	.820	2.68	25.3	27.8	****	****	0.0
523	2054.3	.5	28.1	100.0RC	100.0	.820	2.66	24.5	28.2	****	****	.5
524	2054.5	3.9	27.9	100.0RC	100.0	.820	2.64	24.6	28.4	****	****	3.9
525	2054.7	6.9	26.7	100.0RC	100.0	.820	2.64	24.9	27.8	****	****	6.9
526	2054.9	7.8	26.0	100.0RC	100.0	.820	2.65	25.1	27.2	****	****	7.8
527	2055.1	7.5	25.6	100.0RC	100.0	.820	2.65	24.8	26.8	****	****	7.5
528	2055.3	6.5	25.9	100.0RC	100.0	.820	2.65	24.5	26.9	****	****	6.5
529	2055.5	2.5	27.0	100.0RC	100.0	.820	2.67	24.8	27.4	****	****	2.5
530	2055.7	4.9	26.6	100.0RC	100.0	.820	2.66	25.3	27.4	****	****	4.9
531	2055.9	5.4	26.7	100.0RC	100.0	.820	2.66	25.3	27.5	****	****	5.4
532	2056.1	4.5	26.6	100.0RC	100.0	.820	2.66	24.8	27.3	****	****	4.5
533	2056.3	4.2	26.5	100.0RC	100.0	.820	2.67	25.4	27.2	****	****	4.2
534	2056.5	7.0	25.7	100.0RC	100.0	.820	2.66	25.4	26.9	****	****	7.0
535	2056.7	11.6	24.5	100.0RC	100.0	.820	2.65	25.2	26.2	****	****	11.6
536	2056.9	17.0	23.7	100.0RC	100.0	.820	2.65	26.7	26.3	****	****	17.0
537	2057.1	22.7	23.2	100.0RC	100.0	.820	2.66	29.5	26.8	****	****	22.7
538	2057.3	26.8	22.0	100.0RC	100.0	.820	2.69	31.3	26.7	****	****	26.8
539	2057.5	32.9	19.6	100.0RC	100.0	.820	2.70	31.9	25.6	****	****	32.9
540	2057.7	35.8	18.5	100.0RC	100.0	.820	2.74	32.7	25.6	****	****	35.8
541	2057.9	34.6	19.0	100.0RC	100.0	.820	2.74	32.4	25.9	****	****	34.6
542	2058.1	31.1	20.8	100.0RC	100.0	.820	2.70	32.1	26.3	****	****	31.1
543	2058.3	30.2	22.6	100.0RC	100.0	.820	2.70	33.7	28.0	****	****	30.2
544	2058.5	26.8	23.9	100.0RC	100.0	.820	2.70	33.6	26.7	****	****	26.8
545	2058.7	27.2	22.8	100.0RC	100.0	.820	2.67	31.4	27.3	****	****	27.2
546	2058.9	26.5	21.8	100.0RC	100.0	.820	2.67	29.9	26.1	****	****	26.5
547	2059.1	25.4	21.3	100.0RC	100.0	.820	2.69	29.9	25.7	****	****	25.4
548	2059.3	28.0	20.2	100.0RC	100.0	.820	2.69	30.1	25.1	****	****	28.0
549	2059.5	32.5	18.8	100.0RC	100.0	.820	2.70	30.9	24.7	****	****	32.5
550	2059.7	33.2	18.8	100.0RC	100.0	.820	2.71	31.3	24.8	****	****	33.2

NIVEAU	TCIT	ARG.	POR.	SXC	SW	C.HY.	C.MAT.	NEU	DEA	SCA	SEC	VSHGR
551	2059.9	30.9	18.6	100.0RC	100.0	.82C	2.70	30.0	24.2	****	****	30.9
552	2060.1	26.2	18.6	100.0RC	100.0	.82C	2.75	29.6	23.9	****	****	26.2
553	2060.3	25.2	18.3	100.0RC	100.0	.82C	2.75	28.9	23.4	****	****	25.2
554	2060.5	19.6	16.7	100.0RC	100.0	.82C	2.76	25.5	20.7	****	****	19.6
555	2060.7	14.7	12.7	100.0RC	100.0	.82C	2.76	20.0	15.8	****	****	14.7
556	2060.9	13.9	7.6	100.0RC	100.0	.82C	2.74	13.9	10.4	****	****	13.9
557	2061.1	14.3	2.8	100.0RC	100.0	.82C	2.69	7.8	5.2	****	****	14.3
558	2061.3	5.0	4.9	100.0RC	100.0	.82C	2.69	6.2	5.8	****	****	14.9
559	2061.5	10.2	1.6	100.0	100.0	.82C	2.68	4.9	3.3	****	****	10.2
560	2061.7	8.2A	0.0A	*****	*****	.82C	2.68A	3.1	1.4	****	****	9.0
561	2061.9	6.8A	0.0A	*****	*****	.82C	2.65A	2.6	1.0	****	****	9.4
562	2062.1	7.8	1.2	100.0	100.0	.82C	2.65	2.8	2.4	****	****	7.8
563	2062.3	5.5	2.5	100.0	100.0	.82C	2.66	3.3	3.4	****	****	5.5
564	2062.5	7.3	5.2	100.0	100.0	.82C	2.66	6.3	6.3	****	****	7.3
565	2062.7	0.0	11.7	100.0RC	100.0	.82C	2.69	10.7	11.7	****	****	8.6
566	2062.9	0.0	17.0	100.0RC	100.0	.82C	2.68	15.2	17.0	****	****	11.2
567	2063.1	12.9	18.4	100.0	55.6	.82C	2.65	19.6	20.4	****	****	12.9
568	2063.3	16.2	19.7	100.0	100.0	.82C	2.64	21.9	22.1	****	****	16.2
569	2063.5	20.9	19.1	100.0RC	100.0	.82C	2.63	23.1	22.1	****	****	20.9
570	2063.7	24.5	18.3	100.0RC	100.0	.82C	2.64	24.0	21.8	****	****	24.5
571	2063.9	28.6	16.3	100.0RC	100.0	.82C	2.65	24.3	20.6	****	****	28.6
572	2064.1	33.6	14.6	100.0RC	100.0	.82C	2.66	25.4	19.9	****	****	33.6
573	2064.3	38.5	12.8	100.0RC	100.0	.82C	2.70	27.0	19.6	****	****	38.5
574	2064.5	47.0	11.6	100.0RC	100.0	.82C	2.73	29.8	20.7	****	****	47.0
575	2064.7	48.3	12.1	100.0RC	100.0	.82C	2.76	31.3	22.1	****	****	48.3
576	2064.9	49.6	11.5	100.0RC	100.0	.82C	2.71	30.4	20.7	****	****	49.6
577	2065.1	48.4	11.5	100.0RC	100.0	.82C	2.71	29.9	20.4	****	****	48.4
578	2065.3	44.6	13.6	100.0RC	100.0	.82C	2.68	29.7	21.2	****	****	44.6
579	2065.5	42.2	15.6	100.0RC	100.0	.82C	2.68	30.5	22.6	****	****	42.2
580	2065.7	34.8	20.2	100.0RC	100.0	.82C	2.73	31.8	25.0	****	****	41.5
581	2065.9	41.2MA	*****NC	*****RC	*****	*****D	*****NC	32.0	***	****	****	41.2
582	2066.1	45.9	15.8	100.0RC	100.0	.82C	2.68	32.4	23.6	****	****	45.9
583	2066.3	46.0	14.5	100.0RC	99.2	.82C	2.71	31.9	22.9	****	****	46.0
584	2066.5	44.4	14.8	100.0RC	100.0	.82C	2.73	32.1	23.5	****	****	44.4
585	2066.7	45.8	15.1	100.0RC	100.0	.82C	2.75	33.3	24.5	****	****	45.8
586	2066.9	50.8	14.5	100.0RC	99.9	.82C	2.72	33.9	24.0	****	****	50.8
587	2067.1	55.8	13.7	100.0RC	100.0	.82C	2.73	35.2	24.6	****	****	55.8
588	2067.3	51.8	14.7	100.0RC	100.0	.82C	2.79	35.6	26.1	****	****	51.8
589	2067.5	55.1	12.4	100.0RC	94.6	.82C	2.79	34.5	24.7	****	****	55.1
590	2067.7	55.1	11.6	100.0	99.5	.82C	2.76	33.2	23.0	****	****	55.1
591	2067.9	50.4	13.3	100.0RC	100.0	.82C	2.70	32.2	22.3	****	****	50.4
592	2068.1	41.7	21.8	85.1	67.9	.82C	2.93	32.0	32.2	****	****	44.1
593	2068.3	35.7	19.3	100.0RC	100.0	.82C	2.74	33.5	26.4	****	****	35.7
594	2068.5	30.9	20.9	100.0RC	100.0	.82C	2.77	34.1	27.5	****	****	30.9
595	2068.7	31.0	25.9	77.5	72.1	.82C	3.09	33.2	36.8	****	****	31.0
596	2068.9	30.3	18.6	100.0RC	100.0	.82C	2.83	33.0	25.8	****	****	30.3
597	2069.1	26.7	8.0	100.0RC	100.0	.82C	2.46	33.1	9.1	****	****	26.7
598	2069.3	14.3	25.3	100.0RC	100.0	.82C	2.78	32.7	28.1	****	****	23.9
599	2069.5	9.9	26.9	100.0RC	94.0	.82C	2.76	31.7	28.6	****	****	21.9
600	2069.7	22.9MA	*****NC	*****	*****	*****D	*****NC	31.3	****	****	****	22.9

NIVEAU	TGIT	APG.	POR.	SXC	SW	C.HY.	C.MAT.	NEU	DEN	SCN	SEC	VSHGR
601	2069.9	27.4MA	*****NC	*****	*****	****C	****NC	31.1	****	****	****	27.4
602	2070.1	27.8	20.9	100.0RC	100.0	.82C	2.71	31.5	26.0	****	****	27.8
603	2070.3	23.7	23.3	100.0RC	100.0	.82C	2.73	32.8	27.9	****	****	23.7
604	2070.5	0.0	31.1	100.0RC	97.8	.82C	2.82	23.1	32.7	****	****	17.7
605	2070.7	0.0	31.0	100.0RC	100.0	.82C	2.81	32.7	32.3	****	****	12.6
606	2070.9	11.1	27.6	100.0RC	100.0	.82C	2.74	32.5	25.8	****	****	11.1
607	2071.1	6.5	28.2	100.0RC	100.0	.82C	2.71	30.7	29.4	****	****	6.5
608	2071.3	5.1	27.5	100.0RC	100.0	.82C	2.68	27.6	28.4	****	****	5.1
609	2071.5	9.8	25.5	100.0RC	100.0	.82C	2.66	26.3	27.0	****	****	9.8
610	2071.7	17.7	23.8	100.0RC	100.0	.82C	2.65	27.0	26.5	****	****	17.7
611	2071.9	26.3	21.5	100.0RC	100.0	.82C	2.64	28.2	25.4	****	****	26.3
612	2072.1	37.4	17.9	100.0RC	100.0	.82C	2.64	29.6	23.5	****	****	37.4
613	2072.3	49.1	14.0	100.0RC	100.0	.82C	2.65	31.1	21.6	****	****	49.1
614	2072.5	50.4	14.4	100.0RC	100.0	.82C	2.73	33.9	24.2	****	****	50.4
615	2072.7	49.4	15.6	100.0RC	100.0	.82C	2.83	36.4	27.4	****	****	49.4
616	2072.9	42.5	24.0	83.0	76.3	.82C	3.18	39.0	39.8	****	****	42.5
617	2073.1	38.5	16.9	100.0	99.5	.82C	2.64	36.9	22.6	****	****	38.5
618	2073.3	30.8	21.6	100.0	90.5	.82C	2.72	33.5	27.4	****	****	30.8
619	2073.5	21.9	23.0	100.0	92.4	.82C	2.71	31.4	27.1	****	****	21.9
620	2073.7	14.4	24.0	100.0RC	100.0	.82C	2.70	28.9	26.6	****	****	14.4
621	2073.9	10.4	24.5	100.0RC	100.0	.82C	2.69	27.2	26.3	****	****	10.4
622	2074.1	10.8	24.1	100.0RC	100.0	.82C	2.69	26.9	26.0	****	****	10.8
623	2074.3	10.1	23.9	100.0RC	100.0	.82C	2.70	27.2	25.7	****	****	10.1
624	2074.5	7.7	25.1	100.0RC	100.0	.82C	2.71	28.1	26.5	****	****	10.1
625	2074.7	0.0	28.8	100.0RC	100.0	.82C	2.73	29.1	29.2	****	****	5.3
626	2074.9	0.0	30.4	100.0RC	97.3	.82C	2.67	27.5	30.4	****	****	2.7
627	2075.1	2.4	30.5	100.0RC	100.0	.82C	2.66	28.0	30.9	****	****	2.4
628	2075.3	.2	31.5	100.0RC	100.0	.82C	2.68	29.5	31.6	****	****	.2
629	2075.5	0.0	32.0	100.0RC	100.0	.82C	2.70	31.0	32.0	****	****	0.0
630	2075.7	0.0	31.8	100.0RC	100.0	.82C	2.70	30.7	31.8	****	****	0.0
631	2075.9	0.0	31.1	100.0RC	100.0	.82C	2.68	29.2	31.1	****	****	0.0
632	2076.1	0.0	29.7	100.0RC	100.0	.82C	2.68	27.2	29.7	****	****	0.0
633	2076.3	1.0	27.9	100.0RC	100.0	.82C	2.67	25.7	28.0	****	****	1.0
634	2076.5	1.1	26.4	100.0RC	100.0	.82C	2.68	24.5	26.6	****	****	1.1
635	2076.7	3.1	24.5	100.0RC	100.0	.82C	2.68	23.8	25.0	****	****	3.1
636	2076.9	7.1	23.4	100.0RC	100.0	.82C	2.68	23.9	24.5	****	****	7.1
637	2077.1	9.9	22.5	100.0RC	100.0	.82C	2.66	23.2	24.1	****	****	9.9
638	2077.3	16.0	20.7	100.0RC	100.0	.82C	2.65	23.5	23.1	****	****	16.0
639	2077.5	16.6	20.4	100.0RC	100.0	.82C	2.69	25.5	23.3	****	****	16.6
640	2077.7	14.7	21.2	100.0RC	100.0	.82C	2.70	26.0	23.8	****	****	14.7
641	2077.9	14.5	21.2	100.0RC	100.0	.82C	2.66	23.6	23.5	****	****	14.5
642	2078.1	18.4	19.7	100.0RC	100.0	.82C	2.64	23.1	22.5	****	****	18.4
643	2078.3	27.0	17.2	100.0	100.0	.82C	2.63	23.8	21.1	****	****	27.0
644	2078.5	33.6	16.0	100.0	100.0	.82C	2.64	26.0	21.0	****	****	33.6
645	2078.7	35.8	16.1	100.0	97.6	.82C	2.67	28.3	22.0	****	****	35.8
646	2078.9	29.9	17.9	100.0	89.7	.82C	2.68	28.1	23.0	****	****	29.9
647	2079.1	19.5	21.3	100.0	88.6	.82C	2.67	26.4	24.5	****	****	19.5
648	2079.3	17.6	22.8	100.0	94.7	.82C	2.64	25.6	25.4	****	****	17.6
649	2079.5	19.4	22.1	100.0	99.2	.82C	2.65	26.1	25.1	****	****	19.4
650	2079.7	23.8	20.4	100.0RC	100.0	.82C	2.65	26.7	24.1	****	****	23.8

NIVEAU	TCIT	ARG.	POR.	SXC	SW	C.FY.	C.MAT.	NEU	DEN	SCN	SEC	VSHGR
651	2079.9	25.5	19.0	100.0RC	100.0	.82C	2.69	27.8	23.5	****	****	25.5
652	2080.1	29.1	17.3	100.0RC	100.0	.82C	2.73	28.7	22.8	****	****	29.1
653	2080.3	25.6	17.6	100.0RC	100.0	.82C	2.76	28.6	22.9	****	****	25.6
654	2080.5	19.5	19.6	100.0	99.2	.82C	2.72	27.3	23.2	****	****	19.5
655	2080.7	15.7	22.0	100.0	98.0	.82C	2.67	25.9	24.6	****	****	15.7
656	2080.9	12.5	24.1	100.0	98.3	.82C	2.65	25.5	26.1	****	****	12.5
657	2081.1	13.8	24.3	100.0	98.9	.82C	2.66	26.6	26.5	****	****	13.8
658	2081.3	19.7	22.2	100.0	94.7	.82C	2.66	27.2	25.3	****	****	19.7
659	2081.5	25.0	18.6	100.0RC	100.0	.82C	2.69	27.2	23.0	****	****	25.0
660	2081.7	.5	22.9	100.0RC	100.0	.82C	2.80	26.5	23.1	****	****	25.5
661	2081.9	0.0	21.7	100.0RC	100.0	.82C	2.84	24.6	23.8	****	****	20.4
662	2082.1	23.9	17.4	100.0RC	100.0	.82C	2.69	25.4	21.5	****	****	23.9
663	2082.3	24.1	21.3	100.0RC	100.0	.82C	2.66	28.0	25.1	****	****	24.1
664	2082.5	29.2	20.3	100.0RC	100.0	.82C	2.68	30.0	25.2	****	****	29.2
665	2082.7	38.0	17.4	100.0	51.4	.82C	2.71	31.9	24.4	****	****	38.0
666	2082.9	44.8	15.9	100.0	51.6	.82C	2.73	33.4	24.7	****	****	44.8
667	2083.1	48.7	16.5	100.0	86.6	.82C	2.77	36.0	26.9	****	****	48.7
668	2083.3	47.5	20.0	87.8	83.7	.82C	2.98	36.3	32.4	****	****	47.5
669	2083.5	44.9	16.5	100.0	85.1	.82C	2.78	34.8	26.2	****	****	44.9
670	2083.7	45.4	19.8	85.2	81.5	.82C	2.97	35.6	31.8	****	****	45.4
671	2083.9	37.4	18.7	100.0RC	100.0	.82C	2.79	34.5	26.9	****	****	37.4
672	2084.1	33.9	19.8	100.0	82.0	.82C	2.73	33.1	26.4	****	****	33.9
673	2084.3	35.7	20.8	100.0	79.3	.82C	2.68	33.3	26.9	****	****	35.7
674	2084.5	33.6MA	*****NC	*****	*****	*****C	*****NC	36.9	****	****	****	33.6
675	2084.7	29.2MA	*****NC	*****	*****	*****C	*****NC	34.8	****	****	****	29.2
676	2084.9	30.1	27.0	71.1RC	70.5	.82C	3.00	31.3	38.0	****	****	33.5
677	2085.1	38.6	25.2	81.4	64.7	.82C	2.98	32.7	36.8	****	****	42.0
678	2085.3	45.0	20.3	100.0	80.7	.82C	2.71	37.4	28.6	****	****	45.0
679	2085.5	42.9	24.7	100.0	78.3	.82C	2.84	42.9	35.1	****	****	42.9
680	2085.7	18.7	33.2	100.0RC	100.0	.82C	2.93	44.6	37.1	****	****	37.1
681	2085.9	24.3MA	*****NC	*****	*****	*****C	*****NC	41.8	****	****	****	24.3
682	2086.1	18.6MA	*****NC	*****	*****	*****C	*****NC	35.0	****	****	****	18.6
683	2086.3	15.7	23.5	100.0	84.3	.82C	2.71	29.4	26.4	****	****	15.7
684	2086.5	17.8	23.1	100.0RC	100.0	.82C	2.74	30.7	26.6	****	****	17.8
685	2086.7	23.0	22.5	100.0RC	100.0	.82C	2.75	32.3	27.2	****	****	23.0
686	2086.9	24.7	21.8	100.0	96.3	.82C	2.73	31.6	26.6	****	****	24.7
687	2087.1	23.1	22.9	100.0RC	100.0	.82C	2.74	32.3	27.4	****	****	23.1
688	2087.3	17.3	25.5	100.0RC	100.0	.82C	2.78	33.8	29.2	****	****	17.3
689	2087.5	.0	30.1	100.0RC	100.0	.82C	2.79	32.4	30.1	****	****	10.1
690	2087.7	0.0	27.5	100.0RC	99.0	.82C	2.76	28.4	28.2	****	****	5.8
691	2087.9	0.0	23.8	100.0RC	89.0	.82C	2.73	24.2	24.2	****	****	3.7
692	2088.1	1.4MA	*****NC	*****RC	*****	*****C	*****NC	18.9	****	****	****	1.4
693	2088.3	0.0	17.9	89.2RC	56.6	.82C	2.80	12.4	18.4	****	****	1.4
694	2088.5	2.0	12.1	100.0	100.0	.82C	2.69	11.5	12.5	****	****	2.0
695	2088.7	1.9	17.8	100.0	100.0	.82C	2.67	15.7	18.1	****	****	1.9
696	2088.9	4.6	24.0	100.0	100.0	.82C	2.64	21.4	24.7	****	****	4.6
697	2089.1	10.9	26.2	100.0RC	100.0	.82C	2.65	26.4	27.8	****	****	10.9
698	2089.3	24.3	23.5	100.0	100.0	.82C	2.64	29.2	27.0	****	****	24.3
699	2089.5	38.2	21.4	100.0	93.6	.82C	2.66	34.0	27.4	****	****	38.2
700	2089.7	42.1	24.5	100.0	84.9	.82C	2.78	41.6	33.7	****	****	42.1

NIVEAU	TOIT	ARG.	POR.	SXC	SW	C.HY.	C.MAT.	NEU	DEN	SON	SEC	VSTGR
701	2089.9	37.1MA	*****NC	*****	*****	****C	****NC	46.9	****	****	****	37.1
702	2090.1	35.7MA	*****NC	*****	*****	****C	****NC	47.8	****	****	****	35.7
703	2090.3	35.5MA	*****NC	*****	*****	****C	****NC	43.4	****	****	****	35.5
704	2090.5	30.4	26.7	100.0RC	100.0	.82C	2.76	39.4	32.5	****	****	33.9
705	2090.7	32.0	25.4	100.0RC	100.0	.82C	2.76	38.5	32.0	****	****	32.0
706	2090.9	25.8	27.9	100.0RC	100.0	.82C	2.77	38.8	33.3	****	****	25.8
707	2091.1	21.0	27.8	100.0	88.9	.82C	2.70	35.5	31.6	****	****	21.0
708	2091.3	12.4	29.6	100.0	92.0	.82C	2.71	34.1	31.8	****	****	12.4
709	2091.5	9.8	28.9	100.0RC	100.0	.82D	2.69	31.4	30.6	****	****	9.8
710	2091.7	11.0	26.9	100.0	100.0	.82C	2.66	28.2	28.7	****	****	11.0
711	2091.9	17.7	24.6	100.0	100.0	.82C	2.66	28.7	27.4	****	****	17.7
712	2092.1	27.9	22.4	100.0	100.0	.82C	2.68	31.7	27.1	****	****	27.9
713	2092.3	36.4	21.0	100.0	91.5	.82C	2.73	35.3	28.1	****	****	36.4
714	2092.5	37.1	21.3	100.0	95.3	.82C	2.78	36.8	29.4	****	****	37.1
715	2092.7	35.5	20.5	100.0RC	100.0	.82C	2.75	34.7	27.6	****	****	35.5
716	2092.9	36.6	18.3	100.0RC	100.0	.82C	2.68	31.2	24.6	****	****	36.6
717	2093.1	34.3	19.4	100.0RC	100.0	.82D	2.72	32.7	25.9	****	****	34.3
718	2093.3	30.7	20.6	100.0RC	100.0	.82C	2.74	33.0	26.7	****	****	30.7
719	2093.5	27.8	21.1	100.0RC	100.0	.82C	2.74	32.5	26.7	****	****	27.8
720	2093.7	25.6	22.2	100.0	89.4	.82C	2.74	32.6	27.3	****	****	25.6
721	2093.9	25.0	21.3	100.0RC	100.0	.82D	2.70	30.2	25.7	****	****	25.0
722	2094.1	28.7	20.2	100.0RC	100.0	.82C	2.68	29.5	24.9	****	****	28.7
723	2094.3	36.5	18.8	100.0	91.5	.82C	2.66	30.6	24.5	****	****	36.5
724	2094.5	43.5	17.7	100.0	93.8	.82C	2.68	33.1	24.9	****	****	43.5
725	2094.7	44.9	18.2	100.0RC	100.0	.82C	2.72	35.4	26.6	****	****	44.9
726	2094.9	47.8	17.5	100.0	91.0	.82C	2.74	36.2	27.0	****	****	47.8
727	2095.1	46.3	18.8	100.0	80.3	.82C	2.76	37.1	28.3	****	****	46.3
728	2095.3	46.0	19.2	100.0RC	88.4	.82C	2.74	37.2	28.4	****	****	46.0
729	2095.5	48.1	21.0	100.0	76.1	.82C	2.78	40.3	31.5	****	****	48.1
730	2095.7	50.3	20.0	100.0	87.7	.82D	2.74	39.5	30.0	****	****	50.3
731	2095.9	56.1	17.1	100.0	84.9	.82C	2.77	39.2	29.0	****	****	56.1
732	2096.1	61.9	17.0	100.0	82.9	.82C	3.05	44.0	36.8	****	****	61.9
733	2096.3	63.1	14.8	100.0	84.7	.82C	2.96	46.5	33.0	****	****	63.1
734	2096.5	61.9	14.4	100.0	90.8	.82D	2.95	45.7	32.0	****	****	61.9
735	2096.7	56.0	17.3	100.0	86.7	.82C	3.03	42.8	34.8	****	****	56.0
736	2096.9	47.2	18.3	100.0RC	100.0	.82D	2.85	38.5	29.9	****	****	47.2
737	2097.1	36.4	20.9	100.0RC	100.0	.82C	2.80	36.6	29.1	****	****	36.4
738	2097.3	22.2	24.0	100.0RC	100.0	.82C	2.78	34.1	28.8	****	****	22.2
739	2097.5	9.4	26.2	100.0RC	100.0	.82C	2.72	30.0	28.0	****	****	9.4
740	2097.7	4.2	27.1	100.0RC	100.0	.82C	2.70	27.8	27.9	****	****	4.2
741	2097.9	2.6	27.1	100.0RC	100.0	.82D	2.68	25.7	27.5	****	****	2.6
742	2098.1	1.7	27.9	100.0RC	100.0	.82C	2.67	25.4	28.2	****	****	1.7
743	2098.3	1.2	28.1	100.0RC	100.0	.82C	2.66	25.3	28.3	****	****	1.2
744	2098.5	3.0	27.4	100.0RC	100.0	.82C	2.66	25.1	27.8	****	****	3.0
745	2098.7	4.6	26.1	100.0RC	100.0	.82D	2.67	25.0	26.8	****	****	4.6
746	2098.9	5.0	25.6	100.0	100.0	.82C	2.68	25.3	26.4	****	****	5.0
747	2099.1	6.1	25.3	100.0	100.0	.82C	2.68	25.5	26.3	****	****	6.1
748	2099.3	11.2	23.9	100.0	100.0	.82C	2.66	25.3	25.7	****	****	11.2
749	2099.5	18.1	23.1	100.0	100.0	.82C	2.64	26.2	25.8	****	****	18.1
750	2099.7	26.8	22.3	100.0	96.7	.82D	2.62	28.3	26.0	****	****	26.8

NIVEAU	TOIT	ARG.	POR.	SXC	SW	D.HY.	C.MAT.	NEU	DEN	SCN	SEC	VSTGR
751	2099.9	39.2	21.2	100.0	96.4	.82C	2.60	32.1	26.1	****	****	39.2
752	2109.1	52.9	20.0	100.0	82.5	.82C	2.61	37.8	27.1	****	****	52.9
753	2100.3	56.5MA	*****NC	*****	*****	****C	****NC	43.4	****	****	****	56.5
754	2100.5	54.9MA	*****NC	*****	*****	****C	****NC	43.8	****	****	****	54.9
755	2100.7	54.8	17.3	100.0	77.0	.82C	2.76	36.7	28.5	****	****	54.8
756	2100.9	48.9	15.6	100.0	96.2	.82C	2.77	35.1	25.9	****	****	48.9
757	2101.1	41.4	18.1	100.0RC	100.0	.82C	2.80	35.5	27.4	****	****	41.4
758	2101.3	18.4	27.3	100.0RC	100.0	.82C	2.86	27.8	30.9	****	****	35.0
759	2101.5	27.0	22.9	100.0RC	100.0	.82C	2.79	35.0	28.9	****	****	27.0
760	2101.7	15.2	23.6	100.0	100.0	.82C	2.72	29.7	26.5	****	****	15.2
761	2101.9	4.4	27.3	100.0RC	100.0	.82C	2.72	29.2	28.1	****	****	4.4
762	2102.1	0.0	29.6	100.0RC	100.0	.82C	2.70	28.5	29.6	****	****	0.0
763	2102.3	0.0	30.0	100.0RC	100.0	.82C	2.67	27.2	30.0	****	****	0.0
764	2102.5	0.0	30.5	100.0RC	100.0	.82C	2.66	27.2	30.5	****	****	0.0
765	2102.7	.7	30.9	100.0RC	100.0	.82C	2.66	27.6	31.0	****	****	.7
766	2102.9	2.3	30.9	100.0RC	100.0	.82C	2.66	28.1	31.3	****	****	2.3
767	2103.1	1.7	30.9	100.0RC	100.0	.82C	2.66	28.2	31.2	****	****	1.7
768	2103.3	2.4	29.9	100.0RC	100.0	.82C	2.67	28.0	30.3	****	****	2.4
769	2103.5	2.9	29.6	100.0RC	100.0	.82C	2.68	28.3	30.1	****	****	2.9
770	2103.7	.9	30.3	100.0RC	100.0	.82C	2.68	28.4	30.4	****	****	.9
771	2103.9	0.0	30.1	100.0RC	100.0	.82C	2.68	27.8	30.1	****	****	0.0
772	2104.1	0.0	29.6	100.0RC	100.0	.82C	2.67	26.8	29.6	****	****	0.0
773	2104.3	0.0	29.3	100.0RC	100.0	.82C	2.66	25.8	29.3	****	****	0.0
774	2104.5	0.0	28.4	100.0RC	100.0	.82C	2.66	25.0	28.4	****	****	0.0
775	2104.7	0.0	27.8	100.0RC	100.0	.82C	2.66	24.3	27.8	****	****	0.0
776	2104.9	0.0	28.1	100.0RC	100.0	.82C	2.66	24.6	28.1	****	****	0.0
777	2105.1	.3	26.7	100.0RC	100.0	.82C	2.66	25.4	28.8	****	****	.3
778	2105.3	1.0	28.2	100.0RC	100.0	.82C	2.67	25.9	28.4	****	****	1.0
779	2105.5	0.0	28.6	100.0RC	100.0	.82C	2.67	25.9	28.6	****	****	0.0
780	2105.7	0.0	28.9	100.0RC	100.0	.82C	2.67	25.8	28.9	****	****	0.0
781	2105.9	.3	28.6	100.0RC	100.0	.82C	2.67	25.7	28.6	****	****	.3
782	2106.1	0.0	28.7	100.0RC	100.0	.82C	2.67	25.9	28.7	****	****	0.0
783	2106.3	0.0	28.5	100.0RC	100.0	.82C	2.68	26.2	28.5	****	****	0.0
784	2106.5	0.0	28.3	100.0RC	100.0	.82C	2.67	25.7	28.3	****	****	0.0
785	2106.7	.3	28.1	100.0RC	100.0	.82C	2.67	25.4	28.2	****	****	.3
786	2106.9	0.0	28.4	100.0RC	100.0	.82C	2.67	25.8	28.4	****	****	0.0
787	2107.1	0.0	28.7	100.0RC	100.0	.82C	2.68	26.2	28.7	****	****	0.0
788	2107.3	.2	27.9	100.0RC	100.0	.82C	2.68	25.8	27.9	****	****	.2
789	2107.5	.4	27.6	100.0RC	100.0	.82C	2.68	25.6	27.7	****	****	.4
790	2107.7	2.3	27.0	100.0RC	100.0	.82C	2.67	25.0	27.4	****	****	2.3
791	2107.9	.7	27.4	100.0RC	100.0	.82C	2.67	24.6	27.5	****	****	.7
792	2108.1	0.0	27.6	100.0RC	100.0	.82C	2.67	24.9	27.6	****	****	0.0
793	2108.3	0.0	27.9	100.0RC	100.0	.82C	2.67	25.2	27.9	****	****	0.0
794	2108.5	0.0	27.6	100.0RC	100.0	.82C	2.67	24.8	27.6	****	****	0.0
795	2108.7	0.0	27.8	100.0RC	100.0	.82C	2.67	24.6	27.8	****	****	0.0
796	2108.9	.4	27.6	100.0RC	100.0	.82C	2.67	25.1	27.7	****	****	.4
797	2109.1	.3	27.7	100.0RC	100.0	.82C	2.67	25.0	27.8	****	****	.3
798	2109.3	.5	27.7	100.0RC	100.0	.82C	2.67	25.3	27.8	****	****	.5
799	2109.5	.5	27.4	100.0RC	100.0	.82C	2.68	25.7	27.5	****	****	.5
800	2109.7	0.0	27.2	100.0RC	100.0	.82C	2.69	25.5	27.2	****	****	0.0

NIVEAU	TOIT	ARG.	PCR.	SXC	SW	C.FY.	C.MAT.	NEU	CFN	SCN	SEC	VSHCR
801	2109.9	0.0	27.8	100.0RC	100.0	.82C	2.68	25.4	27.8	****	****	0.0
802	2110.1	1.2	27.7	100.0RC	100.0	.82C	2.68	26.1	27.9	****	****	1.2
803	2110.3	2.1	27.2	100.0RC	100.0	.82C	2.68	25.7	27.5	****	****	2.1
804	2110.5	1.6	26.8	100.0RC	100.0	.82C	2.67	24.6	27.0	****	****	1.6
805	2110.7	1.6	26.6	100.0RC	100.0	.82C	2.67	24.6	26.8	****	****	1.6
806	2110.9	.7	27.0	100.0RC	100.0	.82C	2.67	24.4	27.1	****	****	.7
807	2111.1	.4	27.4	100.0RC	100.0	.82C	2.67	24.4	27.4	****	****	.4
808	2111.3	.4	27.4	100.0RC	100.0	.82C	2.67	24.7	27.5	****	****	.4
809	2111.5	0.0	26.8	100.0RC	100.0	.82C	2.68	24.6	26.8	****	****	0.0
810	2111.7	0.0	26.5	100.0RC	100.0	.82C	2.68	24.3	26.5	****	****	0.0
811	2111.9	0.0	26.3	100.0RC	100.0	.82C	2.67	23.7	26.3	****	****	0.0
812	2112.1	0.0	26.5	100.0RC	100.0	.82C	2.67	23.5	26.5	****	****	0.0
813	2112.3	0.0	26.7	100.0RC	100.0	.82C	2.67	23.7	26.7	****	****	0.0
814	2112.5	0.0	26.4	100.0RC	100.0	.82C	2.67	23.4	26.4	****	****	0.0
815	2112.7	0.0	25.5	100.0RC	100.0	.82C	2.67	22.6	25.5	****	****	0.0
816	2112.9	2.7	24.2	100.0	100.0	.82C	2.67	22.2	24.6	****	****	2.7
817	2113.1	6.7	23.3	100.0	100.0	.82C	2.66	22.6	24.3	****	****	6.7
818	2113.3	10.1	23.1	100.0	100.0	.82C	2.66	24.1	24.8	****	****	10.1
819	2113.5	15.6	21.9	100.0	100.0	.82C	2.67	25.5	24.4	****	****	15.6
820	2113.7	22.2	20.0	100.0	100.0	.82C	2.69	27.2	23.8	****	****	22.2
821	2113.9	0.0	27.9	100.0RC	96.0	.82C	2.80	29.6	29.2	****	****	26.6
822	2114.1	5.4	27.9	100.0RC	100.0	.82C	2.77	31.4	28.8	****	****	30.1
823	2114.3	30.8	22.0	100.0	70.6	.82C	2.65	31.1	26.7	****	****	30.8
824	2114.5	31.6	9.7	100.0RC	100.0	.82C	2.32	30.2	7.8	****	****	31.6
825	2114.7	26.5	20.7	100.0RC	100.0	.82C	2.66	28.5	24.9	****	****	26.5
826	2114.9	20.7	20.5	100.0	91.5	.82C	2.77	29.9	24.9	****	****	20.7
827	2115.1	21.4	18.6	100.0	99.3	.82C	2.86	31.2	24.0	****	****	21.4
828	2115.3	26.8	20.1	100.0	100.0	.82C	2.81	32.8	26.3	****	****	26.8
829	2115.5	30.4	22.3	100.0	75.3	.82C	2.73	34.3	28.2	****	****	30.4
830	2115.7	29.9	23.2	100.0	69.1	.82C	2.70	34.2	28.6	****	****	29.9
831	2115.9	31.3	24.2	100.0	62.8	.82C	2.69	35.1	29.6	****	****	31.3
832	2116.1	33.0	25.2	100.0	61.5	.82C	2.68	36.4	30.7	****	****	33.0
833	2116.3	39.6	23.4	100.0	60.9	.82C	2.65	36.3	29.4	****	****	39.6
834	2116.5	48.1	18.6	100.0	69.7	.82C	2.66	35.5	26.3	****	****	48.1
835	2116.7	43.5	18.9	100.0	73.9	.82C	2.75	36.1	27.7	****	****	43.5
836	2116.9	39.9	20.4	100.0	73.2	.82C	2.75	36.3	28.5	****	****	39.9
837	2117.1	40.7	22.3	100.0	69.8	.82C	2.81	39.5	31.7	****	****	40.7
838	2117.3	39.1	24.1	100.0	69.5	.82C	2.84	41.2	33.6	****	****	39.1
839	2117.5	41.6MA	*****NC	*****	*****	*****	*****NC	42.3	*****	****	****	41.6
840	2117.7	42.2	7.6	100.0RC	100.0	.82C	2.33	42.0	5.2	****	****	42.2
841	2117.9	41.9	21.3	100.0	75.1	.82C	2.85	39.6	31.5	****	****	41.9
842	2118.1	40.4MA	*****NC	*****	*****	*****	*****NC	40.6	*****	****	****	40.4
843	2118.3	42.6MA	*****NC	*****RC	*****	*****	*****NC	42.2	*****	****	****	42.6
844	2118.5	45.5MA	*****NC	*****	*****	*****	*****NC	40.8	*****	****	****	45.5
845	2118.7	49.3MA	*****NC	*****	*****	*****	*****NC	41.2	*****	****	****	49.3
846	2118.9	50.4	20.7	100.0	66.4	.82C	2.89	42.3	33.9	****	****	50.4
847	2119.1	46.6MA	*****NC	*****RC	*****	*****	*****NC	41.5	*****	****	****	46.6
848	2119.3	44.1MA	*****NC	*****RC	*****	*****	*****NC	38.3	*****	****	****	44.1
849	2119.5	44.8	18.2	95.8RC	80.8	.82C	2.97	35.6	31.5	****	****	44.8
850	2119.7	44.7	16.2	100.0	85.1	.82C	2.86	35.9	27.3	****	****	44.7

NIVEAU	TOIT	ARG.	PGR.	SXG	SW	C.HY.	C.MAT.	NEU	DEN	SCA	SEC	VSTGR
851	2119.9	38.2	16.9	100.0	90.6	.820	2.84	34.2	26.1	***	***	38.2
852	2120.1	32.4	16.8	100.0	100.0	.820	2.80	31.3	24.1	***	***	32.4
853	2120.3	23.9	19.6	100.0	100.0	.820	2.81	31.3	25.1	***	***	23.9
854	2120.5	13.8	23.6	100.0	100.0	.820	2.79	31.1	26.6	***	***	13.8
855	2120.7	5.7	26.3	100.0RC	100.0	.820	2.71	28.6	27.4	***	***	5.7
856	2120.9	C.0	28.3	100.0RC	100.0	.820	2.67	25.4	28.3	***	***	C.0
857	2121.1	C.0	27.8	100.0RC	100.0	.820	2.67	24.8	27.8	***	***	C.0
858	2121.3	C.0	27.2	100.0RC	100.0	.820	2.67	24.2	27.2	***	***	C.0
859	2121.5	C.0	27.0	100.0RC	100.0	.820	2.67	24.1	27.0	***	***	C.0
860	2121.7	C.0	26.9	100.0RC	100.0	.820	2.67	24.0	26.9	***	***	C.0
861	2121.9	.7	26.6	100.0RC	100.0	.820	2.67	24.3	26.7	***	***	.7
862	2122.1	C.0	26.9	100.0RC	100.0	.820	2.68	24.6	26.9	***	***	C.0
863	2122.3	.2	27.5	100.0RC	100.0	.820	2.68	25.1	27.6	***	***	.2
864	2122.5	2.1	26.8	100.0RC	100.0	.820	2.68	25.2	27.1	***	***	2.1
865	2122.7	4.2	26.9	100.0RC	100.0	.820	2.67	25.5	27.6	***	***	4.2
866	2122.9	4.0	26.8	100.0RC	100.0	.820	2.66	24.9	27.4	***	***	4.5
867	2123.1	6.0	25.3	100.0RC	100.0	.820	2.67	24.4	26.3	***	***	8.9
868	2123.3	12.3	23.4	100.0RC	100.0	.820	2.65	24.6	25.3	***	***	12.3
869	2123.5	3.0	25.4	100.0RC	100.0	.820	2.69	25.0	25.9	***	***	16.7
870	2123.7	13.5	22.2	100.0RC	96.6	.820	2.68	24.8	24.2	***	***	21.2
871	2123.9	22.8	18.9	100.0	51.5	.820	2.64	24.3	22.4	***	***	22.8
872	2124.1	22.9	18.6	100.0	100.0	.820	2.64	24.0	22.0	***	***	22.9
873	2124.3	22.7	18.4	100.0RC	100.0	.820	2.66	24.8	22.1	***	***	22.7
874	2124.5	22.6	18.3	100.0RC	100.0	.820	2.69	26.0	22.2	***	***	22.6
875	2124.7	17.1	20.2	100.0RC	100.0	.820	2.72	27.0	23.4	***	***	17.1
876	2124.9	9.8	23.8	100.0RC	100.0	.820	2.69	26.5	25.5	***	***	9.8
877	2125.1	8.0	25.2	100.0RC	100.0	.820	2.68	26.1	26.5	***	***	8.0
878	2125.3	5.6	26.6	100.0RC	100.0	.820	2.67	26.4	27.6	***	***	5.6
879	2125.5	3.3	28.3	100.0RC	100.0	.820	2.67	27.0	28.8	***	***	3.3
880	2125.7	4.9	27.8	100.0RC	100.0	.820	2.67	27.2	28.6	***	***	4.9
881	2125.9	4.7	27.8	100.0RC	100.0	.820	2.68	27.6	28.6	***	***	4.7
882	2126.1	8.7	26.9	100.0RC	100.0	.820	2.67	27.5	28.2	***	***	8.7
883	2126.3	6.6	27.3	100.0RC	100.0	.820	2.67	27.1	28.4	***	***	6.6
884	2126.5	7.5	27.1	100.0RC	100.0	.820	2.67	27.2	28.3	***	***	7.5
885	2126.7	10.6	26.0	100.0RC	100.0	.820	2.66	26.7	27.7	***	***	10.6
886	2126.9	10.2	26.2	100.0RC	100.0	.820	2.66	26.9	27.9	***	***	10.2
887	2127.1	8.7	26.5	100.0RC	100.0	.820	2.67	27.1	28.0	***	***	8.7
888	2127.3	7.2	26.8	100.0RC	100.0	.820	2.67	26.9	28.0	***	***	8.0
889	2127.5	8.4	26.1	100.0RC	100.0	.820	2.66	26.1	27.4	***	***	8.4
890	2127.7	9.9	24.9	100.0RC	100.0	.820	2.67	26.0	26.5	***	***	9.9
891	2127.9	10.5	23.4	100.0RC	100.0	.820	2.70	26.6	25.3	***	***	10.5
892	2128.1	10.4	23.9	100.0RC	100.0	.820	2.71	27.3	25.8	***	***	10.4
893	2128.3	7.1	25.9	100.0RC	100.0	.820	2.69	27.6	27.2	***	***	7.1
894	2128.5	6.0	26.3	100.0RC	100.0	.820	2.66	25.5	27.3	***	***	6.0
895	2128.7	6.6	26.4	100.0RC	100.0	.820	2.64	24.5	27.4	***	***	6.6
896	2128.9	6.4	26.6	100.0RC	100.0	.820	2.65	25.0	27.5	***	***	6.4
897	2129.1	4.7	27.0	100.0RC	100.0	.820	2.66	25.5	27.7	***	***	4.7
898	2129.3	4.0	26.9	100.0RC	100.0	.820	2.67	26.0	27.5	***	***	4.0
899	2129.5	4.1	27.1	100.0RC	100.0	.820	2.69	27.1	27.8	***	***	4.1
900	2129.7	3.0	27.4	100.0RC	100.0	.820	2.69	27.5	28.0	***	***	3.0

NIVEAU	TOIT	ARG.	PCR.	SXO	Sh	C.HY.	C.MAT.	NEU	DEN	SCN	SEC	VSHGR
901	2129.9	3.7	26.9	100.0RC	100.0	.82C	2.70	27.6	27.6	****	****	3.7
902	2130.1	3.2	27.2	100.0RC	100.0	.82C	2.69	27.0	27.8	****	****	3.2
903	2130.3	1.6	27.1	100.0RC	100.0	.82D	2.69	26.4	27.4	****	****	1.6
904	2130.5	1.6	26.9	100.0RC	100.0	.82C	2.69	25.9	27.1	****	****	1.6
905	2130.7	2.6	27.0	100.0RC	100.0	.82C	2.68	25.6	27.5	****	****	2.6
906	2130.9	2.6	26.9	100.0RC	100.0	.82C	2.67	25.1	27.3	****	****	2.6
907	2131.1	.7	27.4	100.0RC	100.0	.82C	2.68	25.5	27.5	****	****	.7
908	2131.3	.2	27.3	100.0RC	100.0	.82C	2.69	25.8	27.3	****	****	.2
909	2131.5	.4	27.1	100.0RC	100.0	.82C	2.68	25.4	27.2	****	****	.4
910	2131.7	0.0	27.3	100.0RC	100.0	.82C	2.68	25.2	27.3	****	****	C.0
911	2131.9	0.0	26.9	100.0RC	100.0	.82C	2.68	24.7	26.9	****	****	C.0
912	2132.1	1.6	26.3	100.0RC	100.0	.82C	2.67	24.3	26.6	****	****	1.6
913	2132.3	C.0	27.0	100.0RC	100.0	.82C	2.67	24.2	27.0	****	****	C.0
914	2132.5	.4	27.3	100.0RC	100.0	.82C	2.68	25.0	27.3	****	****	.4
915	2132.7	.5	27.1	100.0RC	100.0	.82D	2.67	24.7	27.2	****	****	.5
916	2132.9	1.6	26.9	100.0RC	100.0	.82C	2.67	24.8	27.2	****	****	1.6
917	2133.1	2.1	26.6	100.0RC	100.0	.82C	2.67	24.9	27.0	****	****	2.1
918	2133.3	1.1	26.9	100.0RC	100.0	.82C	2.68	25.2	27.1	****	****	1.1
919	2133.5	3.2	26.6	100.0RC	100.0	.82C	2.67	25.1	27.1	****	****	3.2
920	2133.7	3.5	26.1	100.0RC	100.0	.82C	2.66	24.1	26.6	****	****	3.5
921	2133.9	1.8	26.1	100.0RC	100.0	.82D	2.66	23.4	26.4	****	****	1.8
922	2134.1	1.1	26.5	100.0RC	100.0	.82C	2.67	24.1	26.6	****	****	1.1
923	2134.3	.4	26.9	100.0RC	100.0	.82C	2.67	24.1	27.0	****	****	.4
924	2134.5	0.0	27.1	100.0RC	100.0	.82C	2.67	24.3	27.1	****	****	C.0
925	2134.7	C.0	26.9	100.0RC	100.0	.82C	2.67	24.3	26.9	****	****	C.0
926	2134.9	1.4	26.1	100.0RC	100.0	.82C	2.67	24.0	26.4	****	****	1.4
927	2135.1	1.4	26.0	100.0RC	100.0	.82C	2.67	24.0	26.3	****	****	1.4
928	2135.3	1.6	26.1	100.0RC	100.0	.82C	2.68	24.7	26.4	****	****	1.6
929	2135.5	0.0	26.9	100.0RC	100.0	.82C	2.69	25.4	26.9	****	****	C.0
930	2135.7	1.1	27.3	100.0RC	100.0	.82C	2.68	25.7	27.4	****	****	1.1
931	2135.9	3.7	26.6	100.0RC	100.0	.82C	2.67	25.5	27.2	****	****	3.7
932	2136.1	2.1	27.2	100.0RC	100.0	.82C	2.68	26.0	27.6	****	****	2.1
933	2136.3	1.6	28.0	100.0RC	100.0	.82C	2.68	26.8	28.3	****	****	1.6
934	2136.5	0.0	28.3	100.0RC	100.0	.82C	2.68	26.5	28.3	****	****	C.0
935	2136.7	C.0	28.0	100.0RC	100.0	.82C	2.69	26.5	28.0	****	****	C.0
936	2136.9	1.8	27.3	100.0RC	100.0	.82C	2.69	26.4	27.6	****	****	1.8
937	2137.1	.7	27.4	100.0RC	100.0	.82C	2.68	25.6	27.5	****	****	.7
938	2137.3	2.7	26.5	100.0RC	100.0	.82C	2.68	25.1	26.9	****	****	2.7
939	2137.5	2.5	26.5	100.0RC	100.0	.82C	2.67	24.6	26.9	****	****	2.5
940	2137.7	1.2	26.6	100.0RC	100.0	.82D	2.67	24.0	26.8	****	****	1.2
941	2137.9	.2	26.7	100.0RC	100.0	.82C	2.68	24.3	26.8	****	****	.2
942	2138.1	0.0	26.5	100.0RC	100.0	.82C	2.68	24.4	26.5	****	****	0.0
943	2138.3	.5	26.6	100.0RC	100.0	.82D	2.67	24.2	25.7	****	****	.5
944	2138.5	2.7	25.8	100.0RC	100.0	.82C	2.67	23.8	26.3	****	****	2.7
945	2138.7	3.7	25.6	100.0RC	100.0	.82C	2.66	23.6	26.2	****	****	3.7
946	2138.9	4.2	25.5	100.0RC	100.0	.82C	2.66	23.4	26.2	****	****	4.2
947	2139.1	2.3	25.8	100.0RC	100.0	.82C	2.66	23.1	26.2	****	****	2.3
948	2139.3	1.8	26.0	100.0RC	100.0	.82C	2.65	22.7	26.3	****	****	1.8
949	2139.5	3.7	25.6	100.0RC	100.0	.82C	2.65	22.8	26.1	****	****	3.7
950	2139.7	C.0	26.0	100.0RC	100.0	.82C	2.66	22.7	26.0	****	****	5.7

NIVEAU	TOIT	ARG.	POR.	SXC	SW	C.FY.	C.MAT.	NEU	DEN	SCN	SEC	VSTGR
951	2139.9	7.4	23.9	100.CRC	100.0	.82C	2.64	22.3	25.0	****	****	7.4
952	2140.1	8.4	23.7	100.0RC	100.0	.82C	2.64	22.7	25.0	****	****	8.4
953	2140.3	9.5	22.5	100.0RC	100.0	.82C	2.65	22.3	23.9	****	****	9.5
954	2140.5	13.7	20.5	100.0RC	100.0	.82C	2.64	21.9	22.5	****	****	13.7
955	2140.7	14.5	20.0	100.0RC	100.0	.82C	2.65	22.0	22.2	****	****	14.5
956	2140.9	10.6	21.2	100.0RC	100.0	.82C	2.67	22.8	23.0	****	****	10.6
957	2141.1	9.7	21.9	100.0PC	100.0	.82C	2.67	23.2	23.5	****	****	9.7
958	2141.3	7.2	23.4	100.0RC	100.0	.82C	2.67	23.8	24.6	****	****	7.2
959	2141.5	3.4	25.0	100.0RC	100.0	.82C	2.68	24.0	25.6	****	****	3.4
960	2141.7	5.0	24.8	100.0RC	100.0	.82C	2.68	24.4	25.6	****	****	5.0
961	2141.9	6.5	24.2	100.0RC	100.0	.82C	2.68	24.4	25.3	****	****	6.5
962	2142.1	6.9	23.5	100.0RC	100.0	.82C	2.67	23.6	24.6	****	****	6.9
963	2142.3	6.7	23.3	100.0RC	100.0	.82C	2.67	23.2	24.4	****	****	6.7
964	2142.5	6.3	22.8	100.0RC	100.0	.82C	2.66	22.0	23.8	****	****	6.3
965	2142.7	8.3	22.4	100.0RC	100.0	.82C	2.65	21.7	23.7	****	****	8.3
966	2142.9	8.2	22.5	100.0	100.0	.82C	2.66	22.3	23.8	****	****	8.2
967	2143.1	6.4	22.6	100.0	100.0	.82C	2.66	22.1	23.7	****	****	6.4
968	2143.3	9.7	21.2	100.0RC	100.0	.82C	2.65	21.3	22.7	****	****	9.7
969	2143.5	9.7	20.8	100.0RC	100.0	.82C	2.64	20.5	22.3	****	****	9.7
970	2143.7	8.2	21.6	100.0	100.0	.82C	2.64	20.3	22.8	****	****	8.2
971	2143.9	5.8	22.0	100.0RC	100.0	.82C	2.65	20.2	22.9	****	****	5.8
972	2144.1	4.4	22.1	100.0RC	100.0	.82C	2.65	20.1	22.8	****	****	4.4
973	2144.3	3.8	22.3	100.0RC	100.0	.82C	2.65	19.8	22.9	****	****	3.8
974	2144.5	6.5	22.1	100.0	100.0	.82C	2.65	20.5	23.1	****	****	6.5
975	2144.7	3.8	23.4	100.0RC	100.0	.82C	2.67	22.0	24.1	****	****	5.1
976	2144.9	0.0	24.3	100.0RC	98.9	.82C	2.68	22.3	24.3	****	****	7.8
977	2145.1	10.1	20.9	100.0	78.2	.82C	2.66	21.8	22.5	****	****	10.1
978	2145.3	16.1	18.3	100.0	73.3	.82C	2.66	21.7	20.8	****	****	16.1
979	2145.5	23.8	14.3	100.0	78.9	.82C	2.70	22.7	18.5	****	****	23.8
980	2145.7	29.0	10.8	100.0	88.9	.82C	2.78	23.5	17.0	****	****	29.0
981	2145.9	25.8	10.3	100.0	90.0	.82C	2.79	23.7	16.9	****	****	25.8
982	2146.1	33.1	10.6	100.0	93.8	.82C	2.78	24.8	17.8	****	****	33.1
983	2146.3	36.3	12.9	82.6	79.3	.82C	2.79	25.2	20.8	****	****	36.3
984	2146.5	38.6	10.0	100.0	85.9	.82C	2.69	24.0	16.6	****	****	38.6
985	2146.7	39.6	9.8	100.0RC	100.0	.82C	2.73	25.3	17.5	****	****	39.6
986	2146.9	37.5	11.7	100.0	100.0	.82C	2.77	27.1	19.5	****	****	37.5
987	2147.1	38.2	12.1	100.0	100.0	.82C	2.73	27.1	19.5	****	****	38.2
988	2147.3	34.5	14.1	100.0RC	100.0	.82C	2.72	27.4	20.6	****	****	34.5
989	2147.5	27.5	16.6	100.0RC	100.0	.82C	2.71	27.2	21.7	****	****	27.5
990	2147.7	23.5	18.4	100.0RC	100.0	.82C	2.69	26.4	22.5	****	****	23.5
991	2147.9	16.6	21.8	100.0	100.0	.82C	2.66	25.2	24.4	****	****	16.6
992	2148.1	9.9	24.5	100.0	100.0	.82C	2.65	24.8	26.1	****	****	9.9
993	2148.3	9.0	24.5	100.0RC	100.0	.82C	2.66	24.6	26.0	****	****	9.0
994	2148.5	5.8	24.2	100.0RC	100.0	.82C	2.66	24.9	25.8	****	****	5.8
995	2148.7	8.5	24.7	100.0	100.0	.82C	2.66	24.7	26.0	****	****	8.5
996	2148.9	5.4	25.9	100.0	100.0	.82C	2.66	24.6	26.8	****	****	5.4
997	2149.1	3.4	25.7	100.0	100.0	.82C	2.67	23.9	26.2	****	****	3.4
998	2149.3	3.4	24.8	100.0	100.0	.82C	2.66	22.4	25.3	****	****	3.4
999	2149.5	4.3	23.9	100.0	100.0	.82C	2.65	21.2	24.5	****	****	4.3
1000	2149.7	3.9	24.1	100.0	100.0	.82C	2.66	22.1	24.7	****	****	3.9

* 25-1-4 *

SNEAP ETU/GIS

PICARDIA

Service Diagraphies
DPRO/GIS
Reference: 9/47 ELF NORGE

COMPUTER PROCESSED INTERPRETATION

PUITS : 25/1-4
WELL : FRIGG
CHAMP : FRIGG
FIELD : FRIGG
SOCIETE : ELF NORGE
COMPANY : ELF NORGE
SIGLE :
CHAMP : FRIGG
FIELD : FRIGG
PERMIS :
PERMIT :
ETAT : NORVEGE
STATE : NORVEGE

Coordonnées : X : 02.15.54.08
Y : 59.5915215N
Z : 25.50
Date enreg. diagraphies :
Logs recording date : 10 mai 1974
Echelle :
Diagram scale : 1/200

Programme :
Main program : PICARDIA
Sous-programme :
Sub-program : NEIDER
LITHO

Date interprétation :
Processing date : MAI 1979

Intervalle no : 1
Interval :
Profondeur inférieure : 2150 mètres
Bottom interval :
Profondeur supérieure : 1950 mètres
Top interval :
Intervalle totale : 200 mètres
Processed length :

Diagraphies utilisées :
Logs processed :
Resistivité : MIA-119-T16
Porosité : BHC-FDC-CNTL
Autres : GR-PS-CAL

Données du trou a : 1950 mètres
Well data of :
Diamètre du trou : 8.1271
Bit size : 129.6° F
Température : FGL/LG+BM
Moy. Type : 1.25
Densité : 0.135 m
R_m : 0.100 m
R_{mc} : 0.321 m

Remarques :

Cette interprétation est le résultat de calculs effectués par ordinateur suivant la procédure habituellement préconisée par les spécialistes de l'analyse des logs, et compte tenu de paramètres choisis au mieux de nos connaissances.
Les résultats ci-dessous doivent être considérés comme une bonne approche des paramètres pétrophysiques recherchés, et non comme reflétant des valeurs absolues, ils sont en effet issus de déductions automatiques.
Il convient tout particulièrement de ne pas prendre en considération les résultats au droit des cavités, l'influence du trou sur les différentes réponses des logs ne pouvant y être toujours valablement corrigée.

This interpretation is the result of electronic computation using methods generally accepted in logging analysis, and also parameters chosen to the best of our knowledge.
The above results are a good approach to the petrophysical parameters sought after, but they must not be considered as absolute values since they are proceeding from automatic deductions based on electrical or other measurements.
It must be specially noted that the results found in front of caved zones must be discarded since the influence of enlarged holes on the various logs responses cannot be always properly corrected.

