Seismograph Service (England) Limited

VELOCITY LOG

LINEAR TIME SCALE

COMPANY	STATOIL
WELL	15/9-18
FIELD	SIGMA
COUNTRY	NORWAY NORTH SEA
LOCATION	58° 21' 01.92" N 01° 48' 12.04" E

CALIBRATION 21.2.84

PERMANENT DATUM	MSL	ELEV.	ELEVATIONS A.M.S.L.
LOG MEASURED FROM	DERRICK FLOOR		K.B. 23 m
DRILLING MEASURED FROM	DERRICK FLOOR		D.F. 23 m
TOTAL TRAVEL TIME REFERRED TO	MSL		G.L. -97 m

DATE	19.12.83	28.12.83	17.1.84	4.2.84	20.2.84
RUN NUMBER	1A	2B	3C	4D	6E
DEPTH DRILLER	520 m	1170 m	2762 m	3321 m	3622 m
DEPTH LOGGER	521 m	1170.5 m	2764 m	3324 m	3623 m
TOP LOGGED INTERVAL	181 m	499 m	1150 m	2740 m	3188 m
BOTTOM LOGGED INTERVAL	520.5 m	1165 m	2757 m	3315 m	3616 m
CASING DRILLER	181 m	499 m	1150 m	2743 m	2743 m
CASING LOGGER	181 m	499 m	1150 m	2740 m	2743 m
TYPE FLUID IN HOLE	SW GEL	LIGNOSULPHONATE	GYPSUM	LIGNOSULPHONATE	
DENSITY	1.08	1.13	1.23	1.42	1.42
LOGGING SPEED ft/min	30	30	30	30	30
MAX. REC. TEMP. DEG. F.	100	100	136	211	208
OPERATING RIG TIME					
RECORDED BY	ARNESEN	HANSEN	ARNESEN	HANSEN	HANSEN

BOREHOLE RECORD			CASING RECORD	
RUN No.	BIT (IN.)	DEPTH m	SIZE (IN.)	DEPTH m
1A	12¼	521	30	181
2B	17½	1170.5	20	499
3C	12¼	2764	13⅜	1150
4D	8½	3324	9⅝	2740
6E	8½	3623	9⅝	

REMARKS

The integrator has been extrapolated 4 m below the bottom of the recorded log in order to include the check level at 3620 m below KB.

CORRECTIONS APPLIED

VERTICAL DEPTHS m	INTERVAL TIME CORRECTION
201 - 1233	Zero
1233 - 1893	2.8 μs/ft linear shift
1893 - 2237	4.3 μs/ft linear shift
2237 - 2993	2.4 μs/ft linear shift
2993 - 3348	5.2 μs/ft linear shift
3348 - 3618	1.1 μs/ft linear shift