



STATOIL

SERVICE PROCESSING CENTRE
STRAVANGER - NORWAY



BLOCK 15/9

LINE ST 8381-309
SP 1 - 365



FILTERED STACK

FIELD RECORDING PARAMETERS

DATA ACQUISITION SYSTEM: 48 CHANNELS
 RECORDING POLARITY: POSITIVE
 RECORD LENGTH/SAMPLE RATE: 17.5 SECS
 SAMPLE RATE: 4000 Hz
 RECORDING INSTRUMENT: 24 GROUPS
 SAMPLE GROUPS: 24 GROUPS
 RECORDING MODE: 24 GROUPS

PROCESSING PARAMETERS

DATA PROCESSED BY: STATOIL SERVICE PROCESSING CENTRE
 POLARITY CORRECTION: YES
 RECORD LENGTH: 17.5 SECS
 SAMPLE RATE: 4000 Hz
 FILTERS: 24 GROUPS
 FILTER TYPE: 24 GROUPS
 FILTER COEFFICIENTS: 24 GROUPS
 FILTER ORDER: 24 GROUPS
 FILTER DELAY: 24 GROUPS
 FILTER PHASE: 24 GROUPS
 FILTER GAIN: 24 GROUPS
 FILTER NOISE: 24 GROUPS
 FILTER SLOPE: 24 GROUPS
 FILTER CURVE: 24 GROUPS
 FILTER OFFSET: 24 GROUPS
 FILTER SCALE: 24 GROUPS
 FILTER UNIT: 24 GROUPS

PROCESSED BY: J.E.N.
OCT. 1983

DISPLAY PARAMETERS: NO SCALING
 LEFT HAND SECTION: PLOT GAIN : 0.2
 SCALING
 RIGHT HAND SECTION: PLOT GAIN : 1.0

DATE: 01/11/83
 TIME: 11:00
 SCALE: 1000000
 UNIT: SECS

