

725!
L-211



statoil

9 March 79

EL/GjO

CORRECTION TO "GEOLOGICAL PROGNOSIS & DRILLING
PROGRAM WELL 34/10-3"

Please note that pages 34 - 44: "Casing cement data and
calculations" are to be replaced by the following pages.

Also please note telephone number correction on page 7:

S. Nedland, Area Geologist mobile telephone: 64906

Sendes:

Oljedirektoratet (2)
Esso Exploration
Norsk Hydro
Saga Petroleum
Svein Nedland
Svein G. Larsen
Jakob Bleie
D.I. Milton
Tore Sund

12 MAR 1979
REGISTRERT
OLJEDIREKTORATET

CASING CEMENT DATA AND CALCULATIONS,

30" CASING.

GENERAL: The cement volume is calculated on the basis of theoretical hole volume, and the casing to be cemented to the sea bed with 150% excess on oper hole volume.

WELL DATA:

Depth kb-sea bed.....	197	m
Depth kb-last shoe.....	-	m
Depth kb-casing set point.....	250	m
Open hole dia.....	36	"
Annulus capacity, cased hole.....	-	l/m
Annulus capacity, open hole.....	200	l/m
Internal capacity, " casing.....	397	l/m
Mud weight.....	1.1	g/cm ³
Bottom hole hydrostatic pres. (BHHP).....		bar
Est. bottom hole static temp. (BHST).....	27	°C
Est. bottom hole circulating temp. (BHCT)....	27	°C
Est. formation integrity.....	-	bar/m

	FILLER/LEAD SLURRY	TAIL IN SLURRY
CEMENT SLURRY COMPOSITION	CLASS + 3.2 l/100 kg Econolite	CLASS + 1 kg/100 kg CaCl ₂
Mix water 1/100 kg	93 <u>sea</u>	44 <u>sea</u>
Total liquid 1/100 kg	96.2	44.6
Slurry weight g/cm ³	1.56	1.91
Slurry yield 1/100 kg	128	76
<u>TEST DATA @ BHCT</u>		
Thickening time @ BHHP, hr:min	5:00	4:00
Crit. Turb. Flow rate: m/s (l/min)		
Fluid loss, ml/30 min, 70 bar		
<u>TEST DATA @ BHST, BHHP</u>		
Compr. strength, bar 12hr	-13.6	102.0
bar 24hr	37.4	125.8
<u>REMARKS:</u>		

Volume calculations: (30" casing)

Annular volume:	$0.200 \text{ m}^3/\text{m} \cdot 54 \text{ m}$	=	10.6 m^3
3 m plug at shoe:	$0.397 \text{ m}^3/\text{m} \cdot 3 \text{ m}$	=	1.3 m^3
			<hr/>
Total	:		11.8 m^3
Volume + 150% excess in open hole:			27.7 m^3
			<hr/>

USE:

Lead: Class G cement + 3.2 l/100 kg Econolite
14000 kg (328 sacks) cement
equal to 17.92 m^3 slurry.

Tail in: Class G cement + 1 kg/100 kg CaCl_2
12800 kg (300 sacks) cement
equal to 9.73 m^3 slurry

Job preparation:

Total liquid lead slurry: 14000 kg cmt (93+3.2)l/100 kg
= 13468 liter (= 13.47 m^3 or 85 bbls)

Volume of Econolite needed in each 10 bbls (1.59 m^3)

displacement tank: 1590 liter $\frac{3.2}{93} + 3.2$ = 53 liter

Total volume Econolite: 53 liter $\cdot \frac{85}{10}$ = 450 liter

Total liquid tail in: 12800 kg cmt. • 44.6 l/100 kg = 5709 liter
(= 5.71 m^3 or 36 bbls)

Amount of CaCl_2 needed = 12800 kg • 1 kg/100 kg = 128 kg

CASING CEMENT DATA AND CALCULATIONS,

20 " CASING.

GENERAL: The cement volume is calculated on the basis of the theoretical annulus volume, and the casing to be cemented to the sea bed with 100% excess on the open hole volume.

WELL DATA:

Depth kb-sea bed.....	197	m
Depth kb-last shoe.....	250	m
Depth kb-casing set point.....	550	m
Open hole dia.....	26	"
Annulus capacity, cased hole.....	195	l/m
Annulus capacity, open hole.....	140	l/m
Internal capacity, 20 " casing.....	178	l/m
Mud weight.....	1.1	g/cm ³
Bottom hole hydrostatic pres. (BHHP).....	59	bar
Est. bottom hole static temp. (BHST).....	96	°C
Est. bottom hole circulating temp. (BHCT)....	31	°C
Est. formation integrity.....	0.149	bar/m

	FILLER/LEAD SLURRY	TAIL IN SLURRY
CEMENT SLURRY COMPOSITION	CLASS G +3.2 l/100 kg Econolite	CLASS G neat
Mix water 1/100 kg	93 <u>sea</u>	44 <u>sea</u>
Total liquid 1/100 kg	96.2	44
Slurry weight g/cm ³	1.56	1.92
Slurry yield 1/100 kg	128	76
TEST DATA @ BHCT		
Thickening time @ BHHP, hr:min	4:00	4:00
Crit. Turb. Flow rate: m/s. (l/min)		
Fluid loss, ml/30 min, 70 bar		
TEST DATA @ BHST, BHHP		
Compr. strength, bar 12 hr @ 27°C	-	
bar 24 hr @ 27°C	37.4	163.3
REMARKS: 12 hr @ 36°C		146.3
24 hr @ 36°C		243.2

Volume calculations: (20" casing)

Annular volume: $0.140 \text{ m}^3/\text{m} \cdot (550 - 250) \text{ m}$	=	42.00 m^3
Volume between the casings: $0.195 \text{ m}^3/\text{m} \cdot (250-197)\text{m}$	=	10.34 m^3
10 m plug at shoe: $0.187 \text{ m}^3/\text{m} \cdot 10 \text{ m}$	=	<u>1.78 m^3</u>
Total theoretical volume:		54.12 m^3
100% excess in open hole:		<u>42.00 m^3</u>
Total cement slurry volume:		<u>96.12 m^3</u>

USE:

Lead slurry: Class G cement + 3.2 l/100 kg Econolite
67400 kg (1580 sacks) cement
equal to 86.27 m^3 slurry.

Tail in slurry: Class G cement neat with seawater
13000 kg (305 sacks) cement
equal to 9.88 m^3 slurry

Job preparation:

Total liquid lead slurry: $67400 \text{ kg} \cdot 96.2 \text{ l}/100 \text{ kg} =$
64840 liter (= 64.84 m^3 or 408 bbls)

Volume of Econolite needed in each 10 bbls

displacement tank: $1590 \text{ liter} \frac{3.2}{96.2} =$ 53 liter

Total volume of Econolite needed: $53 \text{ liter} \frac{408}{10} =$ 2160 liter

Total liquid tail in slurry: $13000 \text{ kg} \cdot 44 \text{ l}/100 \text{ kg} =$
5720 liter (= 5.72 m^3 or 36 bbls)

Time estimate for cement job:

Mix cement: $92.12 \text{ m}^3 / 0.8 \text{ m}^3/\text{m}$ = 120 min

Displacement: $54 \text{ m}^3 / 1.0 \text{ m}^3/\text{min}$ = 45 min

Total pumping time: = 174 min

Hydrostatic pressure at the casing shoe (550 m):

Height of tail in slurry: $(9.88 - 1.78) \text{ m}^3 / 0.140 \text{ m}^3/\text{m}$ = 58 m

Hydrostatic head lead slurry: $0.153 \text{ bar/m} (550-197-58) \text{ m}$ = 45.1 bar

Hydrostatic head tail in slurry: $0.188 \text{ bar/m} 58 \text{ m}$ = 10.9 bar

Hydrostatic head seawater: $0.100 \text{ bar/m} (197-25) \text{ m}$ = 17.2 bar

Total hydrostatic pressure: = 73.2 bar

Equivalent gradient: $73.2 \text{ bar} / 550 \text{ m}$ = 0.133 bar/m

Estimated formation integrity: 0.149 bar/m

CASING CEMENT DATA AND CALCULATIONS, 13 3/8" CASING.

GENERAL: The cement volume is calculated on the basis of the theoretical annulus volume, and the casing to be cemented 100 m into the 20" casing with 25% excess on open hole volume.

WELL DATA:

Depth kb-sea bed.....: 197 m
 Depth kb-last shoe.....: 550 m
 Depth kb-casing set point.....: 1470 m
 Open hole dia.....: 17½ "

Annulus capacity, cased hole.....: 94.7 l/m
 Annulus capacity, open hole.....: 64.5 l/m
 Internal capacity 13 3/8" casing .72 lb/ft.....: 77.3 l/m

Mud weight.....: 1.4 g/cm³
 Bottom hole hydrostatic pres. (BHHP).....: 202 bar
 Est. bottom hole static temp. (BHST).....: 51 °C
 Est. bottom hole circulating temp. (BHCT).....: 40 °C
 Est. formation integrity.....: 0.181 bar/m

	FILLER/LEAD SLURRY	TAIL IN SLURRY
CEMENT SLURRY COMPOSITION	CLASS G + 3.2 l/100 kg Econolite	CLASS G neat
Mix water 1/100 kg	89 <u>fresh</u>	44 <u>fresh</u>
Total liquid 1/100 kg	92.2	44
Slurry weight g/cm ³	1.56	1.90
Slurry yield 1/100 kg	124	76
<u>TEST DATA @ BHCT</u>		
Thickening time @ BHHP, hr:min	5:00 ⁺	3:00
Crit. Turb. Flow rate: m/s (l/min)		
Fluid loss, ml/30 min, 70 bar		
<u>TEST DATA @ BHST, BHHP</u>		
Compr. strength, bar 12 hr @ 27°C	-	
bar 24 hr @ 27°C		
<u>REMARKS:</u> bar 12 hr @ 51°C	not set	113.9
bar 24 hr @ 51°C	28	170.1

Hydrostatic pressure at the casing shoe (1470 m):

Height of tail in slurry: $(9.88 - 1.86)m^3 / 0.0645 m^3/m = \underline{124 m}$

Maximum height lead cement:

Volume to 20" shoe: $0.0645 m^3/m \cdot (1470-124-550) m = 51.3 m^3$

Volume above 20" shoe: $75.65 m^3 - 51.3 m^3 = 24.35 m^3$

Height above 20" shoe: $24.35 m^3 / 0.0947 m^3/m = \underline{257 m}$

Maximum height lead cement: $(1470-550-124+257)m = \underline{1053 m}$

Hydrostatic head lead slurry: $153 \text{ bar/m} \cdot 1053 m = 161.1 \text{ bar}$

Hydrostatic head tail in slurry: $0.186 \text{ bar/m} \cdot 124 m = 23.1 \text{ bar}$

Hydrostatic head mud: $0.137 \text{ bar/m} \cdot 293 m = \underline{40.1 \text{ bar}}$

Total hydrostatic pressure = 224.3 bar

Equivalent gradient: $224.3 \text{ bar} / 1470 m = \underline{0.153 \text{ bar/m}}$

Estimated formation integrity: = 0.181 bar/m

CASING CEMENT DATA AND CALCULATIONS,

" CASING.

GENERAL: The cement volume is calculated on the basis of the theoretical annulus volume and the casing to be cemented 100 m into the 13 3/8" casing with 25% excess on open hole volume.

WELL DATA:

Depth kb-sea bed.....: 197 m
 Depth kb-last shoe.....: 1470 m
 Depth kb-casing set point.....: 1805 m
 Open hole dia.....: 12 1/4 "

Annulus capacity, cased hole.....: 30.3 l/m
 Annulus capacity, open hole.....: 29.1 l/m
 Internal capacity, 9 5/8" casing .43.5 and .47 lb/ft 38.8/38.2 l/m

Mud weight.....: 1.75 g/cm³
 Bottom hole hydrostatic pres. (BHHP).....: 310 bar
 Est. bottom hole static temp. (BHST).....: 69 °C
 Est. bottom hole circulating temp. (BHCT)....: 46 °C
 Est. formation integrity.....: 0.193 bar/m

	FILLER/LEAD SLURRY	TAIL IN SLURRY
CEMENT SLURRY COMPOSITION	CLASS	CLASS G + 3.54 l/100kg Fh-1 + 2.57 l/100kg CFR-2L + 0.13 l/100kg HR-GL
Mix water 1/100 kg		38.7 <u>fresh</u>
Total liquid 1/100 kg		44.9
Slurry weight g/cm ³		1.90
Slurry yield 1/100 kg		76
<u>TEST DATA @ BHCT</u>		
Thickening time @ BHHP, hr:min		4:29
Crit. Turb. Flow rate: m/s (l/min)		175
Fluid loss, ml/30 min, 70 bar		
<u>TEST DATA @ BHST, BHHP</u>		
Compr. strength, bar 12 hr		161.6
bar 24 hr		226.2
<u>REMARKS:</u>		

Volume calculations: (9 5/8" casing)

Annular volume (12 1/4-9 5/8"):	$0.0291 \text{ m}^3/\text{m} \cdot (1805-1470)\text{m}$	=	9.75 m^3
Volume between casings	$: 0.0303 \text{ m}^3/\text{m} \cdot 100 \text{ m}$	=	3.03 "
24 m plug at shoe	$: 0.0388 \text{ m}^3/\text{m} \cdot 24 \text{ m}$	=	0.93 "
Total theoretical volume	:	=	13.71 m^3
25% excess in open hole	$: 9.75 \text{ m}^3 \cdot 0.25$	=	2.44 "
Total slurry volume	:	=	16.15 m^3

USE:

Class G cement +
21250 kg (500 sacks) cement
equal to 16.15 m^3 slurry

Job preparation:

Total liquid needed; $21250 \text{ kg} \cdot 44.9 \text{ l}/100 \text{ kg}$ = 9541 ltr.
(= 9.54 m^3 or 60 bbls)

Volume of FL-1 needed in each
10 bbls displacement tank $1590 \text{ ltr} \cdot \frac{3.54}{44.9}$ = 125 ltr.

Volume of CFR-2L needed in each
10 bbls displacement tank: $1590 \text{ ltr} \cdot \frac{2.57}{44.9}$ = 91 ltr.

Volume of HR-6L needed in each tank: $1590 \text{ ltr} \cdot \frac{6.13}{44.9}$ = 4.6 ltr

Total volume of HR-6L: $4.6 \text{ liter} \cdot \frac{60}{10}$ = 28 liter

Total volume of FL-1 needed: $125 \text{ liter} \cdot \frac{60}{10}$ = 750 liter

Total volume of CFR-2L needed: $91 \text{ liter} \cdot \frac{60}{10}$ = 546 liter

20 bbls spacer to used at 1.82 kg/liter.

Time estimate for the job:

Mixing cement: $16.15 \text{ m}^3 / 0.8 \text{ m}^3/\text{min.}$ = 20 min
Displacement: $71 \text{ m}^3 / 1.0 \text{ m}^3/\text{min}$ = 71 min
Total pumping time: = 91 min
or 1 hour 31 min

Volume calculations:

Annular volume (17½"-13 3/8"): 0.0645 m ³ /m (1470-550)m	=	53.34 m ³
Volume between the casings: 0.0947 m ³ /m · 100 m	=	9.47 m ³
24 m plug at shoe: 0.0773 m ³ /m · 24 m	=	<u>1.86 m³</u>
Total theoretical volume:	=	70.67 m ³
25% excess in open hole: 59.34 m ³ · 0.25	=	<u>14.84 "</u>
Total slurry volume:	=	<u>85.51 m³</u>

USE:

Lead slurry: Class G cement + 3.2 l/100 kg Econolite
61000 kg (1430 sacks) cement
equal to 75.64 m³ slurry

Tail in slurry: Class G cement neat with fresh water
13000 kg (305 sacks) cement
equal to 9.88 m³ slurry

Job preparation:

Total liquid lead slurry: 61000 kg · 92.2 l/100 kg = 56242 ltr.
(= 5.62 m³ or 354 bbls)

Volume of Econolite needed in each 10 bbls

displacement tanks: 1590 liter · $\frac{3.2}{92.2}$ = 55.2 liter

Total volume of Econolite needed: 55.2 liter · $\frac{354}{10}$ = 1954 liter

Total liquid tail in slurry: 13000 kg · 44 l/100 kg = 5720 liter
(= 5.72 m³ or 36 bbls)

Time estimate for the job:

Mixing cement: 85.51 m³/0.8 m³/min = 107 min

Displacement: 101 m³/1.0 m³/min = 101 min

Total pumping time: = 208 min

or 2 hours 28 min.

Hydrostatic pressure at the casing shoe (1805 m):

Cement volume in annulus 13 3/8" - 9 5/8"	: $16.15\text{m}^3 - 10.68\text{m}^3$	= 5.47m^3
Height of cement in annulus 13 3/8"-9 5/8"	: $5.47\text{m}^3 / 0.0303\text{m}^3\text{m}$	= <u>181m</u>
Hydrostatic head cement slurry	: $0.186\text{ bar/m} \cdot 516\text{m}$	= 96.0 bar
Hydrostatic head mud	: $0.172\text{ bar/m} \cdot 1289\text{ m}$	= <u>221.7bar</u>
Total hydrostatic pressure	:	= <u>317.7bar</u>
Equivalent gradient	: 318 bar/1805 m	= <u>0.176bar/m</u>
Estimated formation integrity	:	= <u>0.193bar/m</u>