SIMON PETROLEUM TECHNOLOGY
WELL: 16/1-3
Print: 2630 N Units: (M) F Top 195 Bottom 3500 Scale 1/500 TD 3498
Length: 26 FT Initials: JPK
DIGITAL WIRELINE LOGS PACKAGE
1994
This image may not be used or reproduced without written permission from
SIMON PETROLEUM TECHNOLOGY

COMPLETION LOG

Esso Exploration and Production Norway Inc.

COMPLETION LOG

LICENCE: 001 ROUND: 1

Esso

16/1-3

11 APR 1984

REGISTRERT
OLJEDIREKTORATET

BLOCK MAP

LOCATION COORDINATES	
LATITUDE	58°48'48.90" N
LONGITUDE	02°02'56.45" W
RIG	GLOMAR BISCAY 11
KB ELEVATION	25m AMSL
WATER DEPTH	108m BMSL
TOTAL DEPTH	3498m BKB
	3473 SS
FORMATION AT TOTAL DEPTH	GRANITE BASEMENT

OPERATOR	ESSO
ARRIVED ON LOCN	28/07/82
SPUD DATE	29/07/82
REACH T.D.	09/09/82
RIG RELEASE	28/09/82
WELL STATUS	PLUGGED AND ABANDONED - NO TESTS.
MUDLOGGING BY	GEARHART GEODATA SERVICES LTD
PREPARED BY	CHESSEL/ZEEBREGTS
DATE	

CASING

30"	196mKB
20"	506mKB
13 3/8"	1263mKB
9 5/8"	2727mKB
7"	
4 1/2"	

LOG	RUN NO.	DATE	INTERVAL (mKB)	BIT SIZE	MAX BHT (°F)	TIME SINCE CIRC / CIRC DURATION	MUD TYPE	MUD RESISTIVITY (Ω·M)/TEMP (°F) SURFACE	MUD RESISTIVITY BHT	MUD FILTRATE RESISTIVITY (Ω·M)/TEMP (°F)
IEL/AC/GR 4ARM CALIP.	1-A 2-A	1/8-82 3/8-82	195-520 170-521	12 26	L 100 -	3/1	Sw-GEL "	0.339/70 -	- -	0.296/73
IEL/AC/GR 4 ARM CALIP.	3B 3B	10/8-82 10/8-82	506-1277 506-1201	17 17	110 110	4.5 1.25	Sw-GEL "	0.424/61 -	0.235/110°F -	0.358/64 -
TEMP/CCL IEL/AC/GR	4A 5C	12/8-82 29/8-82	10-1237 1242-2735	13 12	- 154°	4.5 1.75	" Sw-GEL	- 0.355/86	- 0.205/154	- 0.258/74
CN/CDL/GR DLL/MLL/GR	5A 5A	29/8-82 29/8-82	1242-2737 2250-2732.5	12 12	170 179		" "	0.355/86 0.355/86	0.186/170 0.178/179	0.258/74 0.258/74
MFT SWC'S	5A 5A	30/8-82 30/8-82	1850-2750 1762-2729.8	12 12	150 -	- -	" "	- -	- -	- -
TEMP.-CCL IEL/AC/GR	6B 7-D	2/9-82 14/9-82	1235-2200 2724.5-3095.7	9 8	- 182	- 9/1.5	Sw-GEL "	- 0.436/64	- 0.164/182	- 0.255/66
CDL/CN/GR MFT'S	7B 7B	14/9-82 14/9-82	2724.5-3097.5 2741.5-3073.3	8 8	199 -	5/1.5 18/1.5	" "	0.436/66 -	0.155/199 -	0.255/66 -
SWC'S SRC	7B 7A	15/9-82 15/9-82	2733-3095	8 8	- -	- -	" "	- -	- -	- -
IEL/AC/GR	8E	19/9-82	2724-3269	8	206	12/1	Sw-GEL	0.379/62	0.126/206	0.252/66
CNL/CDR/GR	8C	19/9-82	3050-3271	8	206	10/1	Sw-GEL	0.379/62	0.126/206	0.252/66
IEL/AC/GR	8-F	19/9-82	MISRUN	8	206	"	"	0.379/62	0.126/206	0.252/66
DIP LOG DIP LOG	8A 8-B	19/9-82	MISRUN 2725-3270	8	212	-	Sw-GEL	-	-	-
MFT'S MFT'S	8C 8D	" 20/9-82	2742-3194.5 2742.5	8 8	- -		" "	- -	- -	- -
SWC'S	8-C	"	3101-3266	8	-	-	"	-	-	-
IEL/AC/GR	9-F	23/9-82	3200-3495	8	198	4.5/1	"	0.333/71	0.127/198	0.222/71
CNL/CD/GR	9-D	23/9-82	3050-3495	8	208	6.5/1	Sw-GEL	0.333/71	0.121/208	0.222/71

LITHOLOGY SYMBOLS

CONGLOMERATE · SAND,SANDSTONE · SILT,SILTSTONE · CLAY,CLAYSTONE · SHALE · LIGNITE/COAL, CARBONACEOUS, BITUMINOUS · TUFF · MACRO,MICRO FOSSILS · CHERT, GLAUCONITE, PYRITE, MICA · LIMESTONE CALCAREOUS · DOLOMITE DOLOMITIC · CHALK · MARL · SALT · ANHYDRITE · IGNEOUS GRANITE

HYDROCARBON INDICATION: SHOW OR STAIN · CUT · FLOURESCENCE · GAS SHOW

CASING SHOE, LINER · 1° DEVIATION · N12°E DIRECTION · 2° DIPMETER · 2050M DEPTH MKB · (-2025M) DEPTH SUB SEALEVEL · 1984MS TWO WAY TIME FROM SEALEVEL (VELOCITY SURVEEY)

CORED INTERVAL · (NO RECOVERY) · SIDEWALL CORE RECOVERED · REC. W/SHOWS · PERFORATION INTERVAL · CEMENT PLUG INTERVAL

DST: THROUGH CASING · OPEN HOLE · RE-RUN · RFT/FIT

WELL SUMMARY

OBJECTIVE: PRIMARY OBJECTIVE WAS TO TEST THE HYDROCARBON POTENTIAL OF JURASSIC SAND RESERVOIRS IN THIS AREA. EOCENEAND PALEOCENE SANDS WERE CONSIDERED TO BE SECONDARY OBJECTIVES.

RESULTS: PLUG AND ABANDON WITH MINOR HYDROCARBON SHOWS IN PALEOCENE AND JURASSIC.

SERIES	STAGE	GROUP	FORMATION	SPONTANEOUS POTENTIAL / GAMMA RAY 0–100 API UNITS / 6 CALIPER INCHES 16	LITHOLOGY 1 : 500 MKB	RESISTIVITY (OHMS M²/M) 0.2 DEEP INDUCTION 20 / 20 RILD 2000 / 0.2 FOCUSED RESISTIVITY 20 / 20 RSFL 2000	INTERVAL TRANSIT TIME (MICROSECONDS PER FT) 100–0 / 200 BACKUP ΔT 100

MEAN SEA LEVEL @ 25m

SEA FLOOR @ 133m RKB (-108m)

Company	Drillers T.D.
Well	Log F.R.
Field	Log T.D.
County NORTH SEA	Elevations:
State	K.B. D.F. G.L.