

WELL 2/4-2X COMPLETION STRING
 OCEAN VIKING JUNE 9, 1974

7g
well completion record

DESCRIPTION (TOP TO BOTTOM)	LENGTH (FEET)	DEPTH TOP (RKB)
RKB - Tubing Hanger Seat	3 99.70	RKB
National 4 Port Tubing Hanger W/Seal Lock	3.56	299.70
Pup it X-Over 4½" S/L-Vam	2.90	303.26
1 Joint - 4½" 12.75 lb. N-80 Vam tbg.	38.56	306.16
Baker Flow Coupling, 4½" Vam	10.04	344.72
Baker 3.812 F Nipple Top No-Go	1.20	354.76
3-Pup its, 4½" 12.75 lb. N-80 Vam	31.48	355.96
3 Joints - 4½" 12.75 lb. N-80 Vam tbg.	113.18	387.44
Fluted Guide, W/ S/L to Vam x-overs	6.25	500.62
Baker Flow Coupling, 4½" Vam	10.03	506.87
Baker Safety Valve Nipple, for Model "E" Ball Type, Safety Valve	2.20	516.90
Baker Flow Coupling, 4½" VAM	4.10	519.10
Fluted Guide, with S/L to Vam x-overs	5.55	523.20
239 Joints - 4½" 12.75 lb. N-80 Vam tbg.	8964.88	528.75
1 - Pup Joint, 4½" 12.75 lb. N-80 Vam	5.70	9493.63
Baker Flow Coupling, 4½" Vam	10.06	9499.33
Baker Model L Sliding Sleeve, 3.688	3.68	9509.39
1 - Pup Joint, 4½" 12.75 lb. N-80 Vam	9.66	9513.07
Baker Flow Coupling, 4½" Vam	10.04	9522.73
Baker R Nipple, 3.688 Bottom No Go	1.30	9532.77
1 Joint - 4½" 12.75 lb. N-80 Vam tbg.	37.92	9534.07
1 - Pup Joint, 12.75 lb. N-80 Vam	3.75	9571.99
X-Over 4½" Vam Box - 3½ EV Pin	0.00 ²⁰	9575.74
Baker Model H Locator	0000 ²⁰	9576.44
Baker Seal Assembly, Size 190-47	18.60	9577.34
X-Over, 3½ EV Box - 3½ Vam Pin	0.40	9595.90
Flow Coupling, 3½ Vam	3.95	9596.34
Baker 2.75 F Nipple	0.85	9600.29 ⁹
1 Joint - 3½" 9.2 lb. N-80 Vam tbg.	29.53	9601.14
Mule Shoe	1.10	9630.67
Bottom of Tailpipe		9631.77

Baker 9 5/8" Model DB Packer set at 9579.32., RKB

String spaced out with locator sub 2.02' above the packer.

File: Well 2/4 - 2X