



## Generell informasjon

Brønnbane navn	9/4-1
Type	EXPLORATION
Formål	WILDCAT
Status	P&A
Faktakart i nytt vindu	<a href="#">lenke til kart</a>
Hovedområde	NORTH SEA
Brønn navn	9/4-1
Seismisk lokalisering	line 5735 & SP 2462 1/2
Utvinningstillatelse	<a href="#">013</a>
Boreoperatør	Conoco Norway Inc.
Boretillatelse	11-L
Boreinnretning	<a href="#">ENDEAVOUR</a>
Boredager	50
Borestart	31.03.1968
Boreslutt	19.05.1968
Frigitt dato	19.05.1970
Publiseringssdato	22.04.2005
Opprinnelig formål	WILDCAT
Gjenåpnet	NO
Innhold	SHOWS
Funnbrønnbane	NO
Avstand, boredekk - midlere havflate [m]	29.0
Vanndybde ved midlere havflate [m]	68.0
Totalt målt dybde (MD) [m RKB]	2963.0
Maks inklinasjon [°]	5.25
Temperatur ved bunn av brønnbanen [°C]	75
Eldste penetrerte alder	LATE PERMIAN
Eldste penetrerte formasjon	ZECHSTEIN GP
Geodetisk datum	ED50
NS grader	57° 35' 2" N
ØV grader	4° 1' 13" E
NS UTM [m]	6382987.51
ØV UTM [m]	561007.44
UTM sone	31
NPID for brønnbanen	150



## Brønnhistorie

### General

Well 9/4-1 is situated northeast in the Åsta Graben in the Danish-Norwegian Basin. The chosen well location allowed multiple Tertiary to Mesozoic prospects to be tested. The primary objectives of 9/4-1 were Middle Jurassic and Early Triassic (Bunter) sandstones, while basal Tertiary and Early Cretaceous sandstones and Late Cretaceous limestones were secondary objectives.

The well is Type Well for the Egersund Formation.

### Operations and results

Wildcat well 9/4-1 was spudded with the jack-up installation Endeavour on 31 Marc 1968 and drilled to TD at 2963 m in Late Permian Zechstein salt. Three casing strings were set in the hole. Seawater was used as drilling fluid down to 1106 m, from where an XP-20 lignosulphonate type mud was used. When the drilling commenced after the 30" conductor pipe was set, several drilling problems arose. The circulation was lost, and the hole fell in repeatedly, so the conductor pipe had to be re-driven and cemented several times until the hole conditions allowed the 20" casing to be set. At 2963 m the drill pipe stuck in salt, and after five days of unsuccessful fishing operations, it was decided to abandon the hole. The lower part of the hole could not be logged due to the unrecovered fish.

Twenty-five net meter of Jurassic sandstone was penetrated in a sand body (Sandnes Formation) at 2288 m. The section was water wet, but fair shows were logged in the upper 5 m of the sand. The remainder had very scattered poor shows. Porosity averaged 25 percent and examination of sidewall cores indicated a clean permeable sandstone reservoir. The second primary objective, the Bunter Sandstone, was represented by an estimated 60 m of thin interbedded sands and sandstones scattered throughout a thick Triassic section composed predominantly of silty red brown to pastel claystones. Due to lack of logs the interpretation of the Triassic section is somewhat tentative. Late Cretaceous Chalk and Early Cretaceous sandstones proved non-productive due to either the absence of the predicted lithologies or the non-development of reservoir properties in the sediments present. There were no shows in the Triassic or in the secondary target sections. Organic geochemical analyses show excellent source properties in the Late Jurassic Tau Formation with 6 - 7 % TOC and hydrogen index around 250 mg HC/g TOC. Colas and shale in the underlying Vestland and Bryne Formations also show good source potentials. Vitrinite data indicate top oil window maturity already at ca 2000 m.

No conventional cores were cut. Sixty-nine out of 73 attempted sidewall cores were retrieved over the interval 2196 m to 2415 m in the Jurassic and Triassic sections. No fluid samples were taken.

The well was permanently abandoned on 19 May 1968 as a dry hole with shows.

### Testing

No drill stem test was performed.

## Litosstratigrafi



Topp Dyb [mMD RKB]	Litostrat. enhet
97	<a href="#">NORDLAND GP</a>
518	<a href="#">HORDALAND GP</a>
1127	<a href="#">ROGALAND GP</a>
1127	<a href="#">BALDER FM</a>
1154	<a href="#">SELE FM</a>
1174	<a href="#">FISKEBANK FM</a>
1230	<a href="#">LISTA FM</a>
1269	<a href="#">VÅLE FM</a>
1336	<a href="#">SHETLAND GP</a>
1336	<a href="#">EKOFISK FM</a>
1365	<a href="#">TOR FM</a>
1690	<a href="#">HOD FM</a>
1804	<a href="#">BLODØKS FM</a>
1811	<a href="#">CROMER KNOLL GP</a>
1811	<a href="#">RØDBY FM</a>
1822	<a href="#">SOLA FM</a>
1847	<a href="#">ÅSGARD FM</a>
1985	<a href="#">BOKNFJORD GP</a>
1985	<a href="#">FLEKKEFJORD FM</a>
2047	<a href="#">SAUDA FM</a>
2200	<a href="#">TAU FM</a>
2251	<a href="#">EGERSUND FM</a>
2288	<a href="#">VESTLAND GP</a>
2288	<a href="#">SANDNES FM</a>
2319	<a href="#">BRYNE FM</a>
2329	<a href="#">NO GROUP DEFINED</a>
2329	<a href="#">SKAGERRAK FM</a>
2590	<a href="#">SMITH BANK FM</a>
2939	<a href="#">ZECHSTEIN GP</a>

### Spleisede logger

Dokument navn	Dokument format	Dokument størrelse [KB]
<a href="#">150</a>	pdf	0.24





## Geokjemisk informasjon

Dokument navn	Dokument format	Dokument størrelse [KB]
<a href="#">150_1</a>	pdf	0.49
<a href="#">150_2</a>	pdf	0.94
<a href="#">150_3</a>	pdf	0.77

## Dokumenter - eldre Sokkeldirektoratets WDSS rapporter og andre relaterte dokumenter

Dokument navn	Dokument format	Dokument størrelse [KB]
<a href="#">150_01_WDSS_General_Information</a>	pdf	0.20

## Dokumenter - rapportert av utvinningstillatelsen (frigitt ihht til regelverk)

Dokument navn	Dokument format	Dokument størrelse [KB]
<a href="#">150_01_Final_Geological_Report</a>	pdf	0.80
<a href="#">150_02_Composite_well_log</a>	pdf	1.55

## Dokumenter - Sokkeldirektoratets publikasjoner

Dokument navn	Dokument format	Dokument størrelse [KB]
<a href="#">150_01_NPD_Paper_No.24_Lithology_Well_9_4_1</a>	pdf	13.95

## Logger

Type logg	Topp dyp for logg [m]	Bunn dyp for logg [m]
BHC GR	333	1006
BHC GR	975	2416
FDC	1092	2419
GR	300	333
IES	333	1106
IES	1092	2419





### Foringsrør og formasjonsstyrketester

Type utforing	Utforing diam. [tommer]	Utforing dybde [m]	Brønnbane diam. [tommer]	Brønnbane dyp [m]	LOT/FIT slam eqv. [g/cm3]	Type formasjonstest
CONDUCTOR	36	144.0	48	146.0	0.00	LOT
SURF.COND.	20	334.0	26	335.0	0.00	LOT
INTERM.	13 3/8	1092.0	17 1/2	1094.0	0.00	LOT
OPEN HOLE		2963.0	12 1/4	2963.0	0.00	LOT

### Boreslam

Dybde MD [m]	Egenvekt, slam [g/cm3]	Viskositet, slam [mPa.s]	Flytegrense [Pa]	Type slam	Dato, måling
1106	1.02			seawater	
2252	1.23			Spersene XP	
2963	1.25			Spersene XP	