



## Generell informasjon

Brønnbane navn	2/7-26 S
Type	EXPLORATION
Formål	APPRAISAL
Status	RE-CLASS TO DEV
Faktakart i nytt vindu	<a href="#">lenke til kart</a>
Hovedområde	NORTH SEA
Felt	<a href="#">EMBLA</a>
Funn	<a href="#">2/7-20 Embla</a>
Brønn navn	2/7-26
Seismisk lokalisering	PC-88 LINE 369 & COLUMN 1061
Utvinningstillatelse	<a href="#">018</a>
Boreoperatør	Phillips Petroleum Company Norway
Boretillatelse	674-L
Boreinnretning	<a href="#">WEST DELTA</a>
Boredager	178
Borestart	20.03.1991
Boreslutt	13.09.1991
Frigitt dato	13.09.1993
Publiseringsdato	26.05.2009
Opprinnelig formål	APPRAISAL
Reklassifisert til brønnbane	<a href="#">2/7-D-26</a>
Gjenåpnet	NO
Innhold	OIL
Funnbrønnbane	NO
1. nivå med hydrokarboner, alder	DEVONIAN
1. nivå med hydrokarboner, formasjon.	NO GROUP DEFINED
Avstand, boredekk - midlere havflate [m]	29.0
Vanndybde ved midlere havflate [m]	70.8
Totalt målt dybde (MD) [m RKB]	4848.0
Totalt vertikalt dybde (TVD) [m RKB]	4697.0
Maks inklinasjon [°]	24
Temperatur ved bunn av brønnbanen [°C]	167
Eldste penetrerte alder	DEVONIAN
Eldste penetrerte formasjon	NO GROUP DEFINED
Geodetisk datum	ED50



NS grader	56° 19' 59.59" N
ØV grader	3° 14' 53.55" E
NS UTM [m]	6243333.20
ØV UTM [m]	515347.49
UTM sone	31
NPDID for brønnbanen	1756

## Brønnhistorie

### General

Well 2/7 26 S is located on the Embla Field in the Central Graben of the North Sea. It was designed to test the pre-Jurassic sandstones, which had shown commercial quantities of hydrocarbons in the 2/7-20, 2/7-21 S, and 2/7-23 S wells. The objective of the well was to confirm the presence of hydrocarbon bearing sandstones in the western fault block of the structure and to establish the productivity of this reservoir section through a program of well testing and coring. Well location and TD was chosen so that both the upper and lower sandstone members of the pre-Jurassic sequence would be penetrated. The target location was 300 m to the south of the 2/7-9 well at Base Cretaceous level. The reservoir section was expected to be highly fractured and over-pressured. Shallow gas was expected since gas had been encountered in all wells drilled from the template location over the 2/7-20 well.

### Operations and results

Appraisal well 2/7 26 S was spudded with the semi-submersible installation West Delta on 20 March 1991 and drilled to TD at 4848 in Devonian rocks. The well was drilled deviated from a template located over the 2/7-20 well to penetrate the target reservoir section in the western fault block of the Embla structure. Minor shallow gas was detected in sandy zones with an increase in background gas from 4 to 64 units. Apart from some failures when logging and some stuck pipe experiences, drilling proceeded without significant problems. The well was drilled with seawater and hi-vis sweeps down to 575 m, with KCl/PAC mud from 575 m to 4125.5 m, and with Enviromul oil based mud from 4125.5 m to TD.

The 9 5/8" casing was set in claystones of the Lower Cretaceous, Rødby Formation. The remaining Lower Cretaceous section including Sola, Tuxen and Åsgård Formations was penetrated, followed by a Late Jurassic sequence consisting of 3 m Mandal Formation and 82 m Farsund Formation. The top of the reservoir sands were encountered at 4386 m (4226 m TVD), 58 m higher than prognosed. As in the other Embla wells the reservoir was undefined, Pre-Jurassic stratigraphy. Both the upper and the lower sandstone units were present in the well as predicted. The reservoir was oil bearing. No definite OWC was defined, however RFT pressure data, logs and DST results indicated oil-filled porous sandstones from top reservoir and down to at least 4606 m (4465 m TVD).

The cuttings in the intervals between 1520 - 1680 m and 1730 - 1830 m (Base Nordland Group / upper Hordaland Group) showed 30-100% pale to bright yellow fluorescence accompanied by oil in the mud. The cut was blooming to streaming yellow, and the odour was good to strong. Good to excellent oil shows were seen in the interval 3111.4 m to 3973 m with 35% fluorescence in marls/limestones from 3111.4 m and rapidly increasing to 70% by 3018.1 m. Shows up to 80%, with bright yellow fluorescence and yellow fast streaming cut, were seen from 3124.2 to 3230.9 m. Shows were also seen at 3550.9 m, 5% -10% with dull yellow fluorescence and hazy crushed cut. From 3627.1 to 3834.4 m shows of 20% to 80% with a dull fluorescence were seen. The cut was pale blue yellow and slightly streaming. Shows further down in the well, including the pre-



Jurassic reservoir section were weak and most likely caused by the oil-based mud.

A total of 18 cores were cut in the well. The first was cut at 3200.4 - 3214.3 m in the Tor Formation. The second core was cut through the Mandal Formation and into the upper part of the Farsund Formation. A total of 16 cores were cut in the reservoir interval including a core in the rhyolitic rocks at TD. A total of 90 sidewall cores were attempted and 28 sidewall cores were recovered. No wire line fluid samples were taken.

The well was suspended on 13 September 1991 as an oil appraisal well and reclassified to development well 2/7-D-26

#### **Testing**

Two DST tests were performed in this well.

DST 1 was conducted over the interval 4605.5 - 4696.9 m (4465.0 - 4552.2 m TVD). It flowed in the range of 48 Sm3 (300 STB) /day, with signs of unstable flow, at pressures less than 1000 psi.

DST 2 was conducted over a gross interval from 4309.8 - 4538.4 (4184 - 4401 m TVD). The well was tested on a 16/64" choke with flowing rates of 223 Sm3 oil and 61447 Sm3 gas/day. The GOR was 275 Sm3/Sm3, the oil density was 0.81 g/cm<sup>3</sup> (43 deg API), and the gas gravity (air = 1) was 0.81 with 6% CO<sub>2</sub> and 20 ppm H<sub>2</sub>S. A stable down-hole temperature of 160 deg C was measured in the test.

#### **Borekaks i Sokkeldirektoratet**

Borekaksprøve, topp dybde [m]	Borekaksprøve, bunn dybde [m]
579.00	4547.60

Borekaks tilgjengelig for prøvetaking?	YES
--	-----

#### **Borekjerner i Sokkeldirektoratet**

Kjerneprøve nummer	Kerneprøve - topp dybde	Kerneprøve - bunn dybde	Kerneprøve dybde - enhet
1	10500.0	10545.5	[ft ]
2	14103.0	14153.9	[ft ]
3	14417.0	14453.1	[ft ]
4	14457.0	14480.8	[ft ]
5	14481.0	14545.8	[ft ]
6	14558.0	14581.6	[ft ]
7	14586.0	14592.1	[ft ]
8	14598.0	14635.6	[ft ]
9	14636.0	14658.0	[ft ]
10	14660.0	14693.6	[ft ]
11	14696.0	14743.8	[ft ]



## Faktasider

### Brønnbane / Leting

Utskriftstidspunkt: 15.5.2024 - 05:07

12	14746.0	14807.2	[ft ]
13	14807.0	14848.0	[ft ]
14	14854.0	14903.6	[ft ]
15	14903.0	14935.6	[ft ]
16	15312.0	15403.6	[ft ]
17	15404.0	15495.1	[ft ]
18	15844.0	15907.7	[ft ]

Total kjerneprøve lengde [m]	250.7
Kjerner tilgjengelig for prøvetaking?	YES

### Kjernebilder



5480-5487ft



10500-10510ft



10510-10522ft



10522-10534ft



10534-10545ft



14103-14118ft



14118-14133ft



14133-14148ft



14148-14153ft



14417-14432ft



14432-14447ft



14447-14453ft



14457-14472ft



14472-14480ft



14481-14496ft



14496-14511ft



14511-14526ft



14526-14541ft



14541-14545ft



14558-14573ft




14573-14581ft 14586-14592ft 14598-14613ft 14613-14628ft 14628-14635ft



14636-14651ft 14651-14658ft 14660-14675ft 14675-14690ft 14790-14693ft



14696-14711ft 14711-14726ft 14726-14741ft 14741-14743ft 14746-14761ft



14761-14776ft 14776-14791ft 14791-14806ft 14806-14807ft 14807-14822ft



14822-14837ft 14854-14869ft 14869-14884ft 14884-14899ft 14899-14903ft



14903-14918ft 14918-14933ft 14933-14935ft 15312-15327ft 15327-15342ft



## Faktasider

### Brønnbane / Leting

Utskriftstidspunkt: 15.5.2024 - 05:07



15342-15357ft 15357-15372ft 15372-15387ft 15387-15402ft 15402-15403ft



15404-15419ft 15419-15434ft 15434-15449ft 15449-15464ft 15464-15479ft



15479-15494ft 15494-15495ft 15844-15859ft 15859-15874ft 15874-15889ft



15889-15904ft 15904-15907ft

## Oljeprøver i Sokkeldirektoratet

Test type	Flaske nummer	Topp dyp MD [m]	Bunn dyp MD [m]	Væske type	Test tidspunkt	Prøver tilgjengelig
DST	DST 1	4605.50	4696.90		24.08.1991 - 00:00	YES
DST	DST 2	4309.80	4538.40		03.09.1991 - 00:00	YES

## Litostratigrafi



Topp Dyb [mMD RKB]	Litostrat. enhet
100	<a href="#">NORDLAND GP</a>
1606	<a href="#">HORDALAND GP</a>
2966	<a href="#">ROGALAND GP</a>
2966	<a href="#">BALDER FM</a>
2983	<a href="#">SELE FM</a>
3038	<a href="#">LISTA FM</a>
3091	<a href="#">VÅLE FM</a>
3118	<a href="#">SHETLAND GP</a>
3118	<a href="#">EKOFISK FM</a>
3200	<a href="#">TOR FM</a>
3321	<a href="#">HOD FM</a>
3981	<a href="#">BLODØKS FM</a>
3989	<a href="#">HIDRA FM</a>
4057	<a href="#">CROMER KNOLL GP</a>
4057	<a href="#">RØDBY FM</a>
4163	<a href="#">TUXEN FM</a>
4182	<a href="#">ÅSGARD FM</a>
4299	<a href="#">TYNE GP</a>
4299	<a href="#">MANDAL FM</a>
4302	<a href="#">FARSUND FM</a>
4386	<a href="#">NO GROUP DEFINED</a>

#### Dokumenter - eldre Sokkeldirektoratets WDSS rapporter og andre relaterte dokumenter

Dokument navn	Dokument format	Dokument størrelse [KB]
<a href="#">1756_01_WDSS_General_Information</a>	pdf	0.58
<a href="#">1756_02_WDSS_completion_log</a>	pdf	0.25

#### Dokumenter - rapportert av utvinningstillatelsen (frigitt ihht til regelverk)

Dokument navn	Dokument format	Dokument størrelse [KB]
<a href="#">1756_2_7_26_S_COMPLETION_LOG</a>	pdf	2.75
<a href="#">1756_2_7_26_S_COMPLETION_REPORT_2</a>	pdf	38.80

#### Borestrengtester (DST)





**Faktasider**  
**Brønnbane / Leting**

Utskriftstidspunkt: 15.5.2024 - 05:07

Test nummer	Fra dybde MD [m]	Til dybde MD [m]	Reduksjonsven til størrelse [mm]
1.0	4606	4697	6.3
2.0	4310	4538	6.3

Test nummer	Endelig avstengningstrykk [MPa]	Endelig strømningstrykk [MPa]	Bunnhullstrykk [MPa]	Borehullstemperatur [°C]
1.0				133
2.0				

Test nummer	Olje produksjon [Sm <sup>3</sup> /dag]	Gass produksjon [Sm <sup>3</sup> /dag]	Oljetetthet [g/cm <sup>3</sup> ]	Gasstyngde rel. luft	GOR [m <sup>3</sup> /m <sup>3</sup> ]
1.0	53	10123	0.819		191
2.0	223	61447	0.819	0.810	279

### Logger

Type logg	Topp dyp for logg [m]	Bunn dyp for logg [m]
CST GR	4145	4829
CST GR	4147	4777
DLL MSFL BHC GR AMS	2133	4104
FMS GR	3112	4083
LDL CNL GR AMS	3088	4070
LDL CNL NGL AMS	4256	4859
MWD - GR RES DIR	274	4394
OBDT GR	4120	4857
PIL ASL GR AMS	3977	4856
RFT GR	3134	3530
RFT GR	4174	4715
VELOCITY	2255	4800

### Foringsrør og formasjonsstyrketester

Type utforing	Utforing diam. [tommer]	Utforing dybde [m]	Brønnbane diam. [tommer]	Brønnbane dyp [m]	LOT/FIT slam eqv. [g/cm <sup>3</sup> ]	Type formasjonstest
CONDUCTOR	30	158.0	36	160.0	0.00	LOT



## Faktasider

### Brønnbane / Leting

Utskriftstidspunkt: 15.5.2024 - 05:07

INTERM.	20	571.0	26	573.0	0.00	LOT
INTERM.	13 3/8	2130.0	17 1/2	2133.0	1.91	LOT
INTERM.	9 5/8	4117.0	12 1/4	4120.0	2.16	LOT
INTERM.	6 5/8	4847.0	8 1/8	4848.0	0.00	LOT

### Boreslam

Dybde MD [m]	Egenvekt, slam [g/cm3]	Viskositet, slam [mPa.s]	Flytegrense [Pa]	Type slam	Dato, måling
118	1.05			WATER BASED	
160	1.05			WATER BASED	
180	1.05			WATER BASED	
294	1.05			WATER BASED	
576	1.20			WATER BASED	
694	1.32	35.0		OIL BASED	
1178	1.32	38.0		OIL BASED	
1628	1.56	42.0		OIL BASED	
1991	1.70	32.0		OIL BASED	
2143	1.70	26.0		OIL BASED	
2146	1.70	38.0		OIL BASED	
2288	1.70	18.0		OIL BASED	
2473	1.70	18.0		OIL BASED	
2630	1.70	20.0		OIL BASED	
2724	1.70	19.0		OIL BASED	
2874	1.73	21.0		OIL BASED	
2983	1.73	22.0		OIL BASED	
2987	1.73	22.0		OIL BASED	
2998	1.73	23.0		OIL BASED	
3047	1.73	21.0		OIL BASED	
3125	1.73	22.0		OIL BASED	
3138	1.73	22.0		OIL BASED	
3200	1.73	21.0		OIL BASED	
3219	1.73	26.0		OIL BASED	
3341	1.73	21.0		OIL BASED	
3385	1.73	20.0		OIL BASED	
3487	1.73	24.0		OIL BASED	
3498	1.73	24.0		OIL BASED	
3532	1.73	22.0		OIL BASED	
3625	1.73	26.0		OIL BASED	



3678	1.73	26.0	OIL BASED	
3749	1.73	27.0	OIL BASED	
3772	1.73	26.0	OIL BASED	
3778	1.73	26.0	OIL BASED	
3783	1.75	26.0	OIL BASED	
3987	1.75	24.0	OIL BASED	
3999	1.75	24.0	OIL BASED	
4062	1.75	26.0	OIL BASED	
4073	1.75	23.0	OIL BASED	
4113	1.93	35.0	WATER BASED	
4116	1.75	22.0	OIL BASED	
4126	1.76	26.0	OIL BASED	
4146	2.00	52.0	WATER BASED	
4208	2.02	53.0	WATER BASED	
4256	2.02	49.0	WATER BASED	
4279	2.04	46.0	OIL BASED	
4299	2.02	44.0	WATER BASED	
4314	2.02	44.0	WATER BASED	
4315	2.04	45.0	WATER BASED	
4331	2.04	45.0	WATER BASED	
4362	2.06	49.0	WATER BASED	
4394	2.06	50.0	WATER BASED	
4394	2.06	49.0	WATER BASED	
4407	2.04	55.0	WATER BASED	
4414	2.06	49.0	WATER BASED	
4436	2.06	50.0	WATER BASED	
4450	2.06	50.0	WATER BASED	
4468	2.06	49.0	WATER BASED	
4479	2.06	49.0	WATER BASED	
4523	2.06	54.0	WATER BASED	
4542	2.04	48.0	WATER BASED	
4553	2.04	53.0	WATER BASED	
4554	2.04	52.0	WATER BASED	
4602	2.04	46.0	WATER BASED	
4657	2.04	43.0	OIL BASED	
4723	2.04	46.0	WATER BASED	
4849	2.04	42.0	WATER BASED	
4849	2.04	42.0	OIL BASED	



## Trykkplott

Porertrykksdataene kommer fra logging i brønnen hvis ingen annen kilde er oppgitt. I noen brønner der trykk ikke er logget, er det brukt informasjon fra formasjonstester eller brønnspark. Trykkdataene er rapportert inn til Oljedirektoratet og videre prosessert og kvalitetssikret av IHS Markit.

Dokument navn	Dokument format	Dokument størrelse [KB]
<a href="#">1756 Formation pressure (Formasjonstrykk)</a>	pdf	0.22

