



Generell informasjon

Brønnbane navn	2/7-15
Type	EXPLORATION
Formål	APPRAISAL
Status	P&A
Faktakart i nytt vindu	lenke til kart
Hovedområde	NORTH SEA
Felt	ELDFISK
Funn	2/7-8
Brønn navn	2/7-15
Seismisk lokalisering	PG 2/7-K SP.12
Utvinningstillatelse	018
Boreoperatør	Phillips Petroleum Company Norway
Boretillatelse	239-L
Boreinnretning	HAAKON MAGNUS
Boredager	125
Borestart	29.01.1980
Boreslutt	02.06.1980
Frigitt dato	02.06.1982
Publiseringsdato	26.10.2009
Opprinnelig formål	WILDCAT
Gjenåpnet	NO
Innhold	OIL
Funnbrønnbane	NO
1. nivå med hydrokarboner, alder	PALEOCENE
1. nivå med hydrokarboner, formasjon.	EKOFISK FM
2. nivå med hydrokarboner, alder	LATE CRETACEOUS
2. nivå med hydrokarboner, formasjon	TOR FM
Avstand, boredekk - midlere havflate [m]	25.0
Vanndybde ved midlere havflate [m]	69.0
Totalt målt dybde (MD) [m RKB]	4423.0
Totalt vertikalt dybde (TVD) [m RKB]	4423.0
Maks inklinasjon [°]	1.2
Temperatur ved bunn av brønnbanen [°C]	151
Eldste penetrerte alder	LATE JURASSIC



Eldste penetrerte formasjon	HAUGESUND FM
Geodetisk datum	ED50
NS grader	56° 23' 46.82" N
ØV grader	3° 18' 54.63" E
NS UTM [m]	6250375.82
ØV UTM [m]	519456.06
UTM sone	31
NPDID for brønnbanen	225

Brønnhistorie

General

Well 2/7-15 was drilled on the Eldfish East structure in the Feda Graben of the southern North Sea. The well was an appraisal of the productive Danian - Late Cretaceous chalks found in 2/7-8. The well also had an explorative objective, namely to prove the existence of productive Jurassic sandstones on the East Eldfish structure. Projected total depth was 14500 ft (4420 m).

The well is Reference well for the Ran Sandstone Units.

Operations and results

Well 2/7-15 was spudded with the semi-submersible installation Haakon Magnus (now Borgsten Dolphin) on 29 January 1980 and drilled to TD at 4423 m in the Late Jurassic Haugesund Formation. A 2.3 Sm3 influx was taken while drilling at 3667.7 m (3672.8 m logger's depth) in the Farsund Formation. The well was shut in. After shut-in the circulation was lost, probably because the formation broke down. The circulation was resumed by appropriate mud adjustments, and the return mud then contained 3% oil and was slightly gas-cut. The well was drilled with bentonite, Flosal and lime down to 503 m, with Drispac mud from 503 m to 1387 m, and with Drispac/lignosulphonate mud from 1387 m to TD.

The Danian - Late Cretaceous section tested small quantities of hydrocarbons. Shows were encountered, often in fractures, on cored siltstone and claystone in the Early Cretaceous Ran Sandstone Units and Åsgard Formation, but testing proved the section to be generally tight. The logs indicated a 2 m HC-bearing sandstone stringer at 3672.8 m (where the influx was taken while drilling), but no shows were reported from this depth. Isolated shows, in the form of dull yellow fluorescence, were reported also on cored claystone in the Farsund Formation at 4030 m and 4035 m. The 48 m thick Eldfish Formation at 4133 m had somewhat lower gamma ray readings than the Farsund Formation above and Haugesund Formation below, but the lithology was mainly shale/claystone with only traces of sandstone.

Seven conventional cores were taken. The six first were cut consecutively in the interval from 3481.5 m in the Ran Sandstone Units and down to 3554.6 m in the Åsgard Formation. Core no 7 was cut at 4027.7 - 4039.6 m in the Farsund Formation. No wire line fluid samples were taken.

The well was permanently abandoned on 2 June 1980 as an oil appraisal.

Testing

Three zones were drill stem tested between 19 and 27 May 1980. These were both the Early and Late Cretaceous zones, and the Danian. All zones were perforated with two



shots per foot. The following results are after acidizing:

DST 1 perforated the intervals 3450.3 - 3454.0 m, 3463.1 - 3466.2 m, 3471.1 - 3473.5 m, 3475.3 - 3478.4 m, and 3482.6 - 3487.5 m in the Ran Sandstone. During the 4 3/4 hour flow period the well failed to clean up. Final bottom hole flowing pressure at 3443.3 m was 4076 psig on 64/64" choke, and the maximum temperature was 247 def F (119.4 deg C). Only traces of oil and gas were observed, and the water was measured at 104 Sm3/day. The well was shut in for 4 1/3 hours before the packer was unseated for a maximum bottom hole pressure of 9632 psig

DST 2 perforated the interval 3031.2 - 3035.8 m in the Late Cretaceous Tor Formation. The well was flowed for 5.07 hours on 36/64" choke. Final bottom hole flowing pressure at 3026.1 m was 4347 psig and the last measured rate was 50.4 Sm3 water and 6.8 Sm3 oil/day. Maximum temperature was 217 deg F (102.8 deg C). The pressure built up to 6645 psig during a 5.8 hours shut in period.

DST 3 perforated the intervals 3013.3 - 3022.4 m (Ekofisk Formation) and 3031.2 - 3035.8 m (Tor Formation) for a commingled test. The well was flowed for 13.13 hours on 32/64" choke. Final bottom hole flowing pressure was 3934 psig at 3014.2 m. The final rate was 32.8 Sm3 water and 13.4 Sm3 oil/day. Maximum temperature was 218 deg F (103.3 deg C). After 16 hours build up the bottom hole pressure was 6443 psig.

Borekaks i Sokkeldirektoratet

Borekaksprøve, topp dybde [m]	Borekaksprøve, bunn dybde [m]
515.00	4423.00
Borekaks tilgjengelig for prøvetaking?	YES

Borekjerner i Sokkeldirektoratet

Kerneprøve nummer	Kerneprøve - topp dybde	Kerneprøve - bunn dybde	Kerneprøve dybde - enhet
1	11422.0	11459.0	[ft]
2	11459.0	11472.0	[ft]
3	11474.0	11514.0	[ft]
4	11514.0	11562.0	[ft]
5	11562.0	11602.0	[ft]
6	11602.0	11619.0	[ft]
7	13214.0	13246.6	[ft]

Total kjerneprøve lengde [m]	69.4
Kjerner tilgjengelig for prøvetaking?	YES

Palynologiske preparater i Sokkeldirektoratet



Prøve dybde	Dybde enhet	Prøve type	Laboratorie
3465.0	[m]	DC	HRS
3526.0	[m]	DC	HRS
3572.0	[m]	DC	HRS
3581.0	[m]	DC	HRS
3590.0	[m]	DC	HRS
3603.0	[m]	DC	HRS
3618.0	[m]	DC	HRS
3630.0	[m]	DC	HRS
3651.0	[m]	DC	HRS
3670.0	[m]	DC	HRS
3690.0	[m]	DC	HRS
3712.0	[m]	DC	HRS
3734.0	[m]	DC	HRS
3755.0	[m]	DC	HRS
3776.0	[m]	DC	HRS
3795.0	[m]	DC	HRS
3816.0	[m]	DC	HRS
3837.0	[m]	DC	HRS
3859.0	[m]	DC	HRS
3880.0	[m]	DC	HRS

Litostratigrafi

Topp Dyb [mMD RKB]	Litostrat. enhet
94	NORDLAND GP
1689	HORDALAND GP
2898	ROGALAND GP
2898	BALDER FM
2911	SELE FM
2950	LISTA FM
2982	VÅLE FM
3008	SHETLAND GP
3008	EKOFISK FM
3029	TOR FM
3136	HOD FM
3368	BLODØKS FM
3372	HIDRA FM
3419	CROMER KNOLL GP



3419	RØDBY FM
3450	RAN SANDSTONE UNITS
3498	ÅSGARD FM
3584	TYNE GP
3584	MANDAL FM
3606	FARSUND FM
4133	ELDFISK FM
4181	HAUGESUND FM

Geokjemisk informasjon

Dokument navn	Dokument format	Dokument størrelse [KB]
225_1	pdf	2.14
225_2	pdf	3.58
225_3	pdf	10.55

Dokumenter - eldre Sokkeldirektoratets WDSS rapporter og andre relaterte dokumenter

Dokument navn	Dokument format	Dokument størrelse [KB]
225_01_WDSS_General_Information	pdf	0.26
225_02_WDSS_completion_log	pdf	0.25

Dokumenter - rapportert av utvinningstillatelsen (frigitt ihht til regelverk)

Dokument navn	Dokument format	Dokument størrelse [KB]
225_01_2_7_15_Completion_report	pdf	22.32

Borestrengtester (DST)

Test nummer	Fra dybde MD [m]	Til dybde MD [m]	Reduksjonsven til størrelse [mm]
1.0	3425	3462	25.4
2.0	3006	3010	14.3
3.0	2988	3010	13.4





Faktasider

Brønnbane / Leting

Utskriftstidspunkt: 10.5.2024 - 19:00

Test nummer	Endelig avstengningstrykk [MPa]	Endelig strømningstrykk [MPa]	Bunnhullstrykk [MPa]	Borehullstemperatur [°C]
1.0	66.000	30.000		
2.0	46.000	30.000		
3.0	44.000	30.000		

Test nummer	Olje produksjon [Sm3/dag]	Gass produksjon [Sm3/dag]	Oljetetthet [g/cm3]	Gasstyngde rel. luft	GOR [m3/m3]
1.0					
2.0		7			
3.0		13			

Logger

Type logg	Topp dyp for logg [m]	Bunn dyp for logg [m]
DLL BHC GR CAL	3179	3683
DLL BHC GR CAL	3692	4429
FDC CNL GR CAL	2743	2190
FDC CNL GR CAL	3179	3684
FDC CNL GR CAL	3691	4430
GR	0	61
HDT	1369	3190
HDT	3179	3702
HDT	3693	4423
ISF MSFL BHC GR CAL	487	1322
ISF MSFL BHC GR CAL	1368	3191
VELOCITY	1369	4420

Foringsrør og formasjonsstyrketester

Type utforing	Utforing diam. [tommere]	Utforing dybde [m]	Brønnbane diam. [tommere]	Brønnbane dyp [m]	LOT/FIT slam eqv. [g/cm3]	Type formasjonstest
CONDUCTOR	30	128.0	36	128.0	0.00	LOT
SURF.COND.	20	464.0	26	478.0	1.14	LOT
INTERM.	13 3/8	1342.0	17 1/2	1362.0	1.92	LOT
INTERM.	9 5/8	3150.0	12 1/4	3160.0	1.98	LOT
LINER	7	3664.0	8 1/2	3674.0	2.19	LOT



OPEN HOLE		4398.0	5 7/8	4398.0	0.00	LOT
-----------	--	--------	-------	--------	------	-----

Boreslam

Dybde MD [m]	Egenvekt, slam [g/cm3]	Viskositet, slam [mPa.s]	Flytegrense [Pa]	Type slam	Dato, måling
153	1.02	100.0		WATER BASED	02.06.1980
382	1.02	100.0		WATER BASED	02.06.1980
655	1.02	35.0		WATER BASED	02.06.1980
1089	1.22	40.0		WATER BASED	02.06.1980
1289	1.77	47.0		WATER BASED	02.06.1980
1387	1.24	43.0		WATER BASED	02.06.1980
1859	1.76	54.0		WATER BASED	02.06.1980
2165	1.76	54.0		WATER BASED	02.06.1980
2785	1.75	59.0		WATER BASED	02.06.1980
3042	1.71	58.0		WATER BASED	02.06.1980
3185	1.71	44.0		WATER BASED	02.06.1980
3493	1.23	55.0		WATER BASED	02.06.1980
3629	1.78	58.0		WATER BASED	02.06.1980
3699	1.94	58.0		WATER BASED	02.06.1980
3860	1.94	52.0		WATER BASED	02.06.1980
3995	1.94	58.0		WATER BASED	02.06.1980
4027	1.94	62.0		WATER BASED	02.06.1980
4216	1.80	80.0		WATER BASED	02.06.1980
4349	1.93	55.0		WATER BASED	02.06.1980
4423	1.93	57.0		WATER BASED	02.06.1980

Trykkplott

Porertrykksdataene kommer fra logging i brønnen hvis ingen annen kilde er oppgitt. I noen brønner der trykk ikke er logget, er det brukt informasjon fra formasjonstester eller brønnspark. Trykkdataene er rapportert inn til Oljedirektoratet og videre prosessert og kvalitetssikret av IHS Markit.

Dokument navn	Dokument format	Dokument størrelse [KB]
225 Formation pressure (Formasjonstrykk)	pdf	0.23

